Time ralay for starting star - delta TRA-GT



www.mikrobest.pl

Time ralay for starting 2 relays output 2 x SPDT



General characteristics


- Electronic time relay
- 2 relays output with 1 changeover contact (SPDT)
- Green LED for star relay state
- Yellow LED for delta relay state
- Modular DIN 35mm

Order code	Time of scale range for star starting 0,25s-12m	Rated auxiliary supply voltage	Qty per pkg
TRA-GT	Time of scale range for transition 0,1s-0,3s	V 24 V AC/DC	1
		230 V AC	

Function

Starting STAR-DELTA
When the input voltage U is applied, timing delay T1 begins.
Relay contacts Rg change state immediately and timing cycle begins.
Contacts Rg return to their shelf state after time T1. After time T2 relay contacts Rt change state.

Contacts Rt return to their shelf state when input voltage U is removed.



Time rangers


STAR: 0,25s - 12m TRANSITION: 0,1s - 0,3s

x₁m

x8s

x1s

x0,25s



Technical parameters

Supply terminals: A1 - A2 230VAC


C1 - A2 24V AC/DC

Supply voltage tolerance: 0,8 - 1,1 % Consumption: max 8VA 5A/250V AC1 Current rating: 5A/24V DC1

5%

Time deviation: Protection degree: IP20

Dimensions: 90 x 35 x 70mm



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Timers category:

Click to view products by Mikrobest manufacturer:

Other Similar products are found below:

79237785 H3DS-GL AC24-230/DC24-48 H5AN-4DM DC12-24 H5CN-XDNM AC100-240 H5CN-YAN AC100-240 H5CX-L8S-N AC100-240 H3AMNSCAC100240 H3AM-NSR-B AC100-240 H3CA-8 DC12 H3CR-A8-302 DC24 H3CR-F AC24-48/DC12-48 H3CR-G8EL AC200-240 H5AN-4D DC12-24 81506944 88225029 H5S-YB4-X H3CR-A-301 AC100-240/DC100-125 H3CR-AS AC24-48/DC12-48 H3DK-GE AC240-440 H3RN-2 AC24 H3RN-21 AC24 H3CR-H8RL AC/DC24 M H3CR-H8RL AC100-120 S H3CR-G8EL-31 AC100-120 H3CR-H8RL AC100-120 M H3CR-A8-301 AC24-48/DC12-48 H3CR-H8RL AC/DC24 S H7AN-2D DC12-24 H5CN-XANS DC12-48 H3CA-8 DC110 H7AN-W4DM DC12-24 H7AN-4DM DC12-24 H7AN-4D DC12-24 H7AN-RT6M AC100-240 H3CA-8H AC200/220/240 MTR17-BA-U240-116 PM4HSDM-S-AC240VS PM4HSDM-S-AC240VSW PO-405 600DT-CU H3Y-2-B DC24 30S PM4HF8-M-DC24V PM4HS-H-DC12VSW H3Y-2-B AC100-120 10S H3Y-2-B AC100-120 30S H3C-R H3CR-A8-301 24-48AC/12-48DC H3CR-A8E 24-48AC/DC H3CR-F8 100-240AC/100-125DC