




ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE5812 thru NTE5817 6 Amp Plastic Silicon Rectifier

Features:

- Diffused Junction
- Low Forward Voltage Drop
- High Current Capability
- High Reliability
- High Surge Current Capability



Maximum Ratings and Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified. Single phase half sine-wave 60Hz resistive or inductive load. For capacitive load, derate current by 20%)

Maximum Peak Repetitive Reverse Voltage, V_{RRM}	
NTE5812	100V
NTE5814	400V
NTE5815	600V
NTE5817	1000V
Maximum Working Peak Reverse Voltage, V_{RWM}	
NTE5812	100V
NTE5814	400V
NTE5815	600V
NTE5817	1000V
Maximum RMS Voltage, $V_{R(RMS)}$	
NTE5812	70V
NTE5814	280V
NTE5815	420V
NTE5817	700V
Maximum DC Blocking Voltage, V_R	
NTE5812	100V
NTE5814	400V
NTE5815	600V
NTE5817	1000V
Maximum Average Forward Rectified Current ($T_A = +60^\circ\text{C}$, Note 1), I_O	6A
Non-Repetitive Peak Forward Surge Current, I_{FSM}	
8.3ms single half sine-wave superimposed on rated load	400A
Forward Voltage ($I_F = 6A$), V_{FM}	1V
Peak Reverse Current at Rated DC Blocking Voltage, I_{RM}	
$T_J = +25^\circ\text{C}$	5 μ A
$T_J = +100^\circ\text{C}$	1mA
Typical Junction Capacitance (Note 2), C_j	150pF
Typical Thermal Resistance, Junction-to-Ambient (Note 1), R_{thJA}	20 $^\circ\text{C}/\text{W}$
Operating Junction Temperature Range, T_J	-50 $^\circ$ to +150 $^\circ\text{C}$
Storage Temperature Range, T_{stg}	-50 $^\circ$ to +150 $^\circ\text{C}$

Note 1. Lead maintained at ambient temperature at a distance of 9.5mm from the case.

Note 2. Measured at 1MHz and applied reverse voltage of 4V DC.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for NTE manufacturer:

Other Similar products are found below :

[747](#) [797](#) [868](#) [1724](#) [NEH680M50FE](#) [NEHH1.0M450CB](#) [NTE526A](#) [228A](#) [231](#) [954](#) [2023](#) [510](#) [WH20-04-25](#) [04-SLPE3750A](#) [5615](#) [591](#) [69-](#)
[36WW-WR-KIT](#) [7056](#) [7448](#) [NEH.10M50AA](#) [NEH2.2M63AA](#) [NEH330M35DD](#) [NEH33M10AA](#) [NEV.22M100AA](#) [NEV470M50FF](#)
[NTE133](#) [NTE542](#) [NTE74154](#) [R02-11A10-120H](#) [04-SCBW25L-BK](#) [04-SCBW6C-BK](#) [04-SCBW32L-BK](#) [04-SCW10C-BK](#) [04-SCBW19L-](#)
[GR](#) [04-SCW19L-WH](#) [04-SCW19L-OR](#) [04-SCW38L-WH](#) [04-SCBW50L-OR](#) [04-SCBW50L-GR](#) [04-SCW10C-GR](#) [04-SCW10C-OR](#) [04-](#)
[SCBW32L-GR](#) [04-SCBW32L-WH](#) [04-SCBW32L-OR](#) [04-SCBW6C-WH](#) [04-SCBW6C-GR](#) [04-SCBW6C-OR](#) [04-SCBW25L-GR](#) [04-](#)
[SCBW25L-WH](#) [04-ESNF-500L](#)