

## This document was generated on 09/29/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number:                    | 0740621012   |   | •   |
|---------------------------------|--|---|---|
| Status:                         | Active   |   | APA   |
| Overview: VHDM® Backplane C     |  | nnastar Svetama   |   |
| escription:                     |  |   |   |
| escription:                     | 2.00mm Pitch VHDM® Single-Ended Board-to-Board Backplane Header, Vertical, 8-<br>Row, Guide Pin Signal Module, Shield End Version, 80 Circuits, Pin Length 6.25mm, |   |   |
|                                 |  | on A. Series:74075 Enables designers to create custom loaded    | 1045858884  |
|                                 |  | standard pin lengths 4.25, 4.75, 5.15 and 6.25mm25, 4.75, 5.15  | 3388885   |
|                                 | and 6.25mm   | sanuaru piri lengiris 4.25, 4.75, 5.15 anu 6.25mm25, 4.75, 5.15 | 13138   |
|                                 | and 6.25mm   |   | 100033  |
|                                 |  |   | The start   |
| Documents:                      |  |   |   |
| <u>3D Model</u>                 |  | Packaging Specification PK-74061-003 (PDF)                      | Series image - Reference only                     |
| Drawing (PDF)                   |  | RoHS Certificate of Compliance (PDF)                            |   |
| Product Specification           | on PS-74031-999 (PDF)  |   | EU ELV  |
|                                 |  |   | Not Relevant                                      |
| Agency Certificati              | ion  |   |   |
| UL                              |  | E29179  | EU RoHS China RoHS                                |
| Conorol                         |  |   | Not Compliant                                     |
| General<br>Broduct Fomily       |  | Pagkalang Consectors  | REACH SVHC  |
| Product Family                  |  | Backplane Connectors  | Not Contained Per -                               |
| Series                          |  | 74062<br>Backplane  | ED/21/2016 (20 June                               |
| Application                     | Decumente  | •   | 2016)   |
| Application Tooling<br>Comments | Documents  | TM-622010999  | Halogen-Free                                      |
|                                 |  | Keying Position A<br>PCB Header                                 | <u>Status</u>                                     |
| Component Type<br>Overview      |  |   | Low-Halogen                                       |
| Product Name                    |  | VHDM® Backplane Connector Systems<br>VHDM®                      | Need more information on product                  |
| UPC                             |  | 800754881791  | environmental compliance?                         |
| UFC                             |  | 000754001791  | Email productcompliance@molex.com                 |
| Physical                        |  |   | Please visit the <u>Contact Us</u> section for an |
| Circuits (Loaded)               |  | 80  | non-product compliance questions.                 |
| Circuits (maximum)              | )  | 80  |   |
| Color - Resin                   | ,  | Black   | China ROHS 50 Image                               |
| Durability (mating o            | cycles max)  | 200   | ELV Not Relevant                                  |
| First Mate / Last Br            |  | No  |   |
| Flammability                    |  | 94V-0   |   |
| Guide to Mating Pa              | art  | Yes   | Search Parts in this Series                       |
| Keying to Mating Pa             |  | Yes   | 74062 Series                                      |
| Material - Metal                |  | Beryllium Copper, High Performance Alloy (HPA),                 |   |
|                                 |  | Stainless Steel   | Mates NA/:44                                      |
| Material - Plating M            | lating   | Gold  | Mates With  |
| Material - Plating T            | ermination   | Tin-Lead  | 74040 VHDM® Board-to-Board                        |
| Material - Resin                |  | High Temperature Thermoplastic                                  | Daughtercard Receptacle                           |
| Net Weight                      |  | 9.300/g   |   |
| Number of Column                | S  | 10  | Application Tooling   FAQ                         |
| Number of Pairs                 |  | Open Pin Field  | Tooling specifications and manuals are            |
| Number of Rows                  |  | 8   | found by selecting the products below.            |
| Orientation                     |  | Vertical  | Crimp Height Specifications are then              |
| PC Tail Length                  |  | 2.50mm  | contained in the Application Tooling              |
| PCB Locator                     |  | No  | Specification document.                           |
| PCB Retention                   |  | None  | Global  |
| PCB Thickness - R               | ecommended   | 1.80mm  | Description Product #                             |
| Packaging Type                  |  | Tube  | Insertion Module 0622020209                       |
| Pitch - Mating Inter            |  | 2.00mm  | for Standard Shield                               |
| Pitch - Termination             |  | 1.00mm  | Signal Header, 8-                                 |
| Plating min - Mating            |  | 0.762µm   | Row by 10-Wide,                                   |
| Plating min - Termi             | nation   | 0.762µm   | 20.00mm   |
| Polarized to PCB                |  | Yes   |   |

Surface Mount Compatible (SMC) Temperature Range - Operating Termination Interface: Style

#### Electrical

Current - Maximum per Contact Data Rate Shield Type Shielded Voltage - Maximum

Solder Process Data Lead-freeProcess Capability

**Material Info** 

# **Reference - Drawing Numbers**

Yes -55°C to +105°C Through Hole - Compliant Pin

3.0A 3.125 Gbps Ground Plane Shield Yes 120V AC (RMS)/DC

N/A

Signal Pin Inserter 0622015700 Repair Tool 8-Row Pin and 0622015900 Shield Repair Tool Insertion Module 0622020205 for Advanced Mate Signal Header, 8-Row by 10-Wide, 20.00mm 8-Row Shield 0622016100 **Extraction Tool** 

Packaging Specification PK-74061-003 **Product Specification** PS-74031-999 Sales Drawing SD-74062-002 Note: HDM, HDM+, VHDM, VHDM-HSD and GbX are trademarks or registered trademarks of Amphenol TCS.

### This document was generated on 09/29/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 88911-201LF 9514M0C20D 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0740618502 0760151403 0760551105 0760551608 0761451128 0761651124 0761655108 0761659807 0769853208 0736440217 0758324203