



GENERAL DATA:

DROP IN PERFORMANCE (UVA)	AFTER 500 HOURS <25%
RADIANT FLUX TYPICAL	
{UV-A} 315-400nm	APPROX. 75W
{UV-B} 280-315nm	APPROX. 10W
{UV-C} 200-280nm	APPROX. 3W
TEMP OF DISCHARGE TUBE	MIN/MAX 700°C/950°
PRESS TEMP (MAX)	350°C
BURNER POSITION	HORIZONTAL ±10°
DISCHARGE TUBE MATERIAL	QUARTZ NON-OZONE FORMING
BASE	R7S

ELECTRICAL DATA:

BURNER RATING	380W APPROX.
BURNER VOLTAGE	135V ±15
BURNER CURRENT	3.2A
IGNITION VOLTAGE (MIN)	3-4.5 kV

LOCTITE.

ROCKY HILL, CT 06067

TITLE BULB, 400W U.V.
97246

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [loctite](#) manufacturer:

Other Similar products are found below :

[37684](#) [2257357](#) [2139180](#) [LOC-MIKSER2](#) [406](#) [5366, 310ML](#) [603, 10ML](#) [403, 50G](#) [2472691](#) [2701, 50ML](#) [542, 250ML](#) [572, 50ML](#) [3526](#)
[8106, 1L](#) [5800, 50ML](#) [MM01057](#) [1188112](#) [LOC-5615/400ML](#) [97262](#) [983438](#) [3463, 114G](#) [2700, 50ML](#) [648, 50ML](#) [40945](#) [MM01056](#)
[386862](#) [984569](#) [5400, 50ML](#) [5990, 40ML](#) [SUPERLUBE OIL, 375ML](#) [MM01939](#) [290](#) [98472](#) [GC 10 TYPE 3 \(JAR\)](#) [660, 50ML](#) [SUPER](#)
[GLUE GLASS, 3G](#) [LOC-MIKSER](#) [6300, 50ML](#) [2023641](#) [LT 5075](#) [GC 10 TYPE 4 \(JAR\)](#) [495, 50G](#) [243, 250ML](#) [LOC-638-10](#) [641, 10ML](#)
[496, 50G](#) [2472659](#) [98473](#) [5660, 40ML](#) [4080, 50G](#)