

RACK- AND PANEL-MOUNT POWER DISTRIBUTION UNITS (PDUS)



INDUSTRY STANDARDS

UL/cUL 60950 listed UL 1449 (Surge protector models only)

EIA 310-D (19-in. rack-mount models only)

APPLICATION

Rack- and Panel-Mount PDUs not only provide convenient, reliable power to equipment mounted in cabinets or on open frame racks, they can also be configured to meet a wide range of design specifications.

FEATURES

- Power on/off LED indicates whether power is available at the PDU
- External ground stud provided on single-phase models for secure
- Circuit breakers provide additional equipment protection
- Circuits are isolated on dual circuit model; each has its own circuit breaker
- Reset button provides easy access to circuit breaker reset
- Surge protector models have an indicator LED to verify surge circuitry protection
- Rack-mount models mount directly to rack or with adapter bracket
- Rack-mount models designed for single-phase applications Panel-mount models can be mounted flush or with hanging bracket
- Panel-mount models available for both one- and three-phase applications
- Three-phase models have three 20 A, double-pole magnetic breaker/switches with an integral switch guard

SPECIFICATIONS

- · Steel housing
- Power cord with molded-on plug:
- 12-in. (305-mm) long single-phase model: 6 ft. (1.8 m)
- Other single-phase models: 15 ft. (4.6 m)
- Three-phase models: 10 ft. (3 m)

Contact Hoffman for custom modifications and non-standard offerings.

Black, low-gloss textured paint.

BULLETIN: DPS

Standard Product Single-Phase Rack-Mount

| | Surge | Amp | Load | Voltage | Joule | | No. of | | | Rack |
|----------------|------------|-------|--------|---------|--------|---------------------|-------------|------------------|------------------------|-------|
| Catalog Number | Protection | Meter | Rating | (VAC) | Rating | Receptacle Location | Receptacles | Receptacle Style | Power Cord Plug | Units |
| DP1N190615 | No | No | 15A | 120 | _ | Front | 6 | NEMA 5-15R | NEMA 5-15P | 1 |
| DP1N191415 | No | No | 15A | 120 | _ | 6 front, 8 back | 14 | NEMA 5-15R | NEMA 5-15P | 1 |
| DP1N191415M | No | Yes | 15A | 120 | _ | 6 front, 8 back | 14 | NEMA 5-15R | NEMA 5-15P | 1 |
| DP1N191015S | Yes | No | 15A | 120 | 2000 | 2 front, 8 back | 10 | NEMA 5-15R | NEMA 5-15P | 1 |
| DP1N191020 | No | No | 20A | 120 | _ | 2 front, 8 back | 10 | NEMA 5-20R | NEMA 5-20P | 1 |
| DP1N191020S | Yes | No | 20A | 120 | 2000 | 2 front, 8 back | 10 | NEMA 5-20R | NEMA 5-20P | 1 |
| DP1N191020ST | Yes | No | 20A | 120 | 2000 | 2 front, 8 back | 10 | NEMA 5-20R | NEMA L5-20P Twist Lock | 1 |
| DP1N191420 | No | No | 20A | 120 | _ | 6 front, 8 back | 14 | NEMA 5-20R | NEMA 5-20P | 1 |

Isolated circuits on dual-circuit models with separate circuit breakers.

Plugs and Receptacles

| NEMA Type | Plug | Receptacle |
|-------------------------------------|---------|------------|
| NEMA 15 Amp, 120V, Duplex | 5-15P | 5-I5R |
| NEMA 20 Amp, I20V, Duplex | 5-20P | 5-20R |
| NEMA 20 Amp, I 20V, Twist Lock | L5-20P | L5-20R |
| 30 Amp, I20/208V Wye, Twist Lock | L21-30P | L21-30R |

| IEC Туре | Inlet | Outlet |
|-----------------------|-------|--------|
| IEC 15 Amp, 125/250V | C-14 | C-13 |
| IEC 20 Amp, I 25/250V | C-20 | C-19 |

87922518



Standard Product Single-Phase Vertical-Mount

| | Length | Length | Surge | Amp | Load | Voltage | Joule | No. of | | |
|----------------|--------|--------|------------|-------|--------|---------|--------|-------------|-------------------------|------------------------|
| Catalog Number | (in.) | (mm) | Protection | Meter | Rating | (VAC) | Rating | Receptacles | Receptacle Style | Power Cord Plug |
| DP1N120615 | 12.00 | 305 | No | No | 15A | 120 | _ | 6 | NEMA 5-15R | NEMA 5-15P |
| DP1N160620S | 16.00 | 406 | Yes | No | 20A | 120 | 2000 | 6 | NEMA 5-20R | NEMA 5-20P |
| DP1N481815 | 48.00 | 1219 | No | No | 15A | 120 | _ | 18 | NEMA 5-15R | NEMA 5-15P |
| DP1N622415 | 62.00 | 1575 | No | No | 15A | 120 | _ | 24 | NEMA 5-15R | NEMA 5-15P |
| DP1N622420 | 62.00 | 1575 | No | No | 20A | 120 | _ | 24 | NEMA 5-20R | NEMA 5-20P |
| DP1N622420T | 62.00 | 1575 | No | No | 20A | 120 | _ | 24 | NEMA 5-20R | NEMA L5-20P Twist Lock |
| DP1E2663030MT | 66.00 | 1676 | No | Yes | 30A | 250 | _ | 30 | 24 IEC C-13, 6 IEC C-19 | NEMA L6-30P Twist Lock |

Isolate circuits on dual circuit models with separate circuit breakers.

DP1E2663030MT is Ethernet metered; SNMP trap provides remote current monitoring via Ethernet.

Standard Product Three-Phase Vertical-Mount

| Catalog Number | Length (in.) | Length (mm) | Amp Meter | Load Rating | Voltage (VAC) | No. of Outlets per Phase | Total Outlets per PDU | Required Inlet Style | Power Cord Plug |
|----------------|-----------------|----------------|--------------|----------------|------------------|--------------------------|-------------------------|----------------------|---------------------------------|
| DP3E2663635MT | 66.00 | 1676 | Yes | 35A | 250 | 10 IEC C-13. 2 IEC C-19 | 30 IEC C-13, 6 IEC C-19 | IEC C-14 and C-20 | CA style 50A 250 Vac Twist Lock |


DP3E2663635MT is Ethernet metered; SNMP trap provides remote current monitoring via Ethernet.

RACK-MOUNT PDU BRACKET

Allows rack-mount power strips to be mounted to cabinet sides without using up rack space. Made of plated steel. Includes two brackets and mounting hardware. Order power strip separately.

BULLETIN: DPS

| Catalog Number | Finish | Pkg. Qty. |
|----------------|--------|------------|
| A19PSMB | Plated | 2 brackets |



UNIVERSAL POWER STRIP BRACKET



This bracket fits in the corner of the frame of all PROLINE $^{\text{TM}}$ cabinets and facilitates mounting a variety of power strips.

BULLETIN: DPY

| Catalog Number | Description |
|----------------|---|
| EPDUBK | Universal Power Strip Bracket fits all PROLINE cabinets |
| | |

IEC CORD SETS



Cord sets help minimize cord tangle, increasing airflow to equipment.

BULLETIN: DPS

| Catalog Number | Description | Pkg. Qty. |
|----------------|---|-----------|
| DP5E | 0.5-m (1.64-ft.) IEC patch cord. 18/3 SJT Black. C-14 to C-13 | 10 |
| DP10E | 1-m (3.28-ft.) IEC patch cord, 18/3 SJT Black. C-14 to C-13 | 10 |

IEC C-13 RETAINING CLIP



Secures the IEC C-14 inlet into the C-13 outlet. Helps to prevent inadvertently unplugging the cord set

BULLETIN: DPS

| Catalog Number | Description | Pkg. Qty. |
|----------------|-------------------------|-----------|
| DPCLIP | IEC C-13 Retaining Clip | 10 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for hoffman manufacturer:

Other Similar products are found below:

A-1412CHQR CSD201610 CSD20168SS CSD20206 CSD20208SS CSD24168 CSD36248 CSD36308 PCU7 PDS76R PRA197TP PT126

A1008CHNFSS A10106CH A10106CHFL A10106PHCW A1066JFGQRR A1210CHNF A1212SC A1412CHNFSS A161208LP

A161410CH A16H12ALP A16P14 A16P16G A18P16AL A20H16BLP A20P16 A24H2408SSLP Q13138PCE A404CH A606CHNF

A606NF A806SC A845JFGR A864CHQRFGW A90P36F1 HJ1412HWPL2LG HJ1816HWPL2LG RHJ1210HWPL2LG AS125SS

ASE10X10X4 ASE12X12X4 E1PBG E2PBG E3PB LED24V15 LF230VD A10106PHC A10P8SS