

# Feather Touch



4-wire resistive touch panel  
designed for multi-touch  
gesturing applications

**Enabling low-cost, high  
reliability, easily integrated  
alternatives to Projected  
Capacitive Multi-Touch Panels**

- Standard 4-wire resistive touch panel structure, 3.5-inch to 17-inch panel size
- Special controller enabling 2-finger sensing
- Optimized for gesture recognition, pinch, expand, rotate, flick, swipe
- Ultra low input force: 0.02~0.3N
- Special top film technology provides user experience comparable to projected capacitive panels
- Film/Glass, Film/Film/Plastic structures available
- Touch window enables creative Industrial Design: flush surface, logo printing, special shapes supported
- Transparency 82%~90%
- Automotive temperature range available:  
-30~+85°C (operation)  
and -40~+95°C (storage)
- Anti-Newton Ring technology



shaping tomorrow with you

## Feather-Touch Specifications

Operation force	0.02~0.3N (initial, measuring point: center of the touch panel)	
Surface hardness of film	Pencil hardness $\geq$ 3H	JIS K-5400
Transparency	82%~90% typical	JIS K 7105
Haze	5%~10% typical	JIS K 7105 surface: anti-glare
Linearity	$\leq$ 1.5%	
Operation temperature	-5~60°C	
Operation humidity	20~90%RH	Maximum wet bulb temperature 38°C with no condensation
Storage temperature	-30~70°C	
Storage humidity	10~90%RH	Maximum wet bulb temperature 38°C with no condensation
Reliability	1 million finger inputs	Tapping at the same point by silicon rubber R8 hardness 60%

## Feather-Touch Panel Sizes

NC01111-T161	3.8-inch	NC01111-T202	8.4-inch
NC01111-T181	4.3-inch	NC01111-T222	10.4-inch
NC01101-T001	6.95-inch (automotive)	NC01111-T242	12.1-inch
NC01101-T021	6.5-inch (automotive)	NC01111-T081	12.1-inch wide
NC01101-T041	7-inch	NC01111-T261	15-inch
NC01101-T061	7-inch	NC01152-T021	15.3-inch wide
NC01101-T081	8-inch (automotive)	NC01111-T281	17-inch
NC01152-T101	7-inch wide		

## 4-Wire Dual Touch Controller Board & MCU

NC01850-B045RS	USB controller board	
NC01850-B040RS	I2C development test board	
Operation temperature	-5~60°C	
Operation humidity	20~90%RH	Maximum wet bulb temperature 38°C with no condensation
Storage temperature	-30~70°C	
Storage humidity	20~85%RH	Maximum wet bulb temperature 38°C with no condensation
Size	60mm x 30mm	
NC41120-0031	USB controller MCU	
NC41120-0030	I2C controller MCU	

## Contact

### North and South America

Fujitsu Components America, Inc.  
250 E. Caribbean Drive  
Sunnyvale, CA 94089 U.S.A.  
Tel: (1-408) 745-4900  
Fax: (1-408) 745-4970  
Email: components@us.fujitsu.com  
Web: <http://us.fujitsu.com/components/>

### Europe

Fujitsu Components Europe B.V.  
Diamantlaan 25  
2132 WV Hoofddorp  
Netherlands  
Tel: (31-23) 5560910  
Fax: (31-23) 5560950  
Email: info@fceu.fujitsu.com  
Web: [emea.fujitsu.com/components/](http://emea.fujitsu.com/components/)

### Asia Pacific

Fujitsu Components Asia Ltd.  
102E Pasir Panjang Road  
#01-01 Citilink Warehouse Complex  
Singapore 118529  
Tel: (65) 6375-8560 / Fax: (65) 6273-3021  
Email: fcal@fcal.fujitsu.com  
Web: <http://www.fujitsu.com/sg/services/micro/components/>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LCD Touch Panels](#) category:*

*Click to view products by [Fujitsu](#) manufacturer:*

Other Similar products are found below :

[69-502](#) [87-6001-221](#) [CABLE/RTP/USB](#) [98-0003-2211-9](#) [17-8041-226](#) [17-8041-227](#) [CABLE/RTP/RS232](#) [87-4011-201](#) [N010-0554-T352](#)  
[N010-0554-T504](#) [LCDAL04-0430TL0NCNTBR1.0](#) [FTAS00-8.4AS-4A](#) [FTAS00-10.6AW-4A](#) [FTAS00-5.7AS-4A](#) [FTAS00-15.6AW-4A](#)  
[FTAS00-10.4AS-4A](#) [FTAS00-12.1AN-4A](#) [TP01150A-4KB](#) [TP01121W-4KB](#) [TP01104A-4KB](#) [N010-0554-T814](#) [TP01121A-4KB](#)  
[TP01106W-4KB](#) [FTAS00-12.1AN-4](#) [98000334502](#) [FTAS00-12.1AW-4](#) [FTAS00-10.6AW-4](#) [TKU016CT-A100](#) [FTAS00-19AN-4](#) [FTAS00-](#)  
[15AN-4](#) [FTAS00-15.6AW-4](#) [FTAS00-12.1AW-4A](#) [17-8041-205](#) [98-0003-2514-6](#) [98-0003-2549-2](#) [98-0003-2602-9](#) [98-0003-2678-9](#) [17-](#)  
[8031-205](#) [17-8051-205](#) [17-8091-203](#) [17-8421-205](#) [17-8441-205](#) [17-8441-217](#) [17-8541-226](#) [17-8571-203](#) [17-8581-203](#) [17-8891-205](#) [17-](#)  
[8901-226](#) [17-9681-226](#) [29368](#)