

## DK Cable junction boxes



### cable entry via elastic membranes and integrated M 20 thread

- rated insulation voltage: 400 V
- degree of protection: IP 55
- degree of protection: IP 65 (ADM)
- material: thermoplastic
- colour: grey, RAL 7035





#### DN 2000

cable entry: 8 membranes, closed  
(sealing range: Ø 3-12 mm)  
integrated M 20 thread  
without terminals





#### DN 2030

included cable entry 3 ADM 20,  
(sealing range: Ø 6.5-13.5 mm)  
8 membranes, closed  
(sealing range: Ø 3-12 mm)  
integrated M 20 thread  
without terminals



#### DN 2035

5-pole,  
per pole 6 x 1.5 mm<sup>2</sup> sol, 4 x 2.5 mm<sup>2</sup> sol,  
3 x 4 mm<sup>2</sup> sol  
included cable entry 3 ADM 20,  
(sealing range: Ø 6.5-13.5 mm)  
8 membranes, closed  
(sealing range: Ø 3-12 mm)  
integrated M 20 thread



**Cable gland**  
**degree of protection: IP 65**  
colour: grey, RAL 7035  
material: thermoplastic

#### ADM 20

ISO thread                      sealing range  
M 20 x 1.5                      Ø 6.5-13.5 mm

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [hensel](#) manufacturer:*

Other Similar products are found below :

[Hensel](#)