



Features:

- Operating temperature : -55°C to +125°C
- Minimum shrink temperature : 70°C

Specification Table

Material	Colour	Unshrunk Diameter	Fully Shrunk Diameter	External Length / Height (m)	Shrunk Ratio
Polyolefin	Grey	1.6	0.8	100	2:1
		2.4	1.2		
		3.2	1.6		
		4.8	2.4		
		6.4	3.2		
		9.5	4.75		
		12.7	6.4		
		19	9.5		
		25.4	12.7	50	
		38.1	19.1		
		50.8	25.4	25	
		1.6	0.8	5	
		2.4	1.2		
		3.2	1.6		
		4.8	2.4		
		6.4	3.2		
		9.5	4.75		
		12.7	6.4		
		19	9.5		
		25.4	12.7		
38.1	19.1				
50.8	25.4				

Part Number Table

Description	Part Number
Heatshrink, 2:1, 1.6 mm, Grey, 100 m	13633GRY
Heatshrink, 2:1, 2.4 mm, Grey, 100 m	13634GRY
Heatshrink, 2:1, 3.2 mm, Grey, 100 m	13635GRY
Heatshrink, 2:1, 4.8 mm, Grey, 100 m	13636GRY
Heatshrink, 2:1, 6.4 mm, Grey, 100 m	13637GRY
Heatshrink, 2:1, 9.5 mm, Grey, 100 m	13638GRY
Heatshrink, 2:1, 12.7 mm, Grey, 100 m	13639GRY
Heatshrink, 2:1, 19 mm, Grey, 100 m	13640GRY
Heatshrink, 2:1, 25.4 mm, Grey, 50 m	13641GRY
Heatshrink, 2:1, 38.1 mm, Grey, 50 m	13642GRY
Heatshrink, 2:1, 50.8 mm, Grey, 25 m	13643GRY
Heatshrink, 2:1, 1.6 mm, Grey, 5 m	13644GRY
Heatshrink, 2:1, 2.4 mm, Grey, 5 m	13645GRY
Heatshrink, 2:1, 3.2 mm, Grey, 5 m	13646GRY
Heatshrink, 2:1, 4.8 mm, Grey, 5 m	13647GRY
Heatshrink, 2:1, 6.4 mm, Grey, 5 m	13648GRY
Heatshrink, 2:1, 9.5 mm, Grey, 5 m	13649GRY
Heatshrink, 2:1, 12.7 mm, Grey, 5 m	13650GRY
Heatshrink, 2:1, 19 mm, Grey, 5 m	13651GRY
Heatshrink, 2:1, 25.4 mm, Grey, 5 m	13652GRY
Heatshrink, 2:1, 38.1 mm, Grey, 5 m	13653GRY
Heatshrink, 2:1, 50.8 mm, Grey, 5 m	13654GRY

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Wire Identification](#) category.

Click to view products by [Pro Power](#) manufacturer.

Other Similar products are found below :

[0800368](#) [SEZ1DLL](#) [SEZ1CLL](#) [SDRBK](#) [S075X150VAC](#) [HTU6YG](#) [HTU6YE](#) [HTU6RE](#)
[HTU6OTV](#) [HTU6OFO](#) [HTDU2RE](#) [HTDU2OT](#) [HTDU2BW](#) [N100X125C2C](#)
[H200X044H3T](#) [H200X044H2T](#) [H200X034F1T](#) [Q621841](#) [H100X084F2T](#) [H100X044F13](#)
[H100X025H1T2](#) [H100X025F1TB](#) [H050X025H3T](#) [H050X025H1T](#) [H050X025F1T](#)