

Page 1/2 2013-12-04 Product Reference: **TY523MR**



Ty-Rap[®]

TY523MR

Premium cable tie with stainless steel locking barb to cover the most demanding applications.

 T&B Catalog Number:
 TY523MR

 EAN Number:
 05414363065371

 UPC Number:
 78621056475

Description: Premium, standard cable tie, 92 x 2.4 mm,

natural Polyamide 6.6









Technical Information	
Туре	standard
Material	Polyamide 6.6
Material Locking Barb	316 grade stainless steel
Temperature Range	-40°C to +85°C
Flammability Rating	UL 94 V-2
Colour	natural
Halogen free	yes
Silicone free	yes
Approvals	
UL listed	E49405
Germanischer Lloyd approval	yes
Lloyds Register approval	yes
MIL Spec.	MS-3367-4
Other approval	BVQ
Ordering Information	
Length (mm)	92
Width (mm)	2.4
Thickness (mm)	1
Max. Bundle Diameter (mm)	16
Min. Bundle Diameter (mm)	2
Min. Tensile Strength (N)	80
Quantity (pieces)	100
Packaging Type	Euroslot bag



Page 2/2 2013-12-04

Product Reference: TY523MR

Storage Conditions	Nylon (Polyamide) is inherently susceptible to environmental conditions. Polyamide 6.6 cable ties are moisturised to optimum performance levels at machine-side and should be stored in cool dry areas out of direct sunlight. Cable ties are packaged in plastic bags to contain moisture and should remain sealed until ready for use.
Tooling	ERG50, WT193A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Identification category:

Click to view products by ABB manufacturer:

Other Similar products are found below:

CU6337-000 CU6342-000 FCA-410-12 11631010 1-1768037-1 1-1768037-2 1-1768050-0 PXLK-VI Q62184-1 A64304-000 QMT221 HK032WE1NF038B 1330-0519-10 1395199-1 1395200-1 1395202-1 DMVF050WE-300S6 D-SCE-1K-2.4-50-4-CS7834 1538738-1 E90935-000 EC1238-000 EC1465-000 EC1855-000 EC1859-000 EC1863-000 EC5415-000 EC7277-000 EC7352-000 EC7603-000 EC7707-000 EC7735-000 EC7768-000 EC7828-000 EC7854-000 EC7952-000 EC8128-000 1768037-8 1768041-7 NC-127191-10-9 HS048WE2NF038B C03232-000 HTCM-SCE-14-4H-9 HTMS-3/16-9 HT-SCE-1/4-2.0-4 HT-SCE-3/16-2.0-4 HTTMS-1/2-1.50-9 HTTMS-CM-1/2-4H-9 HX-SCE-19.0-50-9 HX-SCE-6.4-50-4 C25254-000