



One smart printer to print it all

Content



BMP™71 Label Printer & Accessories 2



High Performance Industrial Identification / Safety Identification 10



General and Industrial Identification Labels 11



Wire And Cable Marking 16



Electrical Component Marking 22



Datacom Labels 23



Circuit Board and Component Identification Labels 27



Security Identification Labels 29



Laboratory Identification Labels 29



Brady products are sold on the condition that the purchaser will test them in actual use and determine for himself/herself their suitability to his/her intended purpose. Brady warrants to the purchaser that Brady products are free from defects in material and workmanship but limits its obligation under this warranty to the replacement of the product which has been shown to Brady's satisfaction to have been defective at the time of its purchase.

The warranty does not extend to any persons who have acquired the product from the purchaser. It is in lieu of any other warranty, including every warranty of sale-ability, marketability or suitability for the intended purpose, and is also in lieu of any other obligation or liability on the part of Brady.

Under no circumstances will Brady be liable for losses, damage, costs or subsequent damage of whatever nature which may arise in connection with the use of, or inability to use, Brady's products.

BMP™71 LABEL PRINTER



The BMP71 mobile label printer can print on more than 30 different types of label material – all designed with Brady’s industrial-strength durability. Whether you need heat shrink sleeves, die-cut labels or indoor/outdoor vinyl, you can be confident that the BMP71 printer has the right label material for your application.

Speed up your labelling

The powerful BMP71 prints faster than any other printer in it’s class (38 mm/sec). Don’t wait longer than necessary for your labels.

The full keyboard lets you type labels in less time

The BMP71 has a full keyboard, available in 4 different versions: QWERTY, AZERTY, QWERTZ and CYRILLIC. Use both your hands to type your label instead of one finger and save time!

The enlarged full colour screen makes your label printing so much easier

The enlarged screen of the BMP71 enables to see the whole label at once, helping you to compose the label in the most efficient way, eliminating trial and error!

One smart printer to print it all

The BMP71 is your essential tool that handles all your label printing needs.




Order Reference	Description
BMP71-QWERTY-UK	Printer, Hard Carry Case, 2 Label Rolls, 1 Black Ribbon Cartridge, Rechargeable Battery Pack, AC Adaptor, USB Communications Cable, TLS2200® / HandiMark™ Material Roll Adaptor, Quick Start Guide, Product CD (w/ Printer Driver, Tutorials, Full User’s Guide), Cleaning Kit
BMP71-QWERTY-EU	As above but with European Power Supply
BMP71-AZERTY-EU	As above but with AZERTY Keyboard and European Power Supply
BMP71-QWERTZ-EU	As above but with QWERTZ Keyboard and European Power Supply
BMP71-CYRILLIC-EU	As above but with CYRILLIC Keyboard and European Power Supply
M71-AC-EU	BMP71 European AC
M71-AC-UK	BMP71 UK AC
M71-QC-EU	BMP71 European Quick Charger
M71-QC-UK	BMP 71 UK Quick Charger
M71-HC	BMP71 Hard Carry Case
M71-SC	BMP 71 Soft Carry Case
M71-AC-BC	BMP71 AC/BATTERY CHARGER
M71-BATT	BMP71 SPARE BATTERY
M71-CLEAN	BMP71 CLEANING KIT
M71-ADAPT	BMP71 ROLL ADAPTER FOR TLS/HM

Features – Printing Options


Printer

- Large full colour graphic LCD screen
- Display communicates important status information:
 - Installed label part
 - Label size and colour
 - Amount of material remaining
 - Remaining battery charge
 - Label and area status
 - Current font size and rotation
- Thermal transfer printing mechanism - 300 dpi
- High print speed of 38 mm/sec
- Weight : 2.5kg (w/battery)
- Handle to easily carry the printer anywhere you need it
- Built in industrial label cutter
- Print width 46 mm - Print length up to 1016 mm
- Stand alone or PC connectivity via USB
- Durable hard carry case
- Operating temperature range: 4° to 49°C



Labels

- The pre-defined application templates and wizards save time and make it easy to print the exact label you need
- Adjustable to six different widths of labels
- Can print up to 25 lines per label
- Batch label printing or print multiple copies of one label
- Ability to serialise data
- Prints mirror image
- Built-in Smart Cell Technology in labels and ribbons



Memory

- Ability to store, retrieve and delete label files
- Save over 100,000 labels!
- Built in time/date stamp

Text

- Auto font sizing
- Custom True Type Font
- Text size 4 pt to 174pt (scalable)

Battery

- Prints 4000 labels per battery charge (25, 40 to 50 mm labels)
- Rechargeable Battery and AC power/battery charger
- Sleep mode conserves battery power when printer is not in use
- UL and CUL listed battery charger



Symbols & Barcodes

- Standard electrical and datacom symbols included
- Barcode symbologies: Code 39 and Code 128
- Over 500 built in graphics



Prints all TLS2000® and Handimark™ label parts including bulk rolls. Users interested in upgrading to BMP™71 Printer, do not need to invest in a new set of consumables.

Easy way to create labels on your PC with LabelMark™ Labelling Software

Brady's LabelMark™ software lets you easily create labels for Asset ID, Component Marking, Telecom/Datacom Labelling, Wire Markers and more. It allows users to design, edit and print their Brady labels. Integrates completely with Microsoft® Office, AutoCAD® applications and more.

LabelMark™
LABELING SOFTWARE



Easy to Use Graphical Interface Label Design

- Option for line-edit or free-form mode for label design
- Several common barcode symbologies available
- Ability to import graphical images
- Data import support including spreadsheets, ASCII, ODBC and OLE DB

Label Editing

- Easy to use single screen editing
- Multiple document interface for working with different labels at the same time
- Ability to flip/flop data on label (i.e. flip/flop "to"/"from" order)

Label Printing

- Compatible with all Brady media, stock and custom formats
- Works with a variety of different printers to suit various applications



Enhance your labels with advanced graphics and symbols with MarkWare™ software

With Brady's MarkWare™ software you can combine text with graphics, symbols and barcodes. Labels can be used as visual tools throughout your facility. For lean enterprises, Brady's MarkWare™ software provides additional graphics and templates for Signs, Labels, Pipe Markers and Tags - perfect for 5S, TPM and lean visuals.



Quick & Easy Label Design

- Includes label template designs. The size of the template adjusts automatically to the size of the installed material, regardless of width
- Over 600 standardised symbols available
- Ability to import drawings, signs and diagrams
- Supports European CLP Hazardous Substances Identification labels containing GHS and ADR graphics
- Creation of pipe markers guaranteeing compliance based on your choice of national standard
- 5 Barcode protocols and 19 languages

Label Editing


- Advanced functions allow quick label creation ("align objects", "group objects", foreground/background, zoom, rotation...)
- Employs all the basic functions of Windows® applications (copy/paste within the application print preview, etc ...).

Label Printing

- Windows®-compatible print driver included
- Windows® print driver adds the Brady printer to your printer list. This authorises printing directly from other software such as drawing and other widely used creative programs

Applications

Patch Panel ID



Electrical Panel ID



Face Plate ID




Wire & Cable Self-Laminating Labels




Wire & Cable Sleeves



Terminal Block Markers



Wire & Cable Wrap Around Labels




Tag Printing



Desi-Strip Inserts



Flag Labels



Logistics Labelling



Safety Identification



Pipe Marking



Asset ID



Laboratory ID



Information Signs



Circuit Board & Component Labelling



Industrial Barcode Labelling



Security ID



Materials and Ribbons Cross Reference Chart

Material Number	Material Description	Colour	Finish	Min./Max. Service Temperature	Application	Special Properties	Agency Approvals/ Compliance	Recommended Ribbons
Nylon Cloth								
B-499	Nylon Cloth with permanent acrylic pressure sensitive adhesive	White	Matt	-70° to 90°C 30 days	Low profile through-conduit wire marking, component and general labelling	High adhesion makes all-purpose wire marker ideal for environments where heat, oil and dirt are present	HF	M71-R4300
Paper								
B-424	General Purpose Paper with permanent latex adhesive	White	Matt	-40° to 50°C 30 days	Barcode and general labelling	Good contrast and smear resistance		M71-R4300
Polyester								
B-422	Polyester with permanent acrylic adhesive	White	Gloss	-40° C to 100°C 30 days	Electronic PCB ID and component, barcode label and rating plate, outlet and patch panel ID	2 mil adhesive recommended for application on textured surfaces		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-423	Polyester with permanent acrylic adhesive	White	Gloss	-40°C to 120°C 30 days	Electronic PCB ID and component, barcode label, rating plates and outlets		HF	M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-428	Metallised polyester with permanent acrylic adhesive	Silver	Matt	-40°C to 120°C 30 days	Rating plates, electronic component marking		HF	M71-R4300
B-430	Clear polyester with permanent acrylic adhesive	Clear	Gloss	-70°C to 100°C 30 days	General labelling rating/name plates, outlet and general communications	High adhesion make it ideal for highly textured and other surfaces that are difficult to adhere to; Translucent		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-459	Polyester with permanent acrylic adhesive	White	Matt	-40°C to 110°C 30 days	Electronic PCB ID and component, barcode labelling and rating plates			M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-461	Self-laminating polyester with permanent acrylic adhesive	White/ Translucent	Matt	-196°C to 130°C 30 days	Laboratory ID	Excellent abrasion and smudge resistance	HF	M71-R4300 M71-R6200
B-473	Polyester with static dissipative permanent acrylic adhesive	White	Gloss	-40°C to 120°C 30 days	Electronic PCB ID and component, barcode labelling and rating plates	Static dissipative adhesive and liner		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-483	Polyester with permanent rubber adhesive	White	Gloss	-40°C to 120°C 30 days	General labelling; barcode label and rating plates	Ultra-aggressive adhesive for thermal transfer printing, designed for powder coated surfaces		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-486	Polyester with permanent rubber adhesive	Silver	Matt	-40°C to 120°C 30 days	General labelling; barcode label and rating plates	Metallised polyester with ultra-aggressive adhesive for oily, greasy and powder-coated surfaces		M71-R4300
B-488	Polyester with permanent acrylic adhesive	White	Matt	-40°C to 160°C 30 days	Electronic PCB and component; barcode label and rating plates	High performance matt white		M71-R4300 M71-R6200
B-489	Polyester with permanent rubber adhesive	White	Matt	-40°C to 120°C 30 days	General labelling, barcode labelling and rating plates	Ultra-aggressive adhesive for oily, greasy and powder coated surfaces; UL/CSA approval pending		M71-R6200
B-582	BradyGlo™ Polyester with acrylic adhesive	Phosphorescent	Gloss	-40°C to 80°C	Photoluminescent safety identification			M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-7593	EPREP: polyester tag on foam carrier with permanent acrylic adhesive	White, Yellow, Red, Green, Silver, Black	Gloss	-40°C to 100°C 30 days	Electrical components, switches, push buttons, rack and patch panels	650 µm thick material with foam tape to replace engraved name plates; colour match available on demand		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
Polyethylene								
B-109	Polyethylene tag	White	Matt	-40°C to 80°C 30 days	Multi-purpose identification tag, where durability is required	Cross-laminated polyethylene provides extreme tear resistance and excellent cold-weather performance		M71-R4300
B-145	Polyethylene tag	Grey	Matt	-40°C to 100°C 30 days	Power and ground labels	Tear-resistant 2-sided printable tag		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-145FR	Flame retardant rigid polyethylene tag	Grey	Matt	-40°C to 100°C 30 days	Power and ground labels	Tear-resistant 2-sided printable tag		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-7599	Polyethylene tag	White	Matt	-40°C to 50°C 30 days	Multi-purpose identification tag	250 µm polyethylene tag	HF	M71-R6200
Polymide								
B-426	Polymide with permanent acrylic adhesive	Amber	Matt	-70°C to 330°C 80 sec.	Underside PCB and other high temperature, high performance applications	Withstands extremely high temperatures		M71-R4300
B-477	Polymide with static dissipative permanent acrylic adhesive	White	Gloss	-70°C to 300°C 80 sec.	Top- or bottom-side board application for SMT or Through hole	Static dissipative adhesive and liner		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-478	Polymide with static dissipative permanent acrylic adhesive	White	Gloss	-70°C to 300°C 80 sec.	1 mil low profile top- or bottom-side board application for SMT or Through hole	Static dissipative adhesive and liner	HF	M71-R6000 M71-R4400-WT M71-R6900 (colours*)

These materials have static dissipative adhesives

These materials are UL recognised


These materials are CSA approved.


HF Halogen-Free (DIN VDE 0472/parts 815)


*R-6900 ribbon comes in red, green, magenta, yellow and blue


Materials and Ribbons Cross Reference Chart

Material Number	Material Description	Colour	Finish	Min./Max. Service Temperature	Application	Special Properties	Agency Approvals/ Compliance	Recommended Ribbons
Polyolefin								
B-341	PermaSleeve™ heat shrink polyolefin sleeves	White, Yellow	Matt	-40°C to 130°C 1000 hours	Wire marking	2-to-1 shrink ratio, self-extinguishing, meets the material and physical property of AMS-DTL-23053/5 Class 1, SAE AS-81531, MIL-STD-202, Method 215 and UL 224		M71-R4300
B-342	PermaSleeve™ heat shrink polyolefin sleeves	White, Yellow	Matt	-55°C to 130°C 1000 hours	Wire marking	3-to-1 shrink ratio, self-extinguishing, meets the material and physical property of AMS-DTL-23053/5 Class 1, SAE AS-81531, MIL-STD-202, Method 215 and UL 224		M71-R4300
Polypropylene								
B-412	Polypropylene tag	White	Matt	-40°C to 100°C 30 days	Wire, cable and product inventory information	Designed where tensile strength is needed	HF	M71-R6200
B-425	Polypropylene with acrylic adhesive	White	Matt	-40°C to 100°C 30 days	Cable and wire markers, P- and T-labels	Excellent abrasion and smudge resistance	UL SP HF	M71-R4300
B-529	Economy polypropylene with acrylic adhesive	Whit	Gloss	-40°C to 100°C	Low-cost choice for indoor use			M71-R6000 M71-R4400-WT M71-R6900 (colours*)
Tedlar®								
B-437	Tedlar® with permanent acrylic adhesive	White, Yellow	Matt	-70°C to 135°C 30 days	Aerospace and military cable marking	Self-extinguishing		M71-R4300
B-642	Tedlar® with permanent acrylic adhesive	White	Matt	-70°C to 120°C 30 days	Self-laminating, wire and cable marking	Self-extinguishing, low smoke and flame spread, excellent abrasion and smudge resistance		M71-R4300
Thermoplastic Polyether-polyurethane (PUR)								
B-7643	Thermoplastic polyether polyurethane tag	White, Yellow	Matt	-40°C to 90°C 30 days	Wire & cable marking	Zero halogen, more colours available		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
Vinyl								
B-352	Vinyl with permanent acrylic adhesive	Silver	Matt	-40°C to 80°C 30 days	Tamper-resistant labels for security ID; asset ID	Metallised vinyl, designed to fracture easily		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-427	Self-laminating vinyl with permanent acrylic adhesive	White	Matt	-70°C to 70°C 30 days	Self-laminating wire and cable marking	Excellent abrasion and smudge resistance	UL	M71-R4300
B-530	Tamper evident vinyl with acrylic adhesive	White	Gloss	-40°C to 90°C	Tamper-resistant labels for security ID; asset ID	Designed to fracture easily		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-580	High Performance vinyl with permanent acrylic adhesive	Red, Yellow, Blue, Green, White, Orange, Grey, Black, Brown, Purple, Clear, Gold, Ochre, Sky Blue, Light Blue, Pink, Tan	Gloss	-40°C to 82°C	Safety identification, pipe marking	5-year average outdoor durability		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-584	Reflective vinyl with acrylic adhesive	White, Yellow, Orange	Gloss	-40°C to 82°C	Reflective quality makes material ideal for use in low-light conditions	5-year average outdoor durability		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-581	Repositionable vinyl with acrylic adhesive	White, Yellow	Gloss	-40°C to 82°C	Indoor labels where frequent repositioning is required			M71-R6000 M71-R4400-WT M71-R6900 (colours*)
B-7696	Rigid vinyl tag, Rigid Durasleeve	White	Gloss	-40°C to 70°C 30 days	Sleeves, inserts, tags, terminal block markers	Rigid construction		M71-R6000 M71-R4400-WT M71-R6900 (colours*)
Vinyl Cloth								
B-498	Vinyl cloth with repositionable rubber based adhesive	White	Semi-gloss	-40°C to 82°C 30 days	Wire and electronic component marking	Repositionable adhesive	UL	M71-R6200

 These materials have static dissipative adhesives

 These materials are UL recognised

 These materials are CSA approved.

 Halogen-Free (DIN VDE 0472/parts 815)

Tedlar® is a registered trademark of DuPont

*R-6900 ribbon comes in red, green, magenta, yellow and blue



Brady has hundreds of RoHS compliant materials for you to choose from and we are committed to provide you with the latest information. Simply go to www.weeerohs.bradyeurope.com for the latest up-date.



For more information on our materials or to help you choose, visit www.bradyeurope.com

Ribbons

Ribbons

Order Reference	Colour	Ribbon Width (mm)	Ribbon Length (m)	Special property
M71-R4300	Black	50.80	46	Strong environmental resistance against smearing and chemicals. Reliable, sharp-edge print quality to maximize bar code readability.
M71-R4400-WT	White	50.80	46	High density ribbon with excellent solvent resistance, high heat resistance, and super scratch resistance.
M71-R6000	Black	50.80	46	High density ribbon with excellent solvent resistance, high heat resistance, and super scratch resistance.
M71-R6200	Black	50.80	46	Designed for harsh environment labeling applications. Superior abrasion, chemical and heat resistance.
M71-R6400	Black	50.80	46	High density ribbon with excellent solvent resistance, high heat resistance, and super scratch resistance.
M71-R6800-WT	White	50.80	46	Strong environmental resistance against smearing and chemicals. Reliable, sharp-edge print quality to maximize bar code readability.
M71-R6900-BL	Blue	50.80	46	High density ribbon with excellent solvent resistance, high heat resistance, and super scratch resistance.
M71-R6900-GN	Green	50.80	46	High density ribbon with excellent solvent resistance, high heat resistance, and super scratch resistance.
M71-R6900-MA	Magenta	50.80	46	High density ribbon with excellent solvent resistance, high heat resistance, and super scratch resistance.
M71-R6900-RD	Red	50.80	46	High density ribbon with excellent solvent resistance, high heat resistance, and super scratch resistance.
M71-R6900-YL	Yellow	50.80	46	High density ribbon with excellent solvent resistance, high heat resistance, and super scratch resistance.



Bulk Packaging

Bulk labels are designed for the BMP™71 Label Printer as a cost-effective solution for high volume labelling needs. Order references beginning with “B” indicate bulk rolls.





High Performance Industrial Identification / Safety Identification

B-580 Indoor/Outdoor Vinyl:

- Brady's indoor/outdoor grade vinyl tape adheres well to pipes, walls, equipment, windows – most clean, dry surfaces.
- Conforms well to irregular, curved or rough surfaces – it even stands up to grease, oil and most industrial chemicals.
- Five year average outdoor durability in temperatures from 82°C to -40°C, can be applied as low as -18°C.

Diagram	Order Reference	Width A (mm)	Length B (m)	Colour
●	M71C-500-580-WT	12.70	15.24	White
●	M71C-500-580-YL	12.70	15.24	Yellow
●	M71C-500-580-GN	12.70	15.24	Green
●	M71C-500-580-RD	12.70	15.24	Red
●	M71C-500-580-BL	12.70	15.24	Blue
●	M71C-500-580-LB	12.70	15.24	Light Blue
●	M71C-500-580-SB	12.70	15.24	Sky Blue
●	M71C-500-580-OR	12.70	15.24	Orange
●	M71C-500-580-BK	12.70	15.24	Black
●	M71C-500-580-GY	12.70	15.24	Grey
●	M71C-500-580-BR	12.70	15.24	Brown
●	M71C-500-580-GD	12.70	15.24	Gold
●	M71C-500-580-OC	12.70	15.24	Ochre
●	M71C-500-580-PL	12.70	15.24	Purple
●	M71C-500-580-PK	12.70	15.24	Pink
●	M71C-500-580-TN	12.70	15.24	Tan
●	M71C-500-580-CL	12.70	15.24	Clear
●	M71C-1000-580-WT	25.40	15.24	White
●	M71C-1000-580-YL	25.40	15.24	Yellow
●	M71C-1000-580-GN	25.40	15.24	Green
●	M71C-1000-580-RD	25.40	15.24	Red
●	M71C-1000-580-BL	25.40	15.24	Blue
●	M71C-1000-580-LB	25.40	15.24	Light Blue
●	M71C-1000-580-SB	25.40	15.24	Sky Blue
●	M71C-1000-580-OR	25.40	15.24	Orange
●	M71C-1000-580-BK	25.40	15.24	Black
●	M71C-1000-580-GY	25.40	15.24	Grey
●	M71C-1000-580-BR	25.40	15.24	Brown
●	M71C-1000-580-GD	25.40	15.24	Gold
●	M71C-1000-580-OC	25.40	15.24	Ochre
●	M71C-1000-580-PL	25.40	15.24	Purple
●	M71C-1000-580-PK	25.40	15.24	Pink
●	M71C-1000-580-TN	25.40	15.24	Tan
●	M71C-1000-580-CL	25.40	15.24	Clear
●	M71C-2000-580-WT	50.80	15.24	White
●	M71C-2000-580-YL	50.80	15.24	Yellow
●	M71C-2000-580-GN	50.80	15.24	Green
●	M71C-2000-580-RD	50.80	15.24	Red
●	M71C-2000-580-BL	50.80	15.24	Blue
●	M71C-2000-580-LB	50.80	15.24	Light Blue
●	M71C-2000-580-SB	50.80	15.24	Sky Blue
●	M71C-2000-580-OR	50.80	15.24	Orange
●	M71C-2000-580-BK	50.80	15.24	Black
●	M71C-2000-580-GY	50.80	15.24	Grey
●	M71C-2000-580-BR	50.80	15.24	Brown
●	M71C-2000-580-GD	50.80	15.24	Gold
●	M71C-2000-580-OC	50.80	15.24	Ochre
●	M71C-2000-580-PL	50.80	15.24	Purple
●	M71C-2000-580-PK	50.80	15.24	Pink
●	M71C-2000-580-TN	50.80	15.24	Tan
●	M71C-2000-580-CL	50.80	15.24	Clear









Order references with "C" (e.g. M71C) indicate continuous.

General and Industrial Identification Labels


Repositionable Labels

• B-581 Repositionable Vinyl:

- Special adhesive allows easy removal of label to re-apply again and again.
- Best choice for indoor marking where frequent repositioning is required, such as shelves.

Diagram	Order Reference	Width A (mm)	Length B (m)	Colour
	M71C-500-581-YI	12.70	15.24	Yellow
	M71C-500-581-WT	12.70	15.24	White
	M71C-1000-581-YL	25.40	15.24	Yellow
	M71C-1000-581-WT	25.40	15.24	White
	M71C-2000-581-YL	50.80	15.24	Yellow
	M71C-2000-581-WT	50.80	15.24	White







Order references with "C" (e.g. M71C) indicate continuous.




Reflective Labels

• B-584 Reflective Vinyl:

- Ideal for reading labels in low light conditions.

Diagram	Order Reference	Width A (mm)	Length B (m)	Colour
	M71C-500-584-YI	12.70	15.24	Yellow
	M71C-500-584-WT	12.70	15.24	White
	M71C-1000-584-YL	25.40	15.24	Yellow
	M71C-1000-584-WT	25.40	15.24	White
	M71C-2000-584-YL	50.80	15.24	Yellow
	M71C-2000-584-WT	50.80	15.24	White

Order references with "C" (e.g. M71C) indicate continuous.



For more information on our materials or to help you choose, visit www.bradyeurope.com

General and Industrial Identification Labels

Material to Surface Cross Reference Guide

Brady material number (B-number)				Smooth (Examples: Uncoated Metal, Plastic, Glass)	Textured/Rough (Examples: Textured ABS, Cast Metal, Polycarbonate)	Highly Textured / Low Surface Energy (Examples: Powder Coated, Low Surface Energy ABS, Polypropylene)
B-7351	B-352**	B-422*	B-432*	✓ YES	✓ YES	NO
B-435*	B-427**	B-580				
B-483*	B-486*	B-489*	B-499*	✓ YES	✓ YES	✓ YES
B-423*	B-424	B-428*	B-430*			
B-459*	B-473*	B-488*	B-7546*	✓ YES	NO	NO
B-7566	B-7576*					

*Material UL recognised / CSA approved

**Material UL recognised

Rating, Name Plate Labels

- B-422, B-423 Permanent Glossy Polyester
- B-424 General Purpose White Paper
- B-428 Permanent Metallised Polyester
- B-430 Permanent Clear Polyester
- B-483 Ultra-Aggressive Glossy Polyester
- B-486 Ultra-Aggressive Metallised Polyester
- B-489 Ultra-Aggressive Matt Polyester
- B-488 Matt Polyester
- B-499 Nylon Cloth




Diagram	Order Reference	Labels Per Roll	Width A (mm)	Height B (mm)	Applications/ Descriptions	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Surface Suitability
▲	M71-16-483	500	25.40	9.53	Asset ID for textured surfaces	24	3	✓
▲	BM71-17-428	5000	25.40	12.70	General Purpose over-laminated ID	24	5	✓
▲	M71-17-428	500	25.40	12.70	General Purpose over-laminated ID	24	5	✓
▲	M71-17-483	500	25.40	12.70	Asset ID for textured surfaces	24	5	✓
▲	M71-17-486	500	25.40	12.70	Asset ID for oily, greasy and textured surfaces	24	5	✓
▲	M71-17-489	500	25.40	12.70	Asset ID for oily, greasy and textured surfaces	24	5	✓
▲	M71-19-423	250	25.40	25.40	Rating plate	24	10	✓
▲	BM71-19-423	2500	25.40	25.40	Rating plate	24	10	✓
▲	M71-19-483	250	25.40	25.40	Asset ID for textured surfaces	24	10	✓
▲	M71-20-424	100	50.80	25.40	General ID and Asset ID	46	10	✓
▲	BM71-20-424	1000	50.80	25.40	General ID and Asset ID	46	10	✓
▲	M71-20-428	100	50.80	25.40	Asset ID, silver finish	46	10	✓
▲	BM71-20-428	1000	50.80	25.40	Asset ID, silver finish	46	10	✓
▲	M71-20-483	100	50.80	25.40	Asset ID for textured surfaces	46	10	✓
▲	M71-20-486	100	50.80	25.40	Asset ID for oily, greasy and textured surfaces	46	10	✓
▲	M71-22-423	100	76.20	25.40	General ID	50	10	✓
▲	M71-22-428	100	76.20	25.40	Rating plate	50	10	✓
▲	M71-23-423	100	101.60	25.40	General ID	50	9	✓
▲	M71-23-483	100	101.60	25.40	Asset ID for textured surfaces	50	9	✓
◐	M71-24-423-BK	500	28.70	12.70	1.60 mm Black-bordered component ID	24	3	✓
▲	M71-26-423	100	69.85	31.75	General ID and Asset ID	50	13	✓
▲	M71-26-428	100	69.85	31.75	General ID and Asset ID	50	13	✓
▲	M71-29-428	500	38.10	12.70	Face plates, panels, equipment, silver finish	37	5	✓

*Any label 50.80 mm or larger is rotated on liner

Order references beginning with "B" indicate bulk rolls.

Continued on next page >>

✓ Material suitable for smooth surfaces.

✓ Material suitable for smooth and textured surfaces.

✓ Material suitable for smooth, textured and highly textured surfaces.

General and Industrial Identification Labels

Rating, Name Plate Labels (continued)

- B-422, B-423 Permanent Glossy Polyester
- B-428 Permanent Metallised Polyester
- B-430 Permanent Clear Polyester
- B-483 Ultra-Aggressive Glossy Polyester
- B-486 Ultra-Aggressive Metallised Polyester
- B-489 Ultra-Aggressive Matt Polyester
- B-488 Matt Polyester
- B-499 Nylon Cloth




Diagram	Order Reference	Labels Per Roll	Width A (mm)	Height B (mm)	Applications/ Descriptions	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Surface Suitability
▲	M71-29-483	500	38.10	12.70	Asset ID for textured surfaces	37	5	✓
▲	M71-29-486	500	38.10	12.70	Asset ID for oily, greasy and textured surfaces	37	5	✓
▲	M71-29-489	500	38.10	12.70	Asset ID for oily, greasy and textured surfaces	37	5	✓
▲	M71-30-422	250	38.10	19.05	Asset ID for textured surfaces	37	8	✓
▲	M71-30-483	250	38.10	19.05	Asset ID for oily, greasy and textured surfaces	37	8	✓
▲	M71-30-486	250	38.10	19.05	Asset ID for oily, greasy and textured surfaces	37	8	✓
▲	M71-30-499	250	19.05	38.10	Asset ID for oily, greasy and textured surfaces	18	16	✓
▲	M71-31-423	250	38.10	25.40	General ID	37	10	✓
▲	M71-31-483	250	38.10	25.40	Asset ID for textured surfaces	37	10	✓
▲	M71-32-423	250	38.10	38.10	General ID	37	16	✓
▲	M71-32-489	250	38.10	38.10	Asset ID for oily, greasy and textured surfaces	37	16	✓
▲	M71-37-422	100	76.20	48.26	Asset ID for textured surfaces	50	20	✓
▲	M71-37-423	100	76.20	48.26	General ID and Asset ID	50	20	✓
▲	M71-37-483	100	76.20	48.26	Asset ID for oily, greasy and textured surfaces	50	20	✓
▲	M71-37-486	100	76.20	48.26	Asset ID for oily, greasy and textured surfaces	50	20	✓
▲	M71-38-423	100	101.60	48.26	General ID and Asset ID	50	20	✓
▲	M71-38-428	100	101.60	48.26	Asset ID, silver finish	50	20	✓
▲	M71-38-483	100	101.60	48.26	Asset ID for oily, greasy and textured surfaces	50	20	✓
▲	M71-38-489	100	101.60	48.26	Asset ID for oily, greasy and textured surfaces	50	20	✓
▲	M71-78-499	250	48.26	25.40	General ID	46	10	✓
▲	M71-80-488	250	19.05	22.86	Asset ID with print durability	18	10	✓
▲	M71-81-488	750	48.26	6.35	Asset ID with print durability	46	10	✓
▲	M71-81-499	750	48.26	6.35	General ID	46	10	✓
▲	M71-84-499	500	22.86	12.70	General ID	22	2	✓
▲	M71-97-488	250	22.86	22.86	Asset ID with print durability	18	9	✓
●	M71C-375-422	1 (cont.)	9.53	15.24 m	General ID	50	3	✓
●	M71C-375-430	1 (cont.)	9.53	15.24 m	General ID	50	3	✓
●	M71C-475-422	1 (cont.)	12.07	15.24 m	General ID	50	5	✓
●	M71C-500-423	1 (cont.)	12.70	15.24 m	Small ICs	50	5	✓
●	M71C-500-428	1 (cont.)	12.70	15.24 m	Small ICs, silver finish	50	5	✓
●	M71C-500-483	1 (cont.)	12.70	15.24 m	Small ICs, silver finish	50	5	✓
●	M71C-625-422	1 (cont.)	15.88	15.24 m	General ID	50	6	✓
●	M71C-1000-422	1 (cont.)	25.40	15.24 m	General ID	50	10	✓
●	M71C-1000-430	1 (cont.)	25.40	15.24 m	General ID	50	5	✓
●	M71C-1000-483	1 (cont.)	25.40	15.24 m	General ID	50	10	✓
●	M71C-1900-422	1 (cont.)	48.26	15.24 m	General ID	50	10	✓
●	M71C-1900-430	1 (cont.)	48.26	15.24 m	General ID	50	10	✓
●	M71C-1900-483	1 (cont.)	48.26	15.24 m	General ID	50	10	✓

*Any label 50.80 mm or larger is rotated on liner

✓ Material suitable for smooth surfaces.

✓ Material suitable for smooth and textured surfaces.

✓ Material suitable for smooth, textured and highly textured surfaces.

General and Industrial Identification Labels

General Industrial Labels

- B-422 Permanent Glossy Polyester
- B-430 Permanent Clear Polyester
- B-483 Ultra-Aggressive Glossy Polyester
- B-489 Ultra-Aggressive Matt Polyester
- B-580 Indoor/Outdoor Vinyl




Diagram	Order Reference	Labels Per Roll	Colour	Width A (mm)	Height B (mm)	Max. Characters per line for 7 points	Max. Lines of Text for 7 points	Surface Suitability
▲	M71-16-483	500	White	25.40	9.53	14	2	✓
▲	M71-17-483	500	White	25.40	12.70	10	2	✓
▲	M71-17-489	500	White	25.40	12.70	10	2	✓
▲	M71-19-483	250	White	25.40	25.40	14	7	✓
▲	M71-20-483	100	White	50.80	25.40	50	4	✓
▲	M71-23-483	100	White	101.60	25.40	38	4	✓
▲	M71-29-483	500	White	38.10	12.70	14	2	✓
▲	M71-29-489	500	White	38.10	12.70	14	2	✓
▲	M71-30-422	250	White	38.10	19.05	14	3	✓
▲	M71-30-483	250	White	38.10	19.05	14	3	✓
▲	M71-31-483	250	White	38.10	25.40	14	4	✓
▲	M71-32-489	250	White	38.10	38.10	14	4	✓
▲	M71-37-422	100	White	76.20	48.26	28	9	✓
▲	M71-37-483	100	White	76.20	48.26	28	9	✓
▲	M71-38-483	100	White	101.60	48.26	38	9	✓
▲	M71-38-489	100	White	101.60	48.26	39	9	✓
●	M71C-375-422	1 (cont.)	White	9.53	15.24 m	50	2	✓
●	M71C-375-430	1 (cont.)	Clear	9.53	15.24 m	50	2	✓
●	M71C-475-422	1 (cont.)	White	12.07	15.24 m	50	2	✓
●	M71C-500-422	1 (cont.)	White	12.07	15.24 m	50	2	✓
●	M71C-500-483	1 (cont.)	White	12.70	15.24 m	50	2	✓
●	M71C-500-580-BK	1 (cont.)	Black	12.70	15.24 m	50	2	✓
●	M71C-500-580-BL	1 (cont.)	Blue	12.70	15.24 m	50	2	✓
●	M71C-500-580-BR	1 (cont.)	Brown	12.70	15.24 m	50	2	✓
●	M71C-500-580-CL	1 (cont.)	Clear	12.70	15.24 m	50	2	✓
●	M71C-500-580-GD	1 (cont.)	Gold	12.70	15.24 m	50	2	✓
●	M71C-500-580-GN	1 (cont.)	Green	12.70	15.24 m	50	2	✓
●	M71C-500-580-GY	1 (cont.)	Grey	12.70	15.24 m	50	2	✓
●	M71C-500-580-LB	1 (cont.)	Light Blue	12.70	15.24 m	50	2	✓
●	M71C-500-580-OC	1 (cont.)	Ochre	12.70	15.24 m	50	2	✓
●	M71C-500-580-OR	1 (cont.)	Orange	12.70	15.24 m	50	2	✓
●	M71C-500-580-PK	1 (cont.)	Pink	12.70	15.24 m	50	2	✓
●	M71C-500-580-PL	1 (cont.)	Purple	12.70	15.24 m	50	2	✓
●	M71C-500-580-RD	1 (cont.)	Red	12.70	15.24 m	50	2	✓
●	M71C-500-580-SB	1 (cont.)	Sky Blue	12.70	15.24 m	50	2	✓
●	M71C-500-580-TN	1 (cont.)	Tan	12.70	15.24 m	50	2	✓
●	M71C-500-580-WT	1 (cont.)	White	12.70	15.24 m	50	2	✓
●	M71C-500-580-YL	1 (cont.)	Yellow	12.70	15.24 m	50	2	✓
●	M71C-625-422	1 (cont.)	White	15.88	15.24 m	50	3	✓
●	M71C-1000-580-BK	1 (cont.)	Black	25.40	15.24 m	50	5	✓
●	M71C-1000-580-BL	1 (cont.)	Blue	25.40	15.24 m	50	5	✓
●	M71C-1000-580-BR	1 (cont.)	Brown	25.40	15.24 m	50	5	✓
●	M71C-1000-580-CL	1 (cont.)	Clear	25.40	15.24 m	50	5	✓
●	M71C-1000-580-GD	1 (cont.)	Gold	25.40	15.24 m	50	5	✓
●	M71C-1000-580-GN	1 (cont.)	Green	25.40	15.24 m	50	5	✓
●	M71C-1000-580-GY	1 (cont.)	Grey	25.40	15.24 m	50	5	✓
●	M71C-1000-580-LB	1 (cont.)	Light Blue	25.40	15.24 m	50	5	✓



*Any label 50.80 mm or larger is rotated on liner

Continued on next page >>

✓ Material suitable for smooth surfaces.

✓ Material suitable for smooth and textured surfaces.


✓ Material suitable for smooth, textured and highly textured surfaces.

General and Industrial Identification Labels

General Industrial Labels (continued)




- B-422 Permanent Glossy Polyester
- B-430 Permanent Clear Polyester
- B-483 Ultra-Aggressive Glossy Polyester
- B-580 Indoor/Outdoor Vinyl

Diagram	Order Reference	Labels Per Roll	Colour	Width A (mm)	Height B (mm)	Max. Characters per line for 7 points	Max. Lines of Text for 7 points	Surface Suitability
●	M71C-1000-580-OC	1 (cont.)	Ochre	25.40	15.24 m	50	5	✓
●	M71C-1000-580-OR	1 (cont.)	Orange	25.40	15.24 m	50	5	✓
●	M71C-1000-580-PK	1 (cont.)	Pink	25.40	15.24 m	50	5	✓
●	M71C-1000-580-PL	1 (cont.)	Purple	25.40	15.24 m	50	5	✓
●	M71C-1000-580-RL	1 (cont.)	Red	25.40	15.24 m	50	5	✓
●	M71C-1000-580-SB	1 (cont.)	Sky Blue	25.40	15.24 m	50	5	✓
●	M71C-1000-580-TN	1 (cont.)	Tan	25.40	15.24 m	50	5	✓
●	M71C-1000-580-WT	1 (cont.)	White	25.40	15.24 m	50	5	✓
●	M71C-1000-580-YL	1 (cont.)	Yellow	25.40	15.24 m	50	5	✓
●	M71C-1000-422	1 (cont.)	White	25.40	15.24 m	50	5	✓
●	M71C-1000-430	1 (cont.)	Clear	25.40	15.24 m	50	5	✓
●	M71C-1000-483	1 (cont.)	White	25.40	15.24 m	50	5	✓
●	M71C-1900-422	1 (cont.)	White	48.26	15.24 m	50	9	✓
●	M71C-1900-430	1 (cont.)	Clear	48.26	15.24 m	50	9	✓
●	M71C-1900-483	1 (cont.)	White	48.26	15.24 m	50	9	✓
●	M71C-2000-580-BK	1 (cont.)	Black	50.80	15.24 m	50	8	✓
●	M71C-2000-580-BL	1 (cont.)	Blue	50.80	15.24 m	50	8	✓
●	M71C-2000-580-BR	1 (cont.)	Brown	50.80	15.24 m	50	8	✓
●	M71C-2000-580-CL	1 (cont.)	Clear	50.80	15.24 m	50	8	✓
●	M71C-2000-580-GD	1 (cont.)	Gold	50.80	15.24 m	50	8	✓
●	M71C-2000-580-GN	1 (cont.)	Green	50.80	15.24 m	50	8	✓
●	M71C-2000-580-GY	1 (cont.)	Grey	50.80	15.24 m	50	8	✓
▲	M71C-2000-580-LB	1 (cont.)	Light Blue	50.80	15.24 m	50	8	✓
▲	M71C-2000-580-OC	1 (cont.)	Ochre	50.80	15.24 m	50	8	✓
●	M71C-2000-580-OR	1 (cont.)	Orange	50.80	15.24 m	50	8	✓
●	M71C-2000-580-PK	1 (cont.)	Pink	50.80	15.24 m	50	8	✓
●	M71C-2000-580-PL	1 (cont.)	Purple	50.80	15.24 m	50	8	✓
●	M71C-2000-580-RD	1 (cont.)	Red	50.80	15.24 m	50	8	✓
●	M71C-2000-580-SB	1 (cont.)	Sky Blue	50.80	15.24 m	50	8	✓
●	M71C-2000-580-TN	1 (cont.)	Tan	50.80	15.24 m	50	8	✓
●	M71C-2000-580-WT	1 (cont.)	White	50.80	15.24 m	50	8	✓
●	M71C-2000-580-YL	1 (cont.)	Yellow	50.80	15.24 m	50	8	✓



Pre-Printed Labels

- B-423 Permanent Glossy Polyester
- B-428 Permanent Metallised Polyester



Order Reference	Labels Per Roll	Colours	Width A (mm)	Height B (mm)	Pre-Printed Legend	Surface Suitability
M71-30-423-TEST	250	Green on White	38.10	19.05	Tested	✓
M71-30-428-CALI	250	Green on Silver	38.10	19.05	Calibration	✓
M71-35-428-PROP	250	Black on Silver	41.40	19.05	Property Tag	✓

✓ Material suitable for smooth surfaces.

✓ Material suitable for smooth and textured surfaces.

✓ Material suitable for smooth, textured and highly textured surfaces.

Wrap Around Labels

- **B-498 Vinyl cloth:** repositionable rubber based adhesive
- **B-499 Nylon Cloth:** permanent adhesive, pliable for rough and smooth surfaces.





Diagram	Order Reference	Labels Per Roll	Label Width A (mm)	Label Height B (mm)	Max. Wire Diameter (mm)	Approx. Wire Gauge*	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
9 AWG Based on Type of Wire – Max Wire Diam. 3.03 mm								
▲	M71-7-498	500	12.70	12.70	3.03	9	11	5
▲	M71-7-499	500	12.70	12.70	3.03	9	11	5
▲	M71-81-499	750	48.26	6.35	10.00	9	46	10
▲	M71-84-499	500	22.86	12.70	6.00	9	22	2
6 AWG Based on Type of Wire – Max Wire Diam. 4.55 mm								
▲	M71-10-498	750	6.35	19.05	4.55	6	5	3
▲	M71-11-498	500	12.70	19.05	4.55	6	11	8
▲	BM71-11-498	5000	12.70	19.05	4.55	6	11	8
▲	M71-11-499	500	12.70	19.05	4.55	6	11	8
▲	BM71-11-499	5000	12.70	19.05	4.55	6	11	8
3 AWG Based on Type of Wire – Max Wire Diam. 6.06 mm								
▲	M71-16-498	500	9.53	25.40	6.06	3	8	10
▲	M71-16-499	500	9.53	25.40	6.06	3	8	10
▲	M71-17-498	500	25.40	12.70	6.06	3	24	5
▲	M71-18-498	250	19.05	25.40	6.06	3	18	10
▲	M71-18-499	250	19.05	25.40	6.06	3	18	10
▲	BM71-18-498	2500	19.05	25.40	6.06	3	18	10
▲	M71-19-498	250	25.40	25.40	6.06	3	24	10
▲	BM71-19-498	2500	25.40	25.40	6.06	3	24	10
▲	M71-19-499	250	25.40	25.40	6.06	3	24	10
▲	M71-78-499	250	48.26	25.40	10.00	3	46	10
0 AWG Based on Type of Wire – Max Wire Diam. 9.10 mm								
▲	M71-28-499	750	38.10	6.35	9.10	0	5	16
▲	M71-29-498	500	38.10	12.70	9.10	0	11	16
▲	BM71-29-498	5000	12.70	38.10	9.10	0	11	16
▲	M71-29-499	500	12.70	38.10	9.10	0	11	16
▲	M71-30-498	250	19.05	38.10	9.10	0	18	16
▲	M71-30-499	250	19.05	38.10	9.10	0	18	16
▲	M71-31-498	250	25.40	38.10	9.10	0	24	16
▲	M71-31-499	250	25.40	38.10	9.10	0	24	16
▲	M71-32-498	250	38.10	38.10	9.10	0	37	16
0000 AWG Based on Type of Wire – Max Wire Diam. 15.16 mm								
▲	M71-21-498	100	25.40	63.50	15.6	0000	24	23
▲	M71-21-499	100	25.40	63.50	15.6	0000	24	23
0000 AWG Based on Type of Wire – Max Wire Diam. 24.26 mm								
▲	M71-33-498	100	38.10	101.60	24.26	0000	37	16

*Based on National Electric Code insulation measurement of THHN Wire.

Order references beginning with "B" indicate bulk rolls.

Wire and Cable Marking

Self-Laminating Labels

- **B-427 Vinyl:** resistant to water, oil, solvents and abrasion.
- **B-642 Tedlar®:** excellent abrasion and smudge resistance, self-extinguishing




Diagram	Order Reference	Labels Per Roll	Colour	Label Width A (mm)	Label Height B (mm)	Write-on Height C (mm)	Min. Wire Diameter (mm)	Max. Wire Diameter (mm)	Approx. Wire Gauge*	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
10 to 0 AWG Based on Type of Wire – Maximum Wire Diam 10.00											
✗	M71-104-427	250	White	38.10	25.40	9.53	3.00	8.00	10 to 0	37	3
10 to 4 AWG Based on Type of Wire – Maximum Wire Diam 5.00											
⊗	BM71-17-427	5000	White	12.70	25.40	9.53	3.00	5.00	10 to 4	11	3
⊗	M71-17-427	500	White	12.70	25.40	9.53	3.00	5.00	10 to 4	11	3
⊗	BM71-18-427	2500	White	19.05	25.40	9.53	3.00	5.00	10 to 4	18	3
⊗	M71-18-427	250	White	19.05	25.40	9.53	3.00	5.00	10 to 4	18	3
✗	BM71-19-427	2500	White	25.40	25.40	9.53	3.00	5.00	10 to 4	24	3
✗	M71-19-427	250	White	25.40	25.40	9.53	3.00	5.00	10 to 4	24	3
✗	M71-19-427-YL	250	Yellow	25.40	25.40	9.53	3.00	5.00	10 to 4	24	3
✗	M71-19-642	250	White	25.40	25.40	9.53	3.00	5.00	10 to 4	24	3
✗	M71-96-427	250	White	25.40	19.05	9.53	3.00	5.00	10 to 4	24	3
10 to 10 AWG Based on Type of Wire – Maximum Wire Diam 3.00											
⊗	M71-10-427	750	White	6.35	19.05	9.53	3.00	3.00	10 to 10	5	3
⊗	BM71-11-427	5000	White	12.70	19.05	9.53	3.00	3.00	10 to 10	11	3
⊗	M71-11-427	500	White	12.70	19.05	9.53	3.00	3.00	10 to 10	11	3
7 to 0000 AWG Based on Type of Wire – Maximum Wire Diam 12.00											
⊗	BM71-107-427	1000	White	50.80	38.10	12.70	4.00	12.00	7 to 0000	46	5
⊗	M71-107-427	100	White	50.80	38.10	12.70	4.00	12.00	7 to 0000	46	5
7 to 0000 AWG Based on Type of Wire – Maximum Wire Diam 10.00											
✗	M71-88-427	250	White	44.45	38.10	12.70	4.00	10.00	7 to 0000	40	5
7 to 0 AWG Based on Type of Wire – Maximum Wire Diam 8.00											
⊗	M71-28-427	750	White	6.35	38.10	12.70	4.00	8.00	7 to 0	5	5
⊗	BM71-29-427	5000	White	12.70	38.10	12.70	4.00	8.00	7 to 0	11	5
⊗	M71-29-427	500	White	12.70	38.10	12.70	4.00	8.00	7 to 0	11	5
⊗	BM71-30-427	2500	White	19.05	38.10	12.70	4.00	8.00	7 to 0	18	5
⊗	M71-30-427	250	White	19.05	38.10	12.70	4.00	8.00	7 to 0	18	5
⊗	M71-30-427-BL	250	Blue	19.05	38.10	12.70	4.00	8.00	7 to 0	18	5
⊗	M71-30-427-PL	250	Purple	19.05	38.10	12.70	4.00	8.00	7 to 0	18	5
⊗	M71-30-427-RD	250	Red	19.05	38.10	12.70	4.00	8.00	7 to 0	18	5
⊗	BM71-31-427	2500	White	25.40	38.10	12.70	4.00	8.00	7 to 0	24	5
⊗	M71-31-427	250	White	25.40	38.10	12.70	4.00	8.00	7 to 0	24	5
⊗	M71-31-427-GN	250	Green	25.40	38.10	12.70	4.00	8.00	7 to 0	24	5
⊗	M71-31-427-RD	250	Red	25.40	38.10	12.70	4.00	8.00	7 to 0	24	5
⊗	M71-31-427-YL	250	Yellow	25.40	38.10	12.70	4.00	8.00	7 to 0	24	5
⊗	M71-31-642	250	White	25.40	38.10	12.70	4.00	8.00	7 to 0	24	5
⊗	BM71-32-427	1000	White	38.10	38.10	12.70	4.00	8.00	7 to 0	37	5
⊗	M71-32-427	250	White	38.10	38.10	12.70	4.00	8.00	7 to 0	37	5
⊗	M71-32-427-YL	250	Yellow	38.10	38.10	12.70	4.00	8.00	7 to 0	37	5
7 to 4 AWG Based on Type of Wire – Maximum Wire Diam 5.00											
✗	M71-103-427	250	White	25.40	31.75	12.70	4.00	5.00	7 to 4	24	5

*Based on National Electric Code insulation measurement of THHN Wire.

Order references beginning with "B" indicate bulk rolls.

Continued on next page >>

Self-Laminating Labels (continued)

- **B-427 Vinyl:** resistant to water, oil, solvents and abrasion.
- **B-642 Tedlar®:** excellent abrasion and smudge resistance, self-extinguishing




Diagram	Order Reference	Labels Per Roll	Colour	Label Width A (mm)	Label Height B (mm)	Write-on Height C (mm)	Min. Wire Diameter (mm)	Max. Wire Diameter (mm)	Approx. Wire Gauge*	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
3 to 0000 AWG Based on Type of Wire – Maximum Wire Diam 14.00											
⊗	BM71-21-427	1000	White	25.40	63.50	19.05	6.00	14.00	3 to 0000	24	8
⊗	M71-21-427	100	White	25.40	63.50	19.05	6.00	14.00	3 to 0000	24	8
⊗	M71-21-427-YL	100	Yellow	25.40	63.50	19.05	6.00	14.00	3 to 0000	24	8
⊗	M71-21-642	100	White	25.40	63.50	19.05	6.00	14.00	3 to 0000	24	8
1 to 0000 AWG Based on Type of Wire – Maximum Wire Diam 24.00											
⊗	BM71-23-427	1000	White	25.40	101.60	25.40	8.00	24.00	1 to 0000	24	10
⊗	M71-23-427	100	White	25.40	101.60	25.40	8.00	24.00	1 to 0000	24	10
⊗	BM71-33-427	500	White	38.10	101.60	25.40	8.00	24.00	1 to 0000	37	10
⊗	M71-33-427	100	White	38.10	101.60	25.40	8.00	24.00	1 to 0000	37	10
⊗	M71-33-427-YL	100	Yellow	38.10	101.60	25.40	8.00	24.00	1 to 0000	37	10
1 to 0000 AWG Based on Type of Wire – Maximum Wire Diam 17.00											
⊗	BM71-34-427	500	White	38.10	152.40	38.10	8.00	17.00	1 to 0000	37	16
⊗	M71-66-427	100	White	49.23	80.01	25.40	8.00	17.00	1 to 0000	46	10
1 to 0000 AWG Based on Type of Wire – Maximum Wire Diam 36.00											
⊗	M71-34-427	50	White	38.10	152.40	38.10	12.00	36.00	1 to 0000	37	16
1 to 0000 AWG Based on Type of Wire – Maximum Wire Diam 20.00											
⊗	BM71-109-427	500	White	38.10	101.60	38.10	12.00	20.00	1 to 0000	37	16
⊗	M71-109-427	100	White	38.10	101.60	38.10	12.00	20.00	1 to 0000	37	16
1 to 0000 AWG Based on Type of Wire – Maximum Wire Diam 17.00											
⊗	BM71-64-427	1000	White	25.40	85.73	28.58	9.00	17.00	1 to 0000	24	12
⊗	M71-64-427	100	White	25.40	85.73	28.58	9.00	17.00	1 to 0000	24	12

*Based on National Electric Code insulation measurement of THHN Wire.

Order references beginning with "B" indicate bulk rolls.

Applying Self-laminating Labels



Apply the printed area to your wire.



Wrap the clear area around the wire, covering the printed area.



Once applied the clear laminate will protect your legend for years to come.

Wire and Cable Marking

PermaSleeve™ Heat-Shrink Sleeve Markers

- **B-342 Polyolefin:** 3:1 Shrink ratio, self-extinguishing, meets requirements of SAE AMS-DTL-23053/5 Class 1, SAE-AS-81531, MIL-STD-202 method 215K, is UL224 recognised, CSA acceptance pending
- **B-341 Polyolefin:** 2:1 Shrink ratio, same properties as B-342






Diagram	Order Reference	Sleeves Per Roll	Colour	Sleeve Width A (mm)	Sleeve Height B (mm)	Min. Wire Diameter (mm)	Max. Wire Diameter (mm)	Approx. Wire Gauge*	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
3:1 SHRINK RATIO										
25.78mm marker width										
✓	M71-94-1-342	100	White	25.78	4.62	0.58	2.03	28 to 18	22	1
✓	BM71-94-1-342	2500	White	25.78	4.62	0.58	2.03	28 to 18	22	1
✓	M71-94-1-342YL	100	Yellow	25.78	4.62	0.58	2.03	28 to 18	22	1
✓	BM71-94-1-342YL	2500	Yellow	25.78	4.62	0.58	2.03	28 to 18	22	1
✓	M71-125-1-342	100	White	25.78	5.97	1.17	2.79	22 to 16	22	1
✓	BM71-125-1-342	1000	White	25.78	5.97	1.17	2.79	22 to 16	22	1
✓	M71-125-1-342YL	100	Yellow	25.78	5.97	1.17	2.79	22 to 16	22	1
✓	BM71-125-1-342YL	1000	Yellow	25.78	5.97	1.17	2.79	22 to 16	22	1
✓	M71-187-1-342	100	White	25.78	8.51	1.57	3.81	18 to 12	22	2
✓	BM71-187-1-342	1000	White	25.78	8.51	1.57	3.81	18 to 12	22	2
✓	M71-187-1-342YL	100	Yellow	25.78	8.51	1.57	3.81	18 to 12	22	2
✓	BM71-187-1-342YL	1000	Yellow	25.78	8.51	1.57	3.81	18 to 12	22	2
✓	M71-250-1-342	100	White	25.78	11.15	2.39	5.46	16 to 10	22	3
✓	BM71-250-1-342	1000	White	25.78	11.15	2.39	5.46	16 to 10	22	3
✓	M71-250-1-342YL	100	Yellow	25.78	11.15	2.39	5.46	16 to 10	22	3
✓	BM71-250-1-342YL	1000	Yellow	25.78	11.15	2.39	5.46	16 to 10	22	3
✓	M71-375-1-342	100	White	25.78	16.38	3.18	8.13	12 to 6	22	5
✓	BM71-375-1-342	1000	White	25.78	16.38	3.18	8.13	12 to 6	22	5
✓	M71-375-1-342YL	100	Yellow	25.78	16.38	3.18	8.13	12 to 6	22	5
✓	BM71-375-1-342YL	1000	Yellow	25.78	16.38	3.18	8.13	12 to 6	22	5
✓	M71-500-1-342	100	White	25.78	21.62	4.75	11.43	8 to 1	22	7
✓	BM71-500-1-342	1000	White	25.78	21.62	4.75	11.43	8 to 1	22	7
✓	M71-500-1-342YL	100	Yellow	25.78	21.62	4.75	11.43	8 to 1	22	7
✓	BM71-500-1-342YL	1000	Yellow	25.78	21.62	4.75	11.43	8 to 1	22	7
44.83mm marker width										
✓	M71-94-175-342	100	White	44.83	4.62	0.58	2.03	28 to 18	41	1
✓	BM71-94-175-342	2500	White	44.83	4.62	0.58	2.03	28 to 18	41	1
✓	M71-94-175-342YL	100	Yellow	44.83	4.62	0.58	2.03	28 to 18	41	1
✓	BM71-94-175-342YL	2500	Yellow	44.83	4.62	0.58	2.03	28 to 18	41	1
✓	M71-125-175-342	100	White	44.83	5.97	1.17	2.79	22 to 16	41	1
✓	BM71-125-175-342	1000	White	44.83	5.97	1.17	2.79	22 to 16	41	1
✓	M71-125-175-342YL	100	Yellow	44.83	5.97	1.17	2.79	22 to 16	41	1
✓	BM71-125-175-342YL	1000	Yellow	44.83	5.97	1.17	2.79	22 to 16	41	1
✓	M71-187-175-342	100	White	44.83	8.51	1.57	3.81	18 to 12	41	3
✓	BM71-187-175-342	1000	White	44.83	8.51	1.57	3.81	18 to 12	41	3
✓	M71-187-175-342YL	100	Yellow	44.83	8.51	1.57	3.81	18 to 12	41	3
✓	BM71-187-175-342YL	1000	Yellow	44.83	8.51	1.57	3.81	18 to 12	41	3
✓	M71-250-175-342	100	White	44.83	11.15	2.39	5.46	16 to 10	41	3
✓	BM71-250-175-342	1000	White	44.83	11.15	2.39	5.46	16 to 10	41	3
✓	M71-250-175-342YL	100	Yellow	44.83	11.15	2.39	5.46	16 to 10	41	3
✓	BM71-250-175-342YL	1000	Yellow	44.83	11.15	2.39	5.46	16 to 10	41	3
✓	M71-375-175-342	100	White	44.83	16.38	3.18	8.13	12 to 6	41	5
✓	BM71-375-175-342	1000	White	44.83	16.38	3.18	8.13	12 to 6	41	5
✓	M71-375-175-342YL	100	Yellow	44.83	16.38	3.18	8.13	12 to 6	41	5
✓	BM71-375-175-342YL	1000	Yellow	44.83	16.38	3.18	8.13	12 to 6	41	5
✓	M71-500-175-342	100	White	44.83	21.62	4.75	11.43	8 to 1	41	7
✓	BM71-500-175-342	1000	White	44.83	21.62	4.75	11.43	8 to 1	41	7
✓	M71-500-175-342YL	100	Yellow	44.83	21.62	4.75	11.43	8 to 1	41	7
✓	BM71-500-175-342YL	1000	Yellow	44.83	21.62	4.75	11.43	8 to 1	41	7
Continuous marker										
♥	BM71C-125-342	1 (cont.)	White	15.24 m	5.97	1.17	2.79	22 to 16	NA	NA
♥	BM71C-187-342	1 (cont.)	White	15.24 m	8.51	1.57	3.81	18 to 12	NA	NA
♥	BM71C-250-342	1 (cont.)	White	15.24 m	11.15	2.39	5.46	16 to 10	NA	NA
♥	BM71C-375-342	1 (cont.)	White	15.24 m	16.38	3.18	8.13	12 to 6	NA	NA
♥	BM71C-500-342	1 (cont.)	White	15.24 m	21.62	4.75	11.43	8 to 1	NA	NA
2:1 SHRINK RATIO										
25.78mm marker width										
✓	M71-1000-1-341	50	White	25.78	42.16	11.43	24.13	1 to 500	22	16
✓	M71-1000-1-341YL	50	Yellow	25.78	42.16	11.43	24.13	1 to 500	22	16
44.83mm marker width										
✓	M71-1000-175-341	50	White	44.83	42.16	11.43	24.13	1 to 500	41	16
✓	BM71-1000-175-341	500	White	44.83	42.16	11.43	24.13	1 to 500	41	16
✓	M71-1000-175-341YL	50	Yellow	44.83	42.16	11.43	24.13	1 to 500	41	16
Continuous marker										
♥	BM71C-1000-341	1 (cont.)	White	15.24 m	42.16	11.43	24.13	1 to 500	NA	NA

*Based on National Electric Code insulation measurement of THHN Wire.

Order references beginning with "B" indicate bulk rolls.

Rigid Durasleeve Inserts

- **B-7696:** Rigid vinyl tag



Order Reference	Tags Per Roll	Colour	Width (mm)	Height (mm)	Carrier	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
BM71D-3-7696	2500	White	16.00	4.40	AC*-L16	11	1
BM71D-3-7696-YL	5000	Yellow	16.00	4.40	AC*-L16	11	1
BM71D-5-7696	2500	White	30.00	4.40	AC*-L30	21	1
BM71D-5-7696-YL	5000	Yellow	30.00	4.40	AC*-L30	21	1

Order references beginning with "B" indicate bulk rolls.

Ademark Tag Carrier

Ademark carriers are produced in transparent PVC. The special shape of the carrier means that it can be adapted to cables of various diameters. This means that there are only seven different sizes of carriers which cater for cables with external diameters from 1.3 mm up to 24 mm.

- Temperature range: -40° to 60°C
- Material: PVC
- Self extinguishing: UL94V0



Order Reference	Carriers per pack	Length (mm)	Wire O.D. (mm)
AC-0-L16	2000	16.00 mm	1.30 - 2.00
AC-1-L16	2000	16.00 mm	1.80 - 2.50
AC-2-L16	2000	16.00 mm	2.50 - 4.00
AC-3-L16	1000	16.00 mm	4.00 - 6.50
AC-4-L16	1000	16.00 mm	6.00 - 10.00
AC-5-L16	750	16.00 mm	9.00 - 15.00
AC-6-L16	500	16.00 mm	15.00 - 24.00


Order Reference	Carriers per pack	Length (mm)	Wire O.D. (mm)
AC-0-L30	2000	30.00 mm	1.30 - 2.00
AC-1-L30	2000	30.00 mm	1.80 - 2.50
AC-2-L30	2000	30.00 mm	2.50 - 4.00
AC-3-L30	1000	30.00 mm	4.00 - 6.50
AC-4-L30	1000	30.00 mm	6.00 - 10.00
AC-5-L30	750	30.00 mm	9.00 - 15.00
AC-6-L30	500	30.00 mm	15.00 - 24.00

Rapido™

- **B-7599:** Yellow coated polyethylen tag suitable for durable terminated wire marking for electrical devices and fibre installations.

Order Reference	Tags Per Roll	Colour	Width A (mm)	Height B (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
BM71R-1-7599-YL	2500	Yellow	22.90	5.20	11	1
BM71R-2-7599-YL	2500	Yellow	23.00	5.20	8	1
BM71R-3-7599-YL	2500	Yellow	25.00	5.70	7	2
BM71R-4-7599-YL	2500	Yellow	26.00	7.00	7	2
BM71R-5-7599-YL	2500	Yellow	41.00	11.00	17	3

Order references beginning with "B" indicate bulk rolls.



Wire and Cable Marking


Heatex™ Cable Markers

- **B-7643:** Zero halogen polyether polyurethane tag material



Order Reference	Tags Per Roll	Colour	Width A (mm)	Height B (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
BM71H-1-7643-WT	250	White	60.00	10.00	40	4
BM71H-1-7643-YL	250	Yellow	60.00	10.00	40	4
BM71H-2-7643-WT	250	White	75.00	10.00	51	4
BM71H-2-7643-YL	250	Yellow	75.00	10.00	51	4
BM71H-3-7643-WT	250	White	75.00	25.00	51	10
BM71H-3-7643-YL	250	Yellow	75.00	25.00	51	10

Order references beginning with "B" indicate bulk rolls.



Tear Resistant Cable Markers

- **B-109 Polyethylene:** Provides extreme tear resistance and excellent cold-weather performance; meets requirements of DIN VDE 0472/parts 815
- **B-145 Polyethylene:** Tear resistant and 2-side printable, is UL94 V2 recognised




Diagram	Order Reference	Tags Per Roll	Colour	Width A (mm)	Height B (mm)	Write-on Area W x H (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Cable Type
	M71-12-109	100	White	19.05	76.20	17.78 x 52.07	45	6	Cable Bundles; Power & Ground Cables
	BM71-12-109	1,000	White	19.05	76.20	17.78 x 52.07	45	6	Cable Bundles
	M71-36-109	250	White	44.45	28.58	44.45 x 28.57	40	15	Power & Ground Cables
	BM71-111-145-GY	1,000	Grey	19.25	30.63	19.25 x 30.63	16	14	145C Tag; Power & Ground Cables
	BM71-110-145-GY	1,000	Grey	44.45	25.40	44.45 x 25.40	28	20	145P Tag; Power & Ground Cables

Order references beginning with "B" indicate bulk rolls.

Coloured Nylon Ties

Perfect for colour coded applications.

Size: 200 x 4 mm

Material: Nylon

Packing: 100 pieces

Order Reference	Colour	Order Reference	Colour
229955	White	229959	Yellow
229956	Blue	229960	Green
229957	Red	229961	Violet
229958	Orange	229962	Black



BL	Blue, for horizontal cable terminations
BR	Brown, for campus backbone cable terminations
GR	Green, network connections
GY	Grey, for backbone cable between intermediate cross-connect and telecommunications cabinet
OR	Orange, central office termination
PL	Purple, major switching and data equipment terminations
RD	Red, for all key telephone equipment terminations
YL	Yellow, for auxiliary, maintenance, alarms, security, etc.

Terminal Block Repositionable Markers

- **B-498:** Repositionable vinyl cloth

Order Reference	Label Width A (mm)	Label Length B (m) (continuous)	Max. Characters per line for 5 Points
M71C-240-498	6.10	9.14	4
M71C-318-498	8.08	9.14	7
BM71C-318-498	8.08	91.44	7
M71C-375-498	9.53	9.14	7
BM71C-375-498	9.53	91.44	7

Order references beginning with "B" indicate bulk rolls.
Order references with "C" (e.g. M71C) indicate continuous.




EPREP Labels – Engraved Plate Replacement Labels

- **B-7593:** Polyethylene Foam Laminate

BRADY EPREP labels are innovative labels specifically designed to replace engraved and plotted plates for identification of electrical components, electrical cabinets, push buttons, patch panels etc.

Diagram	Order Reference	Tags Per Roll	Colour	Width A (mm)	Height B (mm)	Diameter D (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Format
▲	M71EP-1-7593-SL	250	Silver	27.00	8.00		22	3	Roll
▲	M71EP-1-7593-WT	250	White	27.00	8.00		22	3	Roll
▲	M71EP-2-7593-SL	250	Silver	27.00	12.50		22	5	Roll
▲	M71EP-2-7593-WT	250	White	27.00	12.50		22	5	Roll
▲	M71EP-3-7593-SL	150	Silver	27.00	15.00		22	6	Roll
▲	M71EP-3-7593-WT	150	White	27.00	15.00		22	6	Roll
▲	M71EP-4-7593-SL	150	Silver	27.00	18.00		22	7	Roll
▲	M71EP-4-7593-WT	150	White	27.00	18.00		22	7	Roll
◻	M71EP-5-7593-BK	100	Black	30.00	40.00	24.00	24	5	Fanfolded
◻	M71EP-5-7593-GN	100	Green	30.00	40.00	24.00	24	5	Fanfolded
◻	M71EP-5-7593-RD	100	Black	30.00	40.00	24.00	24	5	Fanfolded
◻	M71EP-5-7593-SL	100	Silver	30.00	40.00	24.00	24	5	Fanfolded
◻	M71EP-5-7593-WT	100	White	30.00	40.00	24.00	24	5	Fanfolded
◻	M71EP-5-7593-YL	100	Yellow	30.00	40.00	24.00	24	5	Fanfolded
▲	M71EP-6-7593-BK	100	Black	45.00	15.00		36	6	Fanfolded
▲	M71EP-6-7593-RD	100	Black	45.00	15.00		36	6	Fanfolded
▲	M71EP-6-7593-YL	100	Yellow	45.00	15.00		36	6	Fanfolded
▲	BM71E-6-7593-SL	500	Silver	45.00	15.00		36	6	Bulk roll
▲	BM71E-6-7593-WT	500	White	45.00	15.00		36	6	Bulk roll
▲	M71EP-7-7593-SL	100	Silver	35.00	18.00		28	7	Roll
▲	M71EP-7-7593-WT	100	White	35.00	18.00		28	7	Roll
▲	M71EP-7-7593-YL	100	Yellow	35.00	18.00		28	7	Roll
▲	M71EP-8-7593-SL	125	Silver	48.00	19.00		39	7	Roll
▲	M71EP-8-7593-WT	125	White	48.00	19.00		39	7	Roll


Order references beginning with "B" indicate bulk rolls.





Roll



Fanfolded




Bulk roll



Nylon Cloth Labels

- **B-499:** White nylon cloth with high adhesion

Order Reference	Tags Per Roll	Label Diameter C (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
M71-82-499	500	9.52	7	2
M71-83-499	250	12.70	9	3



Datacom Labels

Self-Laminating Labels

- **B-427 Vinyl:** excellent abrasion and smudge resistance.





Diagram	Order Reference	Labels Per Roll	Label Width A (mm)	Label Height B (mm)	Write-on Height C (mm)	Application	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
X	BM71-19-427	2500	25.40	25.40	9.53	2 Pair Fibre	24	3
X	M71-19-427	250	25.40	25.40	9.53	2 Pair Fibre	24	3
X	M71-19-427-YL	250	25.40	25.40	9.53	2 Pair Fibre	24	3
X	BM71-21-427	1000	25.40	63.50	19.05	4 Pair STP, 25 Pair Copper, 4-12 Pair Fibre	24	8
X	M71-21-427	100	25.40	63.50	19.05	4 Pair STP, 25 Pair Copper, 4-12 Pair Fibre	24	8
X	M71-21-427-YL	100	25.40	63.50	19.05	4 Pair STP, 25 Pair Copper, 4-12 Pair Fibre	24	8
X	BM71-23-427	1000	25.40	101.60	25.40	50 Pair Copper, 24 Pair Fibre, Backbone cable	24	10
X	M71-23-427	100	25.40	101.60	25.40	50 Pair Copper, 24 Pair Fibre, Backbone cable	24	10
⊗	BM71-29-427	5000	12.70	38.10	12.70	CAT 5, 4 Pair UTP	11	5
⊗	M71-29-427	500	12.70	38.10	12.70	CAT 5, 4 Pair UTP	11	5
⊗	BM71-30-427	2500	19.05	38.10	12.70	CAT 5, 4 Pair UTP	18	5
⊗	M71-30-427	250	19.05	38.10	12.70	CAT 5, 4 Pair UTP	18	5
⊗	M71-30-427-BL	250	19.05	38.10	12.70	CAT 5, 4 Pair UTP	18	5
⊗	M71-30-427-PL	250	19.05	38.10	12.70	CAT 5, 4 Pair UTP	18	5
⊗	M71-30-427-RD	250	19.05	38.10	12.70	CAT 5, 4 Pair UTP	18	5
⊗	BM71-31-427	2500	25.40	38.10	12.70	4 Pair UTP, CAT 5, CAT 5E, RG-6 Coax, RG-59 Coax	24	5
⊗	M71-31-427	250	25.40	38.10	12.70	4 Pair UTP, CAT 5, CAT 5E, CAT 6, Silver Satin, RG-6 Coax, RG-59 Coax	24	5
⊗	M71-31-427-GN	250	25.40	38.10	12.70	4 Pair UTP, CAT 5, CAT 5E, CAT 6, Silver Satin, RG-6 Coax, RG-59 Coax	24	5
⊗	M71-31-427-RD	250	25.40	38.10	12.70	4 Pair UTP, CAT 5, CAT 5E, CAT 6, Silver Satin, RG-6 Coax, RG-59 Coax	24	5
⊗	M71-31-427-YL	250	25.40	38.10	12.70	4 Pair UTP, CAT 5, CAT 5E, CAT 6, Silver Satin, RG-6 Coax, RG-59 Coax	24	5
⊗	BM71-32-427	1000	38.10	38.10	12.70	CAT 5, 4 Pair UTP	37	5
⊗	M71-32-427	250	38.10	38.10	12.70	CAT 5, 4 Pair UTP	37	5
⊗	M71-32-427-YL	250	38.10	38.10	12.70	CAT 5, 4 Pair UTP	37	5
X	BM71-33-427	500	38.10	101.60	25.40	50 Pair Copper, 24 Pair Fibre, Backbone cable	37	10
X	M71-33-427	100	38.10	101.60	25.40	50 Pair Copper, 24 Pair Fibre, Backbone cable	37	10
X	M71-33-427-YL	100	38.10	101.60	25.40	50 Pair Copper, 24 Pair Fibre, Backbone cable	37	10
X	BM71-34-427	500	38.10	152.40	38.10	100 Pair Copper, 36 Pair Fibre	37	16
X	M71-34-427	50	38.10	152.40	38.10	100 Pair Copper	37	16
X	BM71-64-427	1000	25.40	85.73	28.58	Fibre/Coax	24	12
X	M71-64-427	100	25.40	85.73	28.58	Fibre/Coax	24	12
X	M71-66-427	100	49.23	80.01	25.40	50 Pair Copper, 24 Pair Fibre, Backbone cable	46	10
X	M71-88-427	250	44.45	38.10	12.70	CAT 5, 4 Pair UTP	40	5
X	M71-103-427	250	25.40	31.75	12.70	CAT 5, 4 Pair UTP	24	5
X	M71-104-427	250	38.10	25.40	9.53	2 Pair Fibre, Single/Multi-Mode	37	3
X	BM71-107-427	1000	50.80	38.10	12.70	CAT 5, 4 Pair UTP	46	5
⊗	M71-107-427	100	50.80	38.10	12.70	CAT 5, 4 Pair UTP	46	5
X	BM71-109-427	500	38.10	101.60	38.10	50 Pair Copper, 24 Pair Fibre, Backbone cable	37	16
X	M71-109-427	100	38.10	101.60	38.10	50 Pair Copper, 24 Pair Fibre, Backbone cable	37	16

Order references beginning with "B" indicate bulk rolls.

TubeSleeve Carriers

Brady TubeSleeve Carriers are the ideal complement to self-laminating labels, where the cables are thin and available space for text is small. Apply the tubesleeve to the cable and then apply the self-lam. The limited available space is increased significantly, giving you the possibility of printing more text.

Order Reference	Sleeves Per Pack	Min. Cable Diameter (mm)	Max. Cable Diameter (mm)	Recommended Label
BTS1426	1000	1.00	4.00	M71-31-427
BTS4626	1000	4.00	6.00	M71-31-427
BTS6826	400	6.00	8.00	M71-23-423
BTS81226	250	8.00	12.00	M71-23-423



Fibre Optic Labels/Flags

• B-425 Polypropylene




Diagram	Order Reference	Labels Per Roll	Label Width A (mm)	Label Height B (mm)	Application	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
T	M71FT-1-425	250	30.00	20.00	Fibre Strand	24	8
P	M71FP-1-425	250	30.00	20.00	Fibre Strand	24	8
P	M71FP-2-425	250	44.45	25.40	Fibre Strand	35	10

Power and Ground Cable Tags

- **B-109 Polyethylene:** Extreme tear resistance
- **B-145 Polyethylene:** Tear resistant and 2-side printable
- **B145FR Polyethylene:** Tear resistant, 2-side printable and flame retardant




Diagram	Order Reference	Tags Per Roll	Colour	Width A (mm)	Height B (mm)	Write-on Area W x H (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Application
⊙	BM71-12-109	1000	White	19.05	76.20	17.78 x 52.07	45	6	Communications Cables, Power & Ground Cables
⊙	M71-12-109	100	White	19.05	76.20	17.78 x 52.07	45	6	Communications Cables
●	M71-36-109	250	White	44.45	28.58	44.45 x 28.57	40	15	Cable Labels
●	BM71-111-145-GY	1000	Grey	30.63	19.25	19.25 x 30.63	16	14	Cable Labels
●	M71-111-145FR-GY	100	Grey	30.63	19.25	19.25 x 30.63	16	14	Cable Labels
●	M71-111-145-GY	100	Grey	30.63	19.25	19.25 x 30.63	16	14	Cable Labels
●	M71-110-145FR-GY	100	Grey	44.45	25.40	44.45 x 25.40	28	20	Cable Labels
●	BM71-110-145-GY	1000	Grey	44.45	25.40	44.45 x 25.40	28	20	Cable Labels
●	M71-110-145-GY	100	Grey	44.45	25.40	44.45 x 25.40	28	20	Cable Labels

Order references beginning with "B" indicate bulk rolls.

Datacom Labels

Workstation Labels

- B-412 Polypropylene
- B-422 Permanent Glossy Polyester
- B-430 Clear Polyester




Diagram	Order Reference	Labels Per Roll	Label Width A (mm)	Label Height B (mm)	Application	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
▲	M71-16-430	500	25.40	9.53	Location ID, 1-4 Outlet Faceplates	24	3
▲	M71-17-430	500	25.40	12.70	Location ID, 1-4 Outlet Faceplates	24	5
■	BM71-40-412	5000	49.23	9.53	Desi-Strip Inserts	40	3
■	M71-40-412	750	49.23	9.53	Desi-Strip Inserts	40	3
▲	M71-45-422	500	38.10	9.53	Location ID	37	3
▲	M71-45-430	500	38.10	9.53	Location ID	37	3
▲	M71-68-430	750	6.10	3.81	Siemon Faceplates	4	2
▲	M71-71-430	750	8.89	5.08	Siemon Faceplates	7	2

Order references beginning with "B" indicate bulk rolls.

Patch Panel Identification

- B-412 Polypropylene Tag
- B-422 Permanent Glossy Polyester
- B-423 Permanent Polyester
- B-430 Permanent Clear Polyester




Diagram	Order Reference	Tags Per Roll	Label Width A (mm)	Label Height B (mm)	Application	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
▲	M71-10-423	750	19.05	6.35	Patch Panel - ID Port, Voice/Data Identification	18	2
●	M71C-230-412	1 (cont.)	5.84	15.24 m	Broadcast Patch Bay Strips	50	4
●	M71C-375-412	1 (cont.)	9.53	15.24 m	Broadcast Patch Bay Strips	50	3
●	M71C-375-422	1 (cont.)	9.53	15.24 m	Outlet, Pach panel, Cont. Tape, Cut to size	50	3
●	M71C-375-430	1 (cont.)	9.53	15.24 m	Outlet, Pach panel, Cont. Tape, Cut to size	50	3
●	M71C-475-412	1 (cont.)	12.70	15.24 m	Broadcast Patch Bay Strips, Racks& Panels	50	4
●	M71C-500-412	1 (cont.)	12.70	15.24 m	Broadcast Patch Bay Strips	50	5
●	M71C-500-422	1 (cont.)	12.70	15.24 m	Outlet, Pach panel, Cont. Tape, Cut to size	50	5
●	M71C-500-430	1 (cont.)	12.70	15.24 m	Outlet, Pach panel, Cont. Tape, Cut to size	50	5
●	M71C-785-412	1 (cont.)	19.94	15.24 m	Broadcast Patch Bay Strips	50	8



For more information on our materials or to help you choose, visit www.bradyeurope.com

Racks, Panels and General Identification

- B-412 Polypropylene Tag
- B-422 Permanent Glossy Polyester
- B-423 Permanent Polyester
- B-430 Permanent Clear Polyester




Diagram	Order Reference	Labels Per Roll	Label Width A (mm)	Label Height B (mm)	Application	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points
▲	BM71-20-422	1000	50.80	25.40	Racks, Panels & General ID	46	10
▲	M71-20-483	100	50.80	25.40	Racks, Panels & General ID	46	10
▲	M71-23-483	100	101.60	25.40	Racks, Panels & General ID	50	9
▲	M71-30-483	250	38.10	19.05	Racks, Panels & General ID	37	8
▲	M71-31-483	250	38.10	25.40	Racks, Panels & General ID	37	10
▲	M71-37-422	100	76.20	48.26	Racks, Panels & General ID	50	20
▲	M71-37-483	100	76.20	48.26	Racks, Panels & General ID	50	20
▲	M71-38-483	100	101.60	48.26	Racks, Panels & General ID	50	20
▲	M71-61-483	100	12.70	50.80	Racks, Panels & General ID	50	5
▲	M71-65-483	250	34.93	25.40	Racks, Panels & General ID	35	10
●	M71C-230-412	1 (cont.)	5.84	15.24 m	Racks, Panels & General ID	50	2
●	M71C-375-412	1 (cont.)	9.53	15.24 m	Racks, Panels & General ID	50	3
●	M71C-375-422	1 (cont.)	9.53	15.24 m	Closet Hardware Labels, Racks, Panels & General ID	50	3
●	M71C-375-430	1 (cont.)	9.53	15.24 m	Closet Hardware Labels, Racks, Panels & General ID	50	3
●	M71C-500-412	1 (cont.)	12.70	15.24 m	Racks, Panels & General ID	50	5
●	M71C-500-422	1 (cont.)	12.70	15.24 m	Racks, Panels & General ID	50	5
●	M71C-500-430	1 (cont.)	12.70	15.24 m	Racks, Panels & General ID	50	5
●	M71C-500-483	1 (cont.)	12.70	15.24 m	Racks, Panels & General ID	50	5
●	M71C-785-412	1 (cont.)	19.94	15.24 m	Racks, Panels & General ID	50	8
●	M71C-1000-422	1 (cont.)	25.40	15.24 m	Racks, Panels & General ID	50	10
●	M71C-1000-430	1 (cont.)	25.40	15.24 m	Racks, Panels & General ID	50	5
●	M71C-1000-483	1 (cont.)	25.40	15.24 m	Racks, Panels & General ID	50	10
●	M71C-1900-483	1 (cont.)	48.26	15.24 m	Racks, Panels & General ID	50	10

Order references beginning with "B" indicate bulk rolls.





Bulk Packaging

Bulk labels are designed for the BMP™71 Label Printer as a cost-effective solution for high volume labelling needs.

Order references beginning with "B" indicate bulk rolls.

Circuit Board and Component Identification Labels

Material to Circuit Board Process Cross Reference Guide






Brady material number (B-number)				Through Hole Technology		Surface Mount Technology (SMT)		After Process
				Top	Bottom	Top or Bottom		
B-426	B-457	B-478	B-479	✓ YES	✓ YES	✓ YES	✓ YES	
B-422	B-423	B-428	B-437	✓ YES*	✗ NO	✗ NO	✓ YES	
B-459	B-473	B-498*						

*In extreme high temperatures, testing of these materials is recommended.

Polyimides

- **B-426 High Temperature Amber Polyimide:**
Withstands extremely high temperatures
- **B-457 High Temperature White Polyimide:**
good contrast and smear resistance
- **B-477 Static Dissipative Polyimide:**
Static dissipative adhesive and liner
- **B-478 Static Dissipative Polyimide:**
Static dissipative adhesive and liner; low profile






Order Reference	Labels Per Roll	Width A (mm)	Height B (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Max. Bar Code Characters**	Through Hole Technology		SMT Top/Bottom	After Process
							Top	Bottom		
M71-2-477	100	6.35	50.80	41	2	23*	✓	✓	✓	✓
M71-3-457	500	9.53	9.53	7	3	1	✓	✓	✓	✓
M71-4-478	500	10.16	10.16	8	4	2	✓	✓	✓	✓
M71-9-426	750	16.51	5.08	13	2	5*	✓	✓	✓	✓
M71-9-478	750	16.51	5.08	13	2	5*	✓	✓	✓	✓
M71-10-457	750	19.05	6.35	15	2	6*	✓	✓	✓	✓
M71-13-426	750	22.86	6.35	18	2	8*	✓	✓	✓	✓
M71-14-477	750	25.40	4.75	20	1	10	✓	✓	✓	✓
M71-16-426	500	25.40	9.53	20	4	10	✓	✓	✓	✓
M71-16-457	500	25.40	9.53	20	4	10	✓	✓	✓	✓
M71-17-426	500	25.40	12.70	20	5	10	✓	✓	✓	✓
M71-25-478	750	31.75	6.35	26	2	13*	✓	✓	✓	✓
M71-28-426	750	38.10	6.35	31	2	17*	✓	✓	✓	✓

*No human readable characters below / above barcode

**Values for barcode 128, width 2 Dot, ratio 2:1

Tedlar®

- **B-437 Flame-Retardant White Tedlar®**



Order Reference	Labels Per Roll	Width A (mm)	Height B (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Max. Bar Code Characters**	Through Hole Technology		SMT Top/Bottom	After Process
							Top	Bottom		
M71-10-437	750	19.05	6.35	15	2	6*	✓	✗	✗	✓
M71-15-437	750	25.40	6.99	20	2	10*	✓	✗	✗	✓
M71-29-437	500	38.10	12.70	31	5	17	✓	✗	✗	✓

Tedlar® is a registered trademark of DuPont.

*No human readable characters below / above barcode

**Values for barcode 128, width 2 Dot, ratio 2:1

✓ Yes, this material will work with this application.


✗ No, this material does not work with this application.

✓ In extreme high temperatures, testing of these materials is recommended.

Circuit Board and Component Identification Labels

Vinyl Cloth

- **B-498 White Vinyl Cloth:**
with repositionable adhesive



Order Reference	Labels Per Roll	Width A (mm)	Height B (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Max. Bar Code Characters**	Through Hole Technology		SMT Top/Bottom	After Process
							Top	Bottom		
M71-7-498	500	12.70	12.70	10	5	3	✓	✗	✗	✓
M71-10-498	750	19.05	6.35	15	2	6*	✓	✗	✗	✓
M71-16-498	500	25.40	9.53	20	4	10	✓	✗	✗	✓
M71-17-498	500	25.40	12.70	20	5	10	✓	✗	✗	✓
BM71-29-498	5000	38.10	12.70	31	5	17	✓	✗	✗	✓
M71-29-498	500	38.10	12.70	31	5	17	✓	✗	✗	✓
M71-32-498	250	38.10	38.10	37	16	17	✓	✗	✗	✓


*No human readable characters below / above barcode

**Values for barcode 128, width 2 Dot, ratio 2:1

Order references beginning with "B" indicate bulk rolls.

Polyester

- **B-423, B-459 Permanent White Polyester:**
- **B-428 Permanent Metallised Polyester:**
- **B-473 Static Dissipative Polyester:**
Static dissipative adhesive and liner



Order Reference	Labels Per Roll	Width A (mm)	Height B (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Max. Bar Code Characters**	Through Hole Technology		SMT Top/Bottom	After Process
							Top	Bottom		
M71-1-423	750	6.35	6.35	5	2	0	✓	✗	✗	✓
M71-2-423	100	50.80	6.35	41	2	23*	✓	✗	✗	✓
M71-3-423	500	9.53	9.53	7	3	0	✓	✗	✗	✓
M71-4-423	500	10.16	10.16	8	4	0	✓	✗	✗	✓
M71-5-423	750	12.70	5.08	11	1	3	✓	✗	✗	✓
M71-6-423	750	12.70	6.99	11	2	3	✓	✗	✗	✓
M71-6-473	750	12.70	6.99	11	2	3	✓	✗	✗	✓
M71-7-423	500	12.70	12.70	10	5	3	✓	✗	✗	✓
BM71-7-423	5000	12.70	12.70	10	5	3	✓	✗	✗	✓
M71-9-423	750	16.51	5.08	13	2	5*	✓	✗	✗	✓
M71-9-473	750	16.51	5.08	13	2	5*	✓	✗	✗	✓
M71-10-423	750	19.05	6.35	15	2	6*	✓	✗	✗	✓
M71-10-473	750	19.05	6.35	15	2	6*	✓	✗	✗	✓
M71-13-423	750	22.86	6.35	18	2	8*	✓	✗	✗	✓
M71-14-423	750	25.40	4.75	20	1	10	✓	✗	✗	✓
M71-15-423	750	25.40	6.99	20	2	10	✓	✗	✗	✓
M71-15-428	750	25.40	6.99	20	2	10	✓	✗	✗	✓
M71-16-423	500	25.40	9.53	20	4	10	✓	✗	✗	✓
BM71-16-423	5000	25.40	9.53	20	4	10	✓	✗	✗	✓
M71-16-473	500	25.40	9.53	20	4	10	✓	✗	✗	✓
M71-17-423	500	25.40	12.70	20	5	10	✓	✗	✗	✓
BM71-17-423	5000	25.40	12.70	20	5	10	✓	✗	✗	✓
M71-17-428	500	25.40	12.70	20	5	10	✓	✗	✗	✓
M71-17-473	500	25.40	12.70	20	5	10	✓	✗	✗	✓
M71-19-423	250	25.40	25.40	20	10	10	✓	✗	✗	✓
BM71-19-423	2500	25.40	25.40	20	10	10	✓	✗	✗	✓
M71-20-423	100	50.80	25.40	41	10	23	✓	✗	✗	✓
BM71-20-423	1000	50.80	25.40	41	10	23	✓	✗	✗	✓
M71-20-459	100	50.80	25.40	41	10	23	✓	✗	✗	✓
M71-25-423	750	31.75	6.35	26	2	13*	✓	✗	✗	✓
M71-26-423	100	69.85	31.75	57	12	32	✓	✗	✗	✓
M71-27-423	750	38.10	3.18	31	1	17	✓	✗	✗	✓
M71-28-423	750	38.10	6.35	31	2	17	✓	✗	✗	✓
M71-28-473	750	38.10	6.35	31	2	17	✓	✗	✗	✓
M71-29-423	500	38.10	12.70	31	5	17	✓	✗	✗	✓
BM71-29-423	5000	38.10	12.70	31	5	17	✓	✗	✗	✓
M71-29-459	500	38.10	12.70	31	5	17	✓	✗	✗	✓
M71-30-459	250	38.10	19.05	31	8	17	✓	✗	✗	✓
M71-37-423	100	76.20	48.26	60	19	35	✓	✗	✗	✓
M71-38-423	100	101.60	48.26	82	19	47	✓	✗	✗	✓
M71C-500-423	1 (cont.)	12.70	15.24 m	50	5		✓	✗	✗	✓

*No human readable characters below / above barcode

**Values for barcode 128, width 2 Dot, ratio 2:1

Order references beginning with "B" indicate bulk rolls.

✓ Yes, this material will work with this application.

✗ No, this material does not work with this application.

✓ In extreme high temperatures, testing of these materials is recommended.

Security Identification Labels

Tamper Indicating Labels

- B-351 Tamper-Resistant White Vinyl
- B-352 Tamper-Resistant Metallised Vinyl
- B-530 Tamper-Resistant White Vinyl




Diagram	Order Reference	Labels Per Roll	Colour	Width A (mm)	Height B (mm)	Max. Characters per line for 5 Points	Max. Lines of Text for 5 Points	Surface Suitability
▲	M71-17-351	500	White	25.40	12.70	20	5	✓
▲	M71-17-352	500	Silver	25.40	12.70	20	5	✓
▲	M71-20-351	100	White	50.80	25.40	46	10	✓
▲	M71-20-352	100	Silver	50.80	25.40	46	10	✓
▲	M71-31-351	250	White	38.10	25.40	37	10	✓
▲	M71-31-352	250	Silver	38.10	25.40	37	10	✓
▲	M71-37-351	100	White	76.20	48.26	50	20	✓
▲	M71-37-352	100	Silver	76.20	48.26	50	20	✓
●	M71C-500-530	1 (cont.)	White	12.70	15.24 m	50	2	✓
●	M71C-1000-530	1 (cont.)	White	25.40	15.24 m	50	5	✓
●	M71C-2000-530	1 (cont.)	White	50.80	15.24 m	50	10	✓

✓ Material suitable for smooth surfaces.

✓ Material suitable for smooth and textured surfaces.

✓ Material suitable for smooth, textured and highly textured surfaces.

Laboratory Identification Labels

- F** Freezer
- N** Liquid nitrogen

- A** Autoclave
- H** Hot water (100°C) bath

Self-Laminating Labels

- B-427 Vinyl: excellent abrasion and smudge resistance.
- B-461 Polyester: resistant to extreme temperatures (-196°C to 130°C)




Diagram	Order Reference	Labels Per Roll	Label Width A (mm)	Label Height B (mm)	Write-On Height C (mm)	Environment	Application	Vial/Tube size
✗	M71-19-427	250	25.40	25.40	9.53	F N	Straws	0.25 mL Straw
✗	BM71-19-427	2500	25.40	25.40	9.53	F N	Straws	0.2 5mL Straw
✗	M71-19-427-YL	250	25.40	25.40	9.53	F N	Straws	0.25 mL Straw
✗	M71-21-427	100	25.40	63.50	19.53	F N	Straws	0.5 ml Straw
✗	BM71-21-427	1000	25.40	63.50	19.53	F N	Straws	0.5 ml Straw
✗	M71-21-427-YL	100	25.40	63.50	19.53	F N	Straws	0.5 ml Straw
✗	M71-30-427-AW	250	38.10	19.05	–	F N	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
⊗	BM71-30-427	2500	19.05	38.10	12.70	F N	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
✗	BM71-75-461	1000	66.68	25.40	25.40	F N A H	Cryo Vial	1.0 - 8.0 ml Vial/Tube

AW = All White (no transparent area) – YL = Yellow

Order references beginning with "B" indicate bulk rolls.

Vinyl & Nylon Cloth Labels

- **B-498 Vinyl Cloth:**
repositionable adhesive
- **B-499 Nylon Cloth:**
high adhesion




Diagram	Order Reference	Labels Per Roll	Label Width A (mm)	Label Height B (mm)	Label Diameter C (mm)	Environment	Application	Vial/Tube size
▲	M71-11-498	500	12.70	19.05	-	F	Centrifuge, Eppendorf, PCR Tube	0.5 - 0.7ml Tube
▲	BM71-11-498	5000	12.70	19.05	-	F	Centrifuge, Eppendorf, PCR Tube	0.5 - 0.7ml Tube
▲	M71-11-499	500	12.70	19.05	-	F N A	Centrifuge, Eppendorf, PCR Tube, Cryo Vial	0.5 - 0.7ml Tube - 0.6ml Vial/Tube
▲	M71-16-498	500	9.53	25.40	-	F	Centrifuge, Eppendorf, PCR Tube	0.5 - 0.7ml Tube
▲	M71-16-499	500	9.53	25.40	-	F N A	Centrifuge, Eppendorf, PCR Tube	0.5 - 0.7ml Tube
▲	M71-17-498	500	25.40	12.70	-	F	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-29-498	500	38.10	12.70	-	F	Conical Tube, Cryo Vial, Bottles, Petri Dish, Deep Well Plate	12.0 - 24.0ml Vial/Tube 50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	BM71-29-498	5000	12.70	38.10	-	F	Cryo Vial, Conical Tube, Bottles, Petri Dish, Deep Well Plate	12.0 - 24.0ml Vial/Tube 50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-29-499	500	12.70	38.10	-	F N A	Conical Tube, Cryo Vial, Bottles, Petri Dish, Deep Well Plate	12.0 - 24.0ml Vial/Tube 50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-30-499	250	19.05	38.10	-	F N A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-31-498	250	25.40	38.10	-	F	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-31-499	250	25.40	38.10	-	F N A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-78-499	250	48.26	25.40	-	F N A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-81-499	750	48.26	6.35	-	F N A	Well Plate	
▼	M71-82-499	500	-	-	9.53	F N A	Vial Top	0.6 - 1.5ml Vial/Tube
▼	M71-83-499	500	-	-	9.53	F N A	Vial Top	1.0 - 2.0ml Vial/Tube
▲	M71-84-499	500	22.86	12.70	-	F N A	Centrifuge, Cryo Vial, Eppendorf, PCR Tube	0.5 - 0.7ml Tube - 1.5 - 2.0ml Tube 0.6 ml Vial/Tube - 1.0 - 8.0ml Vial/Tube
◆	M71-98-499	500	25.40	9.53	9.53	F N A	Centrifuge, Cryo Vial, Eppendorf, PCR Tube, Vial, Vial Top	0.5 - 0.7ml Tube - 1.0 - 8.0ml Vial/Tube 0.6 - 1.5ml Vial/Tube

Order references beginning with "B" indicate bulk rolls.

Polyester Labels

- **B-423 Glossy White Polyester**
- **B-430 Glossy Clear Polyester**
- **B-488 Matt White Polyester**





Diagram	Order Reference	Labels Per Roll	Label Width A (mm)	Label Height B (mm)	Environment	Application	Vial/Tube size
▲	M71-2-423	100	50.80	6.35	F A	Well Plate	
▲	M71-7-423	500	12.70	12.70	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	BM71-7-423	5000	12.70	12.70	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-14-423	750	25.40	4.75	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-15-423	750	25.40	6.99	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-17-423	500	25.40	12.70	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-17-430	500	25.40	12.70	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-20-423	100	50.80	25.40	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	BM71-20-423	1000	50.80	25.40	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-22-423	100	76.20	25.40	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-31-423	250	38.10	25.40	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate
▲	M71-80-488	250	19.05	22.86	F A	Slide	
▲	M71-81-488	750	48.26	6.35	F A	Well Plate	
▲	M71-97-488	250	22.86	22.86	F A	Slide	
▲	M71C-500-430	1 (cont.)	12.70	15.24M	F A	Conical Tube, Bottles, Petri Dish, Deep Well Plate	50.0 ml Conical Tube/Bottles/Petri Dish/Deep Well Plate

Order references beginning with "B" indicate bulk rolls.

Brady Corporation

“Our mission is to provide innovative identification solutions which improve safety, security, productivity and performance for customers worldwide.”



Company Overview

Brady was founded in 1914 in Eau Claire, Wisconsin, as W.H. Brady Co., and renamed Brady Corporation in 1998. The company began selling products internationally in 1947. In 1984, Brady went public, with stock trading on the Nasdaq Stock Market, and in 1999, moved trading of its stock to the New York Stock Exchange, where it trades under the symbol BRC. The company's global headquarters is in Milwaukee, Wisconsin.

Brady manufactures and markets:

- products for identification and safety applications such as signs and markers, and the printers and software to produce them
- products for wire identification, including labelling materials and tools for wire and cable marking in the electrical and telecommunication markets
- high-performance identification products, including labels and signs that remain legible and highly adhesive even in harsh environments
- precision die-cut parts, including custom die-cut and slit materials for use in cellular phones, pagers, computer disk drives and automotive electronic components

Operations – Some facts:

- 7000 employees around the world
- Operations in 26 countries
- Distribution in more than 100 countries through more than 4,400 distributor partners



BRADY Belgium
Industriepark C/3
Lindestraat 20
9240 Zele
Tel. +32 (0) 52 45 78 11
Fax +32 (0) 52 45 78 12

BRADY Denmark
Svendborgvej 39B
5260 Odense S
Tel. +45 66 14 44 00
Fax +45 66 14 44 50

BRADY France
Parc EUROGIT
45, avenue de l'Europe
59436 Roncq Cedex
Tel. +33 (0) 3 20 01 08 70
Fax +33 (0) 3 20 01 08 76

BRADY Germany
Büchenhöfe 2
63329 Egelsbach
Tel. +49 (0) 6103 7598 660
Fax +49 (0) 6103 7598 670

BRADY Hungary
Puskás Tivadar u. 4.
2040 Budaörs
Tel. +36 23 500 275
Fax +36 23 500 276

BRADY Italy
Via Pitagora 18
20128 Milano
Tel. +39 02 26 00 00 22
Fax +39 02 25 75 351

BRADY Middle-East
PO BOX 18015
Jebel Ali, Dubai, UAE
Tel. +971 4881 2524
Fax +971 4881 3183

BRADY Norway
Breivika Industrivei 9
6018 Ålesund
Tel. +47 70 19 10 30
Fax +47 70 19 05 67

Brady Slovakia
Na Páňoch 18
831 06 Bratislava
Tel. +421 2 3300 4800
Fax +421 2 3300 4801

BRADY Spain
Carretera de Barcelona, 88
Esc B Entresuelo 9C
08302 Mataró
Tel. +34 900 902 993
Fax +34 900 902 994

Brady Sweden
Vallgatan 5
170 67 Solna
Tel. +46 (0) 8 590 057 30
Fax +46 (0) 8 590 818 68

BRADY Turkey
Selvili Sok. No: 3/4
4. Levent Istanbul 34330
Tel. +90 212 264 02 20 / 264 02 21
Fax +90 212 270 83 19

BRADY United Kingdom
Wildmere Industrial Estate
Banbury, Oxon – OX16 3JU
Tel. +44 (0) 1295 228 288
Fax +44 (0) 1295 228 100

BRADY WORLDWIDE
Africa 971-4881-2524
Australia 612-8717-6300
Brazil 55-11-3686-4720
Canada 1-800-263-6179
China (Beijing) 86-10-6788-7799
China (Shanghai) 86-21-6886-3666
China (Wuxi) 86-510-528-2222
Hong Kong 852-2359-3149
Japan 81-45-461-3600
Korea 82-31-451-6600
Latin America 1-414-540-5560
Malaysia 60-4-646-2700
Mexico 525-399-6963
New-Zealand 61-2-8717-2200
Philippines 63-2-658-2077
Singapore 65-6477-7261
Taiwan 886-3-327-7788
Thailand 66-2-793-9200
U.S.A. 1-800-537-8791

Your distributor



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [brady](#) manufacturer:

Other Similar products are found below :

[BMP21-PLUS-KIT1](#) [60338](#) [M71C-2000-595-YL](#) [66271](#) [67063](#) [PSPT-375-175-YL](#) [PTL-28-427](#) [DAT-18-502-10](#) [DAT-38-292-1](#) [DAT-38-292-2.5](#) [DAT-43-502-1](#) [131070](#) [134289](#) [134304](#) [143091](#) [ECL-107-619](#) [B33-9-427](#) [18406](#) [18453](#) [18617](#) [18669](#) [LAT-31-747-1](#) [LAT-47-707-10](#) [LAT-5-747-10](#) [SCN03-1](#) [SCN03-8](#) [SCN10-7](#) [SCN10-8](#) [29750](#) [30153](#) [18472](#) [18489](#) [18491](#) [18581](#) [AF-1-9-PK](#) [PSPT-187-175-YL](#) [29690](#) [PTL-17-422](#) [PTL-42-439](#) [PWC-PK-1](#) [30206](#) [33108](#) [3450-A](#) [3450-D](#) [3450-G](#) [34511](#) [34513](#) [34515](#) [34517](#) [34518](#)