

308-30420



Article Number: 308-30420

Heat Shrink Tubing, HIS-3-Bag, 3:1, 3/16", 4.8/1.5 dia., Polyolefin, Black, 10/pkg



Download spec sheet

Base Data

Local Order Number 308-30420

Type HIS-3-BAG 4.5/1.5 BK

Color Black (BK)

Features and Benefits

- Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters.
- Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing).
- Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels.
- Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications.

Product Description TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing. and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes.

Short Description Heat Shrink Tubing, HIS-3-Bag, 3:1, 3/16", 4.8/1.5 dia., Polyolefin, Black, 10/pkg

Product Dimensions

Length L (Metric) 200 mm

Length L3 (imperial) 6.0 "

Length L3 (metric) 152.4 mm

Shrink Ratio 3:1

Tensile Strength (MPa) 14 MPa

Trade Size 3/16 "

Variant Thin-Wall

Volume Resistance (Ohm cm) 10¹¹ Ω cm (ASTM D 876)

Nominal Diameter (Imperial) 3/16 "

Nominal Diameter (Metric) 4.5 mm

Wall Thickness WT (Imperial) 0.024 "

Wall Thickness WT (Metric) .60 mm

Recovered Diameter d (metric) 1.5 mm

Recovered Diameter d (imperial) 0.059 "

Supplied Diameter D (metric) 4.8 mm

Supplied Diameter D (imperial) 0.188 "

Logistics and Packaging

Quantity Per bag

Package Quantity 10

Package Quantity (Metric) 10 Pieces

Material and Specifications

Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
Dielectric Strength (Metric)	20 kV/mm according to ASTM D 150
Elongation at break	800% nach ASTM D2671
Flammability	UL224 VW-1 (except clear)
Shrink Temperature	+212 °F (+100 °C)
Operating Temperature	-67°F to +275°F (-55°C to +135°C)
ROHS Compliant	Yes
Certification/Specification	SAE - AMS - DTL-23053/5 Class 2 (clear) SAE - AMS - DTL-23053/5 Class 1 and 3 UL224 125 °C 600V VW-1
UL Listed (US and Canada)	Yes

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)