

General Information

S1-M3-25 **Extended Product Type:**

Product ID: 1SAM201907R1103 EAN: 4013614400827

Catalog Description: S1-M3-25 Power Infeed Block

Long Description: S1-M3-25 3-phase power infeed block Flat, for MS116 / MS132, 25mm2, Type E

Categories

Products » Low Voltage Products and Systems » Control Products » Manual Motor Starters » Manual Motor Starters Accessories

Ordering

Minimum Order Quantity: 1 piece **Customs Tariff Number:** 85369010 EAN: 4013614400827

Container Information

Package Level 1 Length: 245 mm Package Level 1 Height: 38 mm Package Level 1 Gross Weight: 0.45 kg 4013614488207 Package Level 1 EAN: Package Level 1 Units: 10 piece Package Level 1 Width: 59 mm

Dimensions

Product Net Height: 43.95 mm 32 mm **Product Net Depth: Product Net Weight:** 0.042 kg **Product Net Width:** 43.8 mm

Technical

Rated Operational Current (Ie): 65 A Degree of Protection: IP20

Connecting Capacity Main Circuit: Rigid 1x 6 ... 25 mm² Flexible 1x 6 ... 16 mm²

Main Circuit 2.5 N·m

Tightening Torque: Wire Stripping Length: Main Circuit 10 mm

Recommended Screw Driver: Pozidriv 2 M3.5

Standards: IEC/EN 60947-1 IEC/EN 60947-4-1

UL 60947-1 UL 60947-4-1

Product Name: Power Infeed Block

Suitable For: MS116 MS132

Suitable for Product Class: Manual Motor Starter

690 V Rated Operational Voltage:

Environmental

Following EU Directive 2002/95/EC August 18, 2005 and amendment **RoHS Status:**

Ambient Air Temperature: Operation -25 +70 °C Storage -50 ...+80 °C

Technical UL/CSA

UL/CSA:

Ampere Rating UL/CSA: 65 A

Connecting Capacity Main Circuit UL/CSA:

Stranded 1/2x 10 ... 4 AWG Flexible 1/2x 10 ... 6 AWG

Tightening Torque UL/CSA: **Maximum Operating Voltage**

Main Circuit 22 in lb Main Circuit 600 V

Certificates and Declarations (Document Number)

2CDC131011M6802 2CDC131034M6801 **Instructions and Manuals:**

2CDC131022M6802

cUL Certificate: 1SAA963001-1701 Data Sheet, Technical Information: 1SBC100192C02-**Declaration of Conformity - CE:** 1SAD938510-0056 **GOST Certificate:** 1SAA937000-2703 **RoHS Information:** 1SAA963003-4402 **UL Certificate:** 1SAA963001-1602

Classifications

E-nummer:	3112082
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC002498 - Accessories for low-voltage switch technology
ETIM 6:	EC002498 - Accessories for low-voltage switch technology
eClass:	7.0 27379201
Object Classification Code:	X



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for abb manufacturer:

Other Similar products are found below:

TV10-516R 017667013 RF727 2CMA100178R1000 5SDD 92Z0401 ESV14-BS EZS-21-250 F204AC-40/0.03 F362-25/0.03

GJL1211001R0011 GJL1211201R8000 GJL1211501R8000 GJL1213001R0017 GJL1213001R0101 GJL1311001R0101 GJL1311001R8010

GJL1311201R0001 GJL1313001R0011 GJL1313001R0101 GJL1317201R0001 A40-30-10-84 AF09-30-01-11 AF460-30-11-68 1455 B14
250 EF45-30 ERG297 HSC2-20 ISAM201904R1001 ISAM350000R1003 ISAZ721201R1009 ISAZ721201R1014 ISAZ721201R1025

ISDA057197R1 ISFA611101R1002 ISFA611130R1103 ISFA611131R1101 ISFA611143R1101 ISFA611202R1108 ISFA611203R1108

ISFA611215R1001 ISFA611216R1108 ISFA611285R1002 ISFA611702R6006 ISFA616162R1025 ISFA619100R3015

ISVR730020R0200 IPC4111 OS30FACC12 OS60GJ03