

## This document was generated on 09/29/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0749801004		⇒ 0 <sup>A</sup>
Status: Active			9-114
Overview:VHDM-HSD™ BackplaneDescription:VHDM-HSD™ BackplanePin End Version, 40 Circ		ane Connectors ane Header, 2.00mm Pitch, 6-Row, Guide Pin Signal Module, ircuits, Pin Length 5.15mm. Series:74984 Enables designers to connectors utilizing standard pin lengths 4.25, 4.75, 5.15 and	
Documents: Drawing (PDF) Product Specification I	PS-74031-999 (PDF)	RoHS Certificate of Compliance (PDF)	Series image - Reference only
Agency Certification CSA		LR19980	EU ELV Not Reviewed
UL		E29179	EU RoHS China RoHS
General			Not Reviewed
Product Family		Backplane Connectors	REACH SVHC
Series		74980	Not Reviewed
Application		Backplane	Halogen-Free
Application Tooling Do	cuments	TM-622010999	Status
Comments		No Keying Orientation	Not Reviewed
Component Type		PCB Header	Need more information on product
Overview		VHDM-HSD <sup>™</sup> Backplane Connectors	environmental compliance?
Product Name		VHDM-HSD™	
UPC Physical		822350642651	Email <u>productcompliance@molex.com</u> Please visit the <u>Contact Us</u> section for any non-product compliance questions.
Circuits (Loaded)		40	
Circuits (maximum)		40	China ROHS Not Reviewed
Color - Resin		Black	ELV Not Reviewed
Durability (mating cycle	es max)	200	,
First Mate / Last Break		No	
Flammability		94V-0	Search Parts in this Series
Guide to Mating Part		Yes	74980 Series
Keying to Mating Part		None	<u>14900</u> Selles
Material - Metal		Copper-Nickel-Silicon, High Performance Alloy (HPA), Stainless Steel	Mates With
Material - Plating Matir	ng	Gold	74880 VHDM-HSD™ Daughtercard
Material - Plating Term		Matte Tin	
Material - Resin		High Temperature Thermoplastic	Use With
Net Weight		7.172/g	Daughtercard Modules
Number of Columns		10	
Number of Pairs		Open Pin Field	Application Tooling   FAQ
Number of Rows		6	Tooling specifications and manuals are
Orientation		Vertical	found by selecting the products below.
PC Tail Length		2.50mm	Crimp Height Specifications are then
PCB Locator		No	contained in the Application Tooling
PCB Retention		None	Specification document.
PCB Thickness - Reco	mmended	1.80mm	Global
Packaging Type		Tube	Description Product #
Pitch - Mating Interface	e	2.00mm	Signal Pin Inserter 0622015700
Plating min - Mating		0.762µm	Repair Tool
Plating min - Terminat	on	0.762µm	Signal Header, 6- <u>0622020216</u>
Polarized to PCB		Yes	Row by 10-Wide,
Surface Mount Compa		Yes	20.00mm
Temperature Range -	Operating	-55°C to +105°C	J L

Termination Interface: Style

Electrical Current - Maximum per Contact Data Rate Voltage - Maximum Through Hole - Compliant Pin

2.0A 5.0 Gbps 120V AC (RMS)/DC

## **Material Info**

Reference - Drawing NumbersProduct SpecificationPS-74031-999Sales DrawingSD-74980-010Note: HDM, HDM+, VHDM, VHDM-HSD and GbX are trademarks or registered trademarks of Amphenol TCS.

## This document was generated on 09/29/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 1410191-1 1410337-1 1410368-3 1410964-2 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0736440217 1-1393708-5 72388-0021LF 73774-1000 532939-1 5-531355-3 5532901-3 85838-180LF HM1S43TRR460H6PLF 0760205010 1-966831-4 3-1469268-7 77427-121LF