



Cirrus 80			
Nominal Power Output at 10°C	300/600W	450/800W	
Typical max inrush current	at 230 AC, amps at 115 AC, amps	10 15	11 14
Fan volumetric flow, approximate, m3/hr	35	35	
Fan lifetime at 40°C L10, hours	52,500	52,500	
Normal input voltage	115V or 230VAC	115V or 230VAC	
Dimensions	- cross section mm - length mm	82 x 110 150	82 x 110 150
Weight (g)	785	785	
Finger guards inlet and outlet	Y	Y	

Options

- Filter Assembly*
- Fixing - 35mm DIN clip

* Typical power reduction of 10% when 30PPI filter fitted

Data is given for illustration purposes only and does not release the customer from independent application tests. This information is subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [dbk technitherm](#) manufacturer:

Other Similar products are found below :

[372467,01](#) [372834,01](#) [372466,01](#) [372735,01](#) [FINGER GUARD LARG](#) [NG150](#) [370306,01](#) [371061,01](#) [371082,01](#) [NG240](#) [15697,6](#) [HP04-1/04-24](#) [NG50](#) [FINGER GUARD SMALL](#) [370089,01](#) [15662](#) [15661,2](#) [NG30](#) [NG100](#) [15696,8](#) [371934,01](#) [371680,01](#) [HP06-2/13-240](#)
[371604,01](#) [370178,01](#) [370184,01](#) [370177,01](#) [370182,01](#) [HP05-1/04-24](#)