

## **PRODUCT SPECIFICATION**



Electrical Characteristics			
Input Voltage	10-100V DC, 20-72V AC	Input current	480mA @ 12V DC, 180mA @ 24V DC 92mA @ 48V DC, 77mA @ 60V DC 540mA @ 30V AC, 240mA @ 60V AC
Frequency	75 FPM	Light Source	Non-replaceable
Flash Mode	Single flash	Flash Pattern	N/A
Technology	Xenon	Power rating	5 W
		Estimated Tube Life	3,000 Hours
Other features	Reverse polarity protection		

Photometric Characteristics				
Colour	Amber	Polar Plot		
Max intensity at HV0	12 cd	0		
Min intensity	12 cd	340 350 380 14 0 10 20 30		
Timing Diagram		330 40 50		
1mS     800mS		310 290 280 270 280 270 280 240 230 220 210 200 190 180 170 180 170 180		

Enclosure			
IP rating	IP 67	Fixing centres	45 mm
Cable exit	Central base grommet	Fastening hardware	2 x M5 x 14mm studs with M5 nuts
Cable dimensions	2 x 0.75mm <sup>2</sup>	Packaging	Thin wall carton
Recommended Mounting	Upright	Max Fastening Torque	3 N/m
Weight (unboxed)	130g	Weight (boxed)	150g

Approvals and Certifications					
EMC	UN ECE R10-03 6101	WEEE	Yes		
CE	Yes	RoHS	Yes		

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for visionalert manufacturer:

Other Similar products are found below:

 $\underline{31105372} \ \underline{30102270} \ \underline{30102272}$