



Main

Range of product	TeSys k control relay
Product or component type	Electromagnetic relay
Device short name	CA2K
Contactor application	Control circuit
Utilisation category	AC-15
Control circuit type	AC
Coil type	Standard
Coil technology	Without integral suppression device
Pole contact composition	4 NO
[Uc] control circuit voltage	230/240 V AC 50/60 Hz
Connections - terminals	Screwclamp terminal 1 cable 1.5 mm ² - cable stiffness: solid Screwclamp terminal 2 cable 4 mm ² - cable stiffness: solid Screwclamp terminal 1 cable 0.75 mm ² - cable stiffness: flexible - without cable end Screwclamp terminal 2 cable 4 mm ² - cable stiffness: flexible - without cable end Screwclamp terminal 1 cable 0.34...1.5 mm ² - cable stiffness: flexible - with cable end Screwclamp terminal 1 cable 0.34...2.5 mm ² - cable stiffness: flexible - with cable end

Complementary

Contact operation	Mechanically linked conforming to IEC 60947-5-1
Control circuit voltage limits	0.8...1.15 Uc at 50 °C operational 50/60 Hz <= 0.2 Uc at 50 °C drop-out 50/60 Hz
[Ui] rated insulation voltage	600 V - conforming to CSA C22-2 No 14 690 V - conforming to BS 5424 690 V - conforming to IEC 60947 750 V - conforming to VDE 0110 group C
Flame retardance	V1 conforming to UL 94 Class C2 conforming to NF F 16-101 Class C2 conforming to NF F 16-102
Tightening torque	0.8...1.3 N.m - on screwclamp terminal - with screwdriver Philips 2 mm 0.8...1.3 N.m - on screwclamp terminal - with screwdriver flat Ø 6 mm
[Ue] rated operational voltage	<= 690 V AC <= 400 Hz
[Ith] conventional free air thermal current	10 A at ≤ 50 °C
Irms rated making capacity	110 A at <= 690 V AC conforming to IEC 60947
Associated fuse rating	10 A gG at <= 690 V conforming to VDE 0660 10 A gG at <= 690 V conforming to IEC 60947
Inrush power in VA	30 VA at 20 °C
Hold-in power consumption in VA	4.5 VA at 20 °C
Mechanical durability	10000000 cycles
Operating rate	10000 cyc/h at 20 °C
Operating time	5...15 ms coil energisation and NC opening 10...20 ms coil energisation and NO closing 10...20 ms coil de-energisation and NO opening 15...25 ms coil de-energisation and NC closing
Minimum switching current	5 mA
Minimum switching voltage	17 V

Non-overlap time	1.5 ms on energisation between NC and NO contacts 1.5 ms on de-energisation between NC and NO contacts
Non overlap distance	0.5 m
Insulation resistance	> 10 MOhm
Height	58 mm
Width	45 mm
Depth	57 mm
Product weight	0.18 kg

Environment

Standards	BS 5424 IEC 60947 NF C 63-140 VDE 0660
Product certifications	CSA UL
IP degree of protection	IP2x conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-50...80 °C
Operating altitude	2000 m without derating in temperature
Shock resistance	10 gn control relay open 15 gn control relay closed
Vibration resistance	2 gn 5...300 Hz control relay open 4 gn 5...300 Hz control relay closed
Heat dissipation	1.3 W at 50/60 Hz
Immunity to microbreaks	2 ms
RoHS EUR conformity date	0640
RoHS EUR status	Compliant

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [General Purpose Relays](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[APF30318](#) [JVN1AF-4.5V-F](#) [PCN-105D3MHZ](#) [5JO-10000S-SIL](#) [5JO-1000CD-SIL](#) [5JO-400CD-SIL](#) [LY2S-AC220/240](#) [LYQ20DC12](#)
[6031007G](#) [6131406HQ](#) [6-1393099-3](#) [6-1393099-8](#) [6-1393122-4](#) [6-1393123-2](#) [6-1393767-1](#) [6-1393843-7](#) [6-1415012-1](#) [6-1419102-2](#) [6-](#)
[1423698-4](#) [6-1608051-6](#) [6-1608067-0](#) [6-1616170-6](#) [6-1616248-2](#) [6-1616282-3](#) [6-1616348-2](#) [6-1616350-1](#) [6-1616350-8](#) [6-1616358-7](#) [6-](#)
[1616359-9](#) [6-1616360-9](#) [6-1616931-6](#) [6-1617039-1](#) [6-1617052-1](#) [6-1617090-2](#) [6-1617090-5](#) [6-1617347-5](#) [6-1617353-3](#) [6-1617801-8](#) [6-](#)
[1617802-2](#) [6-1618107-9](#) [6-1618248-4](#) [M83536/1-027M](#) [CX-4014](#) [MAHC-5494](#) [MAVCD-5419-6](#) [703XCX-120A](#) [7-1393100-5](#) [7-1393111-7](#)
[7-1393144-5](#) [7-1393767-8](#)