


DRG No. <b>CP32944</b>	ISSUE <b>1</b>	TYPE No. OXL/CLH/100/FLxx/- OXL/CLH/100/CL/FLxx/-		DIM. IN: MILLIMETRES	ODC:QS:40077 ISSUE 1 DO NOT SCALE	THIS DRAWING AND THE COPYRIGHT AND DESIGN RIGHT THEREIN ARE THE PROPERTY OF OXLEY DEVELOPMENTS CO. Ltd. AND MUST NOT BE REPRODUCED OR DISCLOSED TO A THIRD PARTY WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY.	ISS	MODIFICATION	DATE
---------------------------	-------------------	---	--	-------------------------	---	--	-----	--------------	------

© COPYRIGHT OXLEY DEVELOPMENTS Co. Ltd. 2001



MATERIALS AND FINISHES	
DESCRIPTION	MATERIAL, FINISH
BODY	ALUMINIUM ALLOY, MATT BLACK ANODISED
LENS	POLYCARBONATE
TERMINATIONS	FLYING LEADS : COLOUR RED AND BLACK WIRE INSULATION. LENGTH DEFINED IN PART No. (cm)
NUT	ALUMINIUM ALLOY
WASHER	BeCu. TIN PLATED

ELECTRICAL / OPTICAL CHARACTERISTICS

	AlGaAs RED	YELLOW	GREEN	BLUE	WHITE
LUMINOUS INTENSITY TYPICAL (mcd AT RATED VOLTAGE)	1200	1000	1250	1200	1000
WAVELENGTH TYPICAL (nm)	637	585	525	470	N/A
FORWARD CURRENT (mA) TYP	20	20	20	20	20
FORWARD VOLTAGE (V)	1.9	1.9	3.6	3.6	3.6
REVERSE VOLTAGE (V) MAX	5				

MOUNTING DETAILS
MOUNTING HOLE : $\phi 10.15 \pm 0.1$
RECOMMENDED MOUNTING TORQUE : 1Nm
CHASSIS THICKNESS : 1.5mm (Min)

ORDERING INFORMATION :

WHEN ORDERING, STATE TYPE NUMBER, SPECIFYING FLYING LEAD LENGTH AND LED COLOUR

e.g OXL/CLH/100/FL10/G

FLYING LEAD LENGTH IN cm      COLOUR (AL, Y, G, B or W)  
AlGaAs RED, RED, YELLOW, GREEN, BLUE or WHITE

MATERIAL AS STATED	DRAWN <i>Simon Ryssam</i>
FINISH AS STATED	CHECKED T. DAVIS
PLATING AS STATED	APPROVED DA01/351
TOLERANCE AS STATED	DATE 10 DEC 01

REMARKS

TITLE  
WIDE ANGLE HIGH BRIGHTNESS LED INDICATOR WITH FLYING LEADS

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [oxley manufacturer](#):*

Other Similar products are found below :

[DLT/1000/ROHS](#) [OXL/CLH/100/FL30/GREEN](#) [OXL/CLH/100/12AC/FL30/ALGAAS RED](#) [OXL/CLH/63/BB/24AC/FL30/GREEN](#)  
[OXL/CLH/100/230/FL30/GREEN](#) [OXL/CLH/100/P/24AC/FL30/ALGAAS RED](#) [OXL/CLH/100/24AC/FL30/WHITE](#)  
[OXL/CLH/63/FL30/GREEN](#) [OXL/CLH/100/24AC/FL30/ALGAAS RED](#) [OXL/CLH/100/230/FL30/ALGAAS RED](#)  
[OXL/CLH/63/24AC/FL30/YELLOW](#) [LSB2/156/RED](#) [LS/B1/093 WHITE](#) [OXL/CLH/80/P/12AC/FL30/H/GREEN](#) [040/30P/KP2 SILVER](#)  
[DLT/10000/ROHS](#) [DLT4/L/22000/ROHS](#) [028/30P/KP2/L SILVER](#) [028/30P/LA/KP2 SILVER](#) [SN/040/RP SILVER](#) [FLTM/P/5000/ROHS](#)  
[SMOX/060/B1/LP GOLD](#) [040/30P/KP2/L SILVER](#) [040/30P/LA/KP2 SILVER](#)