3M General Purpose Paper Masking Tape 2120

Product Data Sheet	
	Date: January 2012 Supersedes: New
Product Description	3M General Purpose Paper Masking Tape 2120 is a room temperature, premium quality tape for holding, bundling, sealing and non critical masking applications.
Key Features	Crepe paper backing for conformability that will maintain integrity when formed around corners. Backing saturated for easy tear – resists slivering yet hand tearable. Rubber adhesive with instant adhesion. Good holding power that resists lifting or curling and helps reduce rework. Special backsize treatment controls unwind and helps reduce waste. Designed for indoor use only. Tape should not be subjected to outdoor exposure or prolonged periods of sunlight as product may become very difficult to remove.

Physical Properties

Adhesive Type	Rubber
Backing Type	Crepe Paper
Tape Colour	Natural
Thickness AFERA 5006	0.126mm

Performance Characteristics	Adhesion to Stainless Steel AFERA 5001	6N/25mm
	Tensile Strength AFERA 5004	75N/25mm
	Elongation at break	9.5%
	Temperature Range	30°C for 1 hour

Storage	Store under normal conditions of 70`F (21`C) and 50% R.H. in the original carton.
Shelf Life	3M 2120 has a shelf life of 12 months from date of manufacture when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity
Precautionary Information	Refer to product label and Material Safety Data Sheet for health and safety information before using the product. For information please contact your local 3M Office. www.3M.com
Important Notice	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark the 3M Company.

3M United Kingdom PLC 3M House, 28 Great Jackson Street, Manchester, M15 4PAProduct Information Tel 0870 60 800 Fax 0870 60 700	The Iveagh Building0The Park, Carrickmines	Customer Service : Tel (01) 280 3555 Fax (01) 280 3509
---	--	--

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 3m manufacturer:

Other Similar products are found below :

SC401U 98-0003-3071-6 00-054007-70220-7 00-054007-34717-0 021200-40230 6840-2X50-GRAY 701-W 7993MP-2CIRCLE-100 FDV14-187C 8124/14 812510-100 8125/17 813216 8204-3LFM 8425-8 MNG14BCX FP301-1-6"-Clear FV14-6C 920102-01-25-R 927739-40 929835-01-28-RK 929836-09-16 929974-01-40-R 951240-2520-AR-PR 960X/980X 98-0003-3075-7 HF36564-100 HF625/26-30 1/2-5-5430 1/2-5-850S 1/2-5-3431 12X12-6-4056B 12X12-6-433 12X12-6-4930 13-500-NB 14526-EZ5B-300-02C 1-4-4658F 14520-EZAB-300-0EC DSTK9013-3420 DSTK9015-3402 14T26-SZLB-200-0LC 14T50-SZWB-100-0NC 1-5-3437 1-5-4496W 1-5-4943F 1-5-363 1-5-5451 1-5-421 158250-0120 MTI14-187L