# **Sleeving**







#### **Features**

- · Self-extinguishing, Poly-Aramid, Multifilament Braided Sleeve
- This product offers some expansion
- Working temperature of -60°C up to + 240°C
- · Good mechanical abrasion resistance
- Excellent resistance to humidity and outstanding performances under Beta,
   Gamma and Xray radiation as well as a high resistance to chemicals
- Suitable for protecting cables and hoses in harsh environmental conditions
- · Standard colours: Ivory, Olive Green
- · This Sleeve can be cut to length

### **Packaging**

Supplied on Reels

### **Specification**

Physical	Working temperature	-60°C to +240°C		
	Peak temperature	+240°C		
	Melting point	+310°C		
	Carbonization	Above 370°C		
	Clammability	V-W1		
	Flammability	V-0		
Chemical	Chemical resistance	Unaffected by most chemicals		

#### **Part Number Table**

Description	Nominal Diameter (mm)	Recommended Range of Use (mm)		Reel Length	Colour	Part Number
		Min.	Max.	(m)		
Sleeving, Braid, 50	10	8	16	50	Ivory	NOMEX10IY50R
					Olive Green	NOMEX10OEDB50R
	15	10	20		Ivory	NOMEX15IY50R

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



## **X-ON Electronics**

**Authorized Distributor** 

Click to view similar products for Wire Identification category.

Click to view products by Pro Power manufacturer.

Other Similar products are found below:

PCM39 M200X042FPT M200X042UPT M200X050ACT M200X050AGT

M200X080FQT M200X080UPT M200X100ACT M200X100AFT M200X100AIT

M300X050ACT M300X050AET M300X050AFT M300X100ACT M300X100AET

PDP6 PRL100BY18KIT PS10002WT H050X025H1TB H050X034H1T

H050X034H1TB H050X044H1T H050X044H2T H050X044H3T H050X064H2T