

Current - Maximum per Contact

## This document was generated on 07/18/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0757059503		$\land$
Status: Active			I AM
		ane Connector System	
	<u>GbX I-Trac™ Backplane Connector System</u> GbX I-Trac™ Vertical Header Module, 1.85mm by 3.70mm Pitch, Right Guide, Left Endwall, 11 Rows, 5 Columns, 110 Circuits, Mating Pin Length 4.70mm		
Documents:			
3D Model		RoHS Certificate of Compliance (PDF)	
Drawing (PDF)			
Drawing (FDF)			and a second sec
A monor Contification			Series image - Reference only
Agency Certification		E29179	
OL		E29179	EUELV
General			Not Relevant
Product Family		Backplane Connectors	NOT Relevant
Series		75705	EU RoHS China RoHS
Application		Backplane, Midplane, Orthogonal	Compliant
Component Type		PCB Header	REACH SVHC
Overview		GbX I-Trac <sup>™</sup> Backplane Connector System	Not Contained Per -
Product Name		GbX I-Trac™	ED/21/2016 (20 June
UPC		822350968096	2016)
0.0			Halogen-Free
Physical			Status
Circuits (Loaded)		110	Low-Halogen
Circuits (maximum)		110	· · · · · · · · · · · · · · · · · · ·
Color - Resin		Black	Need more information on product
Durability (mating cycles max)		200	environmental compliance?
First Mate / Last Break		No	Email productcompliance@molex.com
Flammability		94V-0	Please visit the <u>Contact Us</u> section for any
Guide to Mating Part		Yes	non-product compliance questions.
Keying to Mating Part		None	
Material - Metal		High Performance Alloy (HPA)	China ROHS Green Image
Material - Plating Mating		Gold	ELV Not Relevant
Material - Plating Termin		Tin	
Material - Resin		High Temperature Thermoplastic	
Net Weight		7.815/g	
Number of Columns		5	Search Parts in this Series
Number of Pairs		6, Open Pin Field	75705 Series
Number of Rows		11	
Orientation		Vertical	Mates With
PC Tail Length PCB Locator		2.10mm	75710 GbX I-Trac™ Right Angle Receptack Module
		No	
PCB Retention		Yes	
PCB Thickness - Recom	mended	1.60mm	Use With
Packaging Type Pitch - Mating Interface Pitch - Termination Interface		Tray	<u>78232</u> GbX I-Trac <sup>™</sup> Vertical Power
			Receptacle. <u>75234</u> Backplane Free Standin Guide Pin
		1.85mm, 3.70mm	
		1.00mm, 2.70mm	Guide Fill
Plating min - Mating Plating min - Termination		0.762µm	
Plating min - Termination Polarized to PCB		0.762µm	Application Tooling   FAQ
		No	Tooling specifications and manuals are
Stackable		No	found by selecting the products below.
Surface Mount Compatible (SMC)		Yes	Crimp Height Specifications are then
Temperature Range - Operating		-55°C to +80°C	contained in the Application Tooling
Termination Interface: Style		Through Hole - Compliant Pin	Specification document.
Electrical			Global
Current - Maximum per (	Contact	1.0A	Description Product #

Data Rate Real Signals (per 25mm) Shield Type Shielded Voltage - Maximum

Solder Process Data Lead-freeProcess Capability

**Material Info** 

**Reference - Drawing Numbers** Sales Drawing 12.0 Gbps 148 N/A No 120V AC (RMS)/DC

Press-In Tool0622018601Vertical Header 11-Row, 5-ColumnBackplane InsertionTool for SignalContact Insertion

N/A

SD-75705-004

## This document was generated on 07/18/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 1410191-1 1410337-1 1410368-3 1410964-2 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0736440217 1-1393708-5 72388-0021LF 73774-1000 532939-1 5-531355-3 5532901-3 85838-180LF HM1S43TRR460H6PLF 0760205010 1-966831-4 3-1469268-7 77427-121LF