

This document was generated on 04/04/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	75010 0602		(1920) (1920)
	<u>75910-0603</u>		1775
Status:	Active		
Overview:GbX I-Trac™ BackplDescription:1.85mm by 3.70mm		ane Connector System	
		n Pitch, GbX I-Trac™ Right Angle Header Module, Unguided, Open	
		Columns, 132 Circuits, Mating Pin Length 4.70mm	
	,	, · · · · · · · · · · · · · · · ·	
Documents:			
3D Model		Product Specification PS-75710-999 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
			Series
Agamay Cartifica	tion		image - Reference only
Agency Certification		E00170	
UL		E29179	EU RoHS China RoHS
General			RoHS Compliant by
		Rackplana Connectors	
Product Family		Backplane Connectors	Exemption REACH SVHC
Series		75910 Contener Deventereerd	
Application		Coplanar, Daughtercard	Contains SVHC: No
Component Type		Right Angle Male	Low-Halogen Status
Overview		GbX I-Trac [™] Backplane Connector System	Low-Halogen Pb
Product Name		GbX I-Trac™	Need more information on product
Style		N/A	environmental compliance?
Physical			
Circuits (Loaded)		132	Email productcompliance@molex.com
Circuits (maximum)		132	For a multiple part number RoHS Certificate of
		Black	Compliance, <u>click here</u>
Color - Resin			Blasse visit the Contact Lie section for any
Durability (mating cycles max)		200	Please visit the <u>Contact Us</u> section for any
First Mate / Last Break		No	non-product compliance questions.
Flammability		94V-0	
Guide to Mating Part		No	
Keying to Mating Part		None	
Material - Metal		High Performance Alloy (HPA)	Search Parts in this Series
Material - Plating Mating		Gold	<u>75910</u> Series
Material - Plating Terr	mination	Tin	
Material - Resin		High Temperature Thermoplastic	Mates With
Number of Columns		6	<u>75710</u> GbX I-Trac [™] Right Angle Receptacle
Number of Pairs		6, Open Pin Field	Module
Number of Rows		11	
Orientation		Right Angle	
PC Tail Length		2.00mm	
PCB Locator		Yes	<u>78235</u> GbX I-Trac [™] Right Angle Power
PCB Retention		Yes	Receptacle
PCB Thickness - Rec	commended	1.60mm	
Packaging Type		Tray	Application Tooling FAQ
Pitch - Mating Interface		1.85mm, 3.70mm	Tooling specifications and manuals are
Pitch - Termination In		1.00mm, 2.70mm	found by selecting the products below.
Plating min - Mating		0.762µm	Crimp Height Specifications are then
Plating min - Termina	tion	0.762µm	contained in the Application Tooling
Polarized to PCB		Yes	Specification document.
Surface Mount Compa	atible (SMC)	Yes	Global
Temperature Range - Operating		-55°C to +80°C	Description Product #
Termination Interface:		Through Hole - Compliant Pin	Press-In Tool 0622018605
			for Right Angle
Electrical			Receptacle and
Current - Maximum per Contact		1A	
Data Rate			Header 11-Row, 6-
		12.0 Gbps	Column

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 88911-201LF 9514M0C20D 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0740618502 0760151403 0760551105 0760551608 0761451128 0761651124 0761655108 0761659807 0769853208 0736440217 0758324203