


[WIRING SYSTEM KITS](#)
[PROTOTYPING BOARDS](#)
[WIRE](#)
[WIRING PENCILS](#)
[WIRING DISTRIBUTION STRIPS](#)
[MISCELLANEOUS](#)

[About Us](#)
[Order Info](#)
[Site Map](#)
[Contact Us](#)

Wiring Pencil Wire (insulated)

[Order Form](#)
[Safety Data Sheet](#)
[Instruction Sheet](#)


4 per pack

The wire requires a soldering iron temperature of 400°C+ to remove the enamel. (Weller bit temperature code 8 or 9)

- Solderable Enamelled Copper Wire
- Colours – gold, pink, green, violet/blue
- Coated in self-fluxing polyurethane, conforming to BS4520 Grade 2 (now incorporated within BS6811 Section 1, Pt3)
- Suitable for prototype wiring, PCB track repairs, shorting links and coil forming

Maximum continuous temperature +120°C
Suitable soldering temperature 400-480°C

Insulation Thickness

38 swg	0.012 mm	Grade 2
36 swg	0.014 mm	Grade 2

Resistance

0.967 Ohms/m typ

Current Rating

38 swg	82 MA
36 swg	131 MA

Spool Length (Average)

38 swg	38 m
36 swg	27 m

Insulation Breakdown

1500 V RMS

Wire Diameter:

1/0.15mm (38 SWG)

Product:	Color
RRP-C-105	Gold
RRP-G-105	Green
RRP-P-105	Pink
RRP-V-105	Violet

Wire Diameter:

1/0.19mm (36SWG)

Product:	Color
RRW-C-105	Gold
RRW-G-105	Green
RRW-P-105	Pink
RRW-V-105	Violet

CAUTION

Emits toxic Vapour
when soldered
Ventilate area well

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [roadrunner](#) manufacturer:

Other Similar products are found below :

[RRB-120](#) [RRP-103](#) [RRS-P-102](#) [RRP-123](#) [RRP-A-105](#) [RRW-A-105](#) [RRB-007](#) [RRB-003](#)