

This document was generated on 02/12/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0	76015940 <u>3</u>		6
Status: Active Overview: GbX I-Trac™ Backplane Connector System			
•		Header Module, 1.85mm by 3.70mm Pitch, Right Guide, Left	
Er	idwall, 7 Rows, 4 Co	lumns, 56 Circuits, Mating Pin Length 4.70mm, Lead-Free	
Decumenter			
Documents:		Product Crecification DC 75710 000 (DDE)	3 b 1 5
<u>3D Model</u>		Product Specification PS-75710-999 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Agency Certification			Series image - Reference only
UL		E29179	
			EU ELV
General			Not Relevant
Product Family		Backplane Connectors	
Series		<u>76015</u>	EU RoHS China RoHS
Application		Backplane, Midplane, Orthogonal	Compliant
Component Type		PCB Header	REACH SVHC
Overview		GbX I-Trac [™] Backplane Connector System	Not Contained Per
Product Name		GbX I-Trac™	-ED/79/2015 (17
UPC		822350963381	December 2015)
0.0			Halogen-Free
Physical			
Circuits (Loaded)		56	<u>Status</u>
Circuits (maximum)		56	Low-Halogen
Color - Resin		Black	Need more information on product
			environmental compliance?
Durability (mating cycles max)		200	
First Mate / Last Break		No	Email productcompliance@molex.com
Flammability		94V-0	Please visit the <u>Contact Us</u> section for any
Guide to Mating Part		Yes	non-product compliance questions.
Keying to Mating Part		None	
Material - Metal		High Performance Alloy (HPA)	China ROHS Green Image
Material - Plating Mating		Gold	ELV Not Relevant
Material - Plating Termina	tion	Tin	
Material - Resin		High Temperature Thermoplastic	
Net Weight		5.532/g	
Number of Columns		4	Search Parts in this Series
Number of Pairs		4, Open Pin Field	76015 Series
Number of Rows		/ Vorticol	Mates With
Orientation		Vertical	76020 GbX I-Trac™ Right Angle Receptac
PC Tail Length		2.10mm	Module
PCB Locator		No	
PCB Retention		None	
PCB Thickness - Recomm	nended	1.60mm	Use With
Packaging Type		Tray	<u>78227</u> GbX I-Trac™ Vertical Power
Pitch - Mating Interface		1.85mm, 3.70mm	Receptacle. <u>75234</u> Backplane Free Standir
Pitch - Termination Interface		1.00mm, 2.70mm	Guide Pin
Plating min - Mating		0.762µm	
Plating min - Termination		0.762µm	Application Tooling FAQ
Polarized to PCB		Νο	Tooling specifications and manuals are
Stackable		No	
			found by selecting the products below.
Surface Mount Compatible (SMC)		Yes	Crimp Height Specifications are then
Temperature Range - Operating		85°C	contained in the Application Tooling
Termination Interface: Sty	le	Through Hole - Compliant Pin	Specification document.
Flootrigel			Global
Electrical		1.00	Description Product #
Current - Maximum per Co	ontact	1.0A	I I

Data Rate Shield Type Shielded Voltage - Maximum

Solder Process Data Lead-freeProcess Capability

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing 12.0 Gbps N/A No 120V AC (RMS)/DC

N/A

Backplane Insertion0621005110Tool for SignalContact InsertionPress-In Tool for0622018607Vertical Header 7-Row, 4-Column

PS-75710-999 SD-76015-004

This document was generated on 02/12/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 09231126901
 PCN10F-24P-2.54DS(72)
 004.767
 02221602702
 024069
 602427301412000
 013275
 691327-1
 74670-0732
 74680-0340

 75880-0015
 76453-0014
 86093159ALF
 923454
 QLC260R
 120X10099X
 120X10019X
 120X10129X
 121A10039X

 121A10309X
 122A10019X
 122A10029X
 122A10249X
 122A10669X
 122A11089X
 122A13089X
 121B10409X
 122A10089X

 122A10129X
 122A10349X
 122A10249X
 122A10669X
 122A11089X
 122A13089X
 121B10409X
 122A10089X

 122A10129X
 122A10349X
 122A13359X
 1377391-4
 DIN-048CPC-SR1-MH
 1393583-2
 1393726-7
 140X10059X
 140X10129X
 143-1913

 000
 143-1908-000
 1484472-1
 173052
 2110070-1
 2110070-2
 CBC20T00-008FDS5-0-1-002VR
 983-0SE12-12P6
 17041102202
 172699

 5036
 173051
 20
 8457096
 010
 025