

# Universal Reversible USB 2.0 Cable (Up / Down Angle Reversible A to 5Pin Mini-B M/M), 6-ft.

## MODEL NUMBER: UR030-006-UDA







## **Highlights**

- Up / Down Angle Reversible A connector eliminates guess-work as to connector orientation
- Meets or Exceeds USB 2.0 Specifications
- Connects to Cameras, PDA's, etc with Mini-B 5-Pin connectors

### **System Requirements**

- Any USB device requiring a USB cable with Mini-B 5-Pin connector
- USB 2.0 performance only when used with USB 2.0 device and USB 2.0 controller

#### **Package Includes**

 6-ft. USB 2.0 Up / Down Angle Reversible A to Mini-B Gold Device Cable (A Male to 5-Pin Mini-B Male)

#### Description

Tripp Lite's UR030-006-UDA 6-ft, Up / Down Angle Reversible USB 2.0 "A" to Mini-B 5-pin device cable, meets or exceeds USB 2.0 Specifications. Connects a Digital camera, PDA, Cell Phone, etc to a USB port on a

computer or hub. Backward compatible - can be used with older USB 1.1 applications as well. All Tripp Lite USB 2.0 cabling includes superior foil shielding for reliable, error-free data communications. The significantly faster data transfer rates of USB 2.0 (up to 480 Mbps) make them perfect for multimedia applications. Features nickel plated connectors and gold plated copper contacts for superior conductivity. The cable is manufactured with molded connectors and integral strain relief for extra durability and long life.

# Features

- Up / Down Angle Reversible "A" connector plugs in any direction
- Meets or Exceeds USB 2.0 Specifications
- Connects to Cameras, Cell Phones, PDA's, etc with 5-Pin Mini-B USB connectors
- Supports faster data transfer rate (1.5 to 480 Mbps) for low speed and high speed devices including multimedia applications
- Premium double-shielded cables with tinned copper braid and aluminum Mylar foil
- Nickel plated connectors and gold plated copper contacts for superior conductivity.
- Molded connectors and integral strain relief for extra durability and long life.

# **Specifications**

INPUT	
Cable Length (ft.)	6
Cable Length (m)	1.8
PHYSICAL	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Color	Black	
ENVIRONMENTAL		
Operating Temperature Range	-10/+75° C (14 to 167° F)	
Storage Temperature Range	-20/+80° C (-4 to 176° F)	
CONNECTIONS		
Side A - Connector 1	REVERSIBLE USB A (MALE)	
Side B - Connector 1	USB MINI-B 5-PIN (MALE)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Cables / IEEE 1394 Cables category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

68768-0173 FNY-W6003-01 88764-0800 13805532 148700-1 17-200621 17-250051P 954 AC102012-2 IP-USB1(C10)S-RW

CABLE/RTP/USB/DT 0847290003 10115240-12200LF RS232-GTD USBFTVX2SA2N03A USBFTV2SA2N03A 1689404-1 FTP-629Y401 FTP-628Y402 943301-001 FNY-W6022 FNY-W6003-03 1310-1015-05 1310-1018-04 1310-1019-04 0887283402 UA-30AMFM-SL7B02 UA-30AMFM-SL7B01 UA-30AFM-LD7B03 UA-30AMFM-SL7B03 USBAPSCC7202A UES-1001A160 UES-1003A160 USBFTVX7SA2N20A USBFTVX2SA2N20A USBFTV2PEMSA2N10A FTP-629Y602 USBCAMCM100 USB A/F\*2 to 2.54

2\*5P-SH L=400mm EP-CBUSB10P2FLT 1310-1033-01 1310-1037-04 ASR-USB 68784-0075 17-241361 17-230471 217B-BC02 USB-29 19800-010500-200-RS USB+MINI DIN 6P WITH BKT