

This document was generated on 01/17/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0768710007

Status: **Active**

Overview: **QSFP+ Interconnect Solution**

Quad Small Form-factor Pluggable Plus (QSFP) Assembly without Flange, Stacked 2 **Description:**

by 1 with Elastomer Gaskets and Light Pipes, Tin

Documents:

3D Model Application Specification AS-76870-001-001 (PDF) **Drawing (PDF)** Application Specification AS-76871-0002-001 (PDF)

Product Specification PS-76870-001-001 (PDF) RoHS Certificate of Compliance (PDF)

Agency Certification

E29179

General

I/O Connectors **Product Family**

Series 76871

Application Module-to-Board Component Type Receptacle **Electrical Model** Yes

Overview **QSFP+ Interconnect Solution**

QSFP Product Name Type N/A

UPC 884982637337

Physical

Boot Color N/A Circuits (Loaded) 76 Circuits (maximum) 76 Durability (mating cycles max) 100 Flammability 94V-0 Gender Female Keying to Mating Part None

Lock to Mating Part Yes Material - Metal **Phosphor Bronze**

Material - Plating Mating Gold Material - Plating Termination Tin Net Weight 30.000/g Number of Rows Orientation Right Angle

PC Tail Length 1.25mm **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray **Panel Mount** No Pitch - Mating Interface 0.80mm Pitch - Termination Interface 0.80mm Polarized to Mating Part Yes

Polarized to PCB Yes Ports Surface Mount Compatible (SMC)

Temperature Range - Operating -40°C to +85°C

Termination Interface: Style Through Hole - Compliant Pin

No

Waterproof / Dustproof

Electrical



Series image - Reference only

EU ELV

Not Reviewed

EU RoHS China RoHS

Not Reviewed REACH SVHC Not Reviewed **Halogen-Free Status**

Not Reviewed

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u> Please visit the Contact Us section for any non-product compliance questions.

China ROHS Not Reviewed ELV Not Reviewed RoHS Phthalates Not Reviewed

Search Parts in this Series

76871 Series

Use With <u>74757</u>, <u>74758</u> Current - Maximum per Contact0.5AGrounding to PanelNoneShield TypeEMI Gasket

Shielded Yes

Voltage - Maximum 120V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Application Specification AS-76870-001-001, AS-76871-0002-001

Electrical Model Document EE-76870-001
Product Specification PS-76870-001
S-Parameter Model SP-76870-001
Sales Drawing SD-76871-003

This document was generated on 01/17/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 61-168618-12P D38999/20FJ24PA L/C D38999/20FJ29SB L/C D38999/24FG11SN L/C 72.250.1628.2 72.250.2428.2 74720-0505 747680210 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 FCN-268D024-G/2F#10X-R10 MP-5T180MUNNA-005 MP-5XRJ45UNNB-003 PCS-E50FA PCS-XE26LKA PCS-XE26MA+ PCS-XES68MS+ G38A71314B 91-569719-35R 9776-18-6 DX40-50P(55) 1571250010 157-22500-3 MS3471L14-19P L/C MS3476W12-10S L/C 171224-6031 1888020-8 91-569786-35H 91-569786-35M 91-644626-35P 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 FCN-268D008-G/1K 2000314-1 2007498-2 PCR-E28LMDAG1+ PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFDT+ G38A71214B HDRA-E68W1LFDTC-SL+