

## Datasheet for part number DBM25SHK52

Our Catalog Part Number: DBM-25S-H-K52

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D\*M

Product Datasheet	
General	D*M High reliable D-Sub Connectors
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	200
Contact Arrangement	25 contacts size 20
Dielectric Withstanding Voltage	1000 VAC at sea level
Current Rating	7.5 A max
Contact Resistance	7.5 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	50 microinch gold over 100 microinch copper
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Socket
Contact Type	Straight Solder
Contact Material	copper alloy
Contact Finish	50 microinch gold over 100 microinch copper
Hardware	.120" (3,05mm) Through Hole

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Micro-D Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

M243082311F M2430834F M24308/4-6F 65-1920-15 M83513/01-HN M83513/03-A10N M83513/03-B14C M83513/03-D09C M83513/03-D11N M83513/03-G02N M83513/03-G05N M83513/03-G08C M83513/03-G09N M83513/03-G12N M83513/03-H13N M83513/04-E15N M83513/04-G04C M83513/10-E01NP M83513/13-B01NP M83513/13-C01NN M83513/16-A01CP M83513/22-D01NP M83513/25-B01NP 6R2004A30F015 6R4006A28A120 703006A13F060 704002A03F200 705001A13F120 7-1532020-5 748567-1-P MDB1-31SH003 MDM-15PBS-L58 MDM-15PCBRM7T MDM-15PH003B-A174 75-068624-59S MDM-15PH034B MDM-15SH001L MDM-15SH004B MDM-21PH003K MDM-25PH003B-A174 MDM-25PHW01F-A174 MDM-37PH006L-A174 MDM-37PH048M5-A174 MDM-37SCBRP-A174 MDM-51PBS-L56 MDM-51PSF MDM-51SH003M7 MDM-51SSM7-A174 MDM-9PBSP-L58 MDM-9PH003M7