


Coaxial Cables

RG58CU 50Ω

pro-POWER

RoHS
Compliant





Description:

Stranded Tinned Annealed Copper Wire, Solid PE Insulation, Tinned Annealed Copper Wire Braiding 93% Coverage, PVC Sheath.

Application:

For CATV/MATV, Broadband, HDTV and Satellite Broadcasting Transmission use.



Construction:

Conductor

Material : Stranded Tinned Annealed Copper Wire
Stranding : 19/0.19mm (20AWG)

Insulation

Material : Solid PE
Nominal I.D : 2.9mm

Shielding

Material : Tinned Annealed Copper Wire Braiding, 93% coverage

Sheath

Material : PVC
Nominal O.D : 5mm
Colour : Black

Coaxial Cables

RG58CU 50Ω

pro-POWER

Physical Properties:

Min. Bend Radius : 50mm
Operating Temperature : -15°C to +70°C

Electrical Properties:

Max. D.C Resistance : 35.4Ω/km 20°C
Nom. Characteristic Impedance : 50+/-3Ω
Nom. Capacitance : 101pF/m
Voltage Test : Core to Shielding 2,300V AC / 1 min
Nom. Velocity of Propagation : 66%
Max. Attenuation (dB /100m)

MHz	1	10	50	100	200
dB	1.4	4.6	10.8	16.1	23.9
MHz	400	700	900	1,000	***
dB	37.7	55.8	65.6	70.5	***

Part Number Table

Description	Part Number
Cable, Coaxial, RG58C/U, 100m	CBBR0441

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)