

This document was generated on 08/20/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0782292001

Status: Active

Overview: GbX I-Trac Backplane Connector System

Description: GbX I-Trac Right-Angle Header with Right Hold Down, Power Module, 2 Blades, 40

Amps, Lead-Free

Documents:

3D Model Application Specification AS-78231-007-001 (PDF)

Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-78231-006-001 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family Backplane Connectors

Series 78229
Application Daughtercard
Component Type Power Header

Overview GbX I-Trac Backplane Connector System

Product Name GbX I-Trac UPC 883906023379

Physical

Circuits (Loaded) 2
Circuits (maximum) 2

Circuits Detail 40 Amps (20/Split Blade). Power Module 1 Blade

Length P1, 8.27mm; P2, 8.27mm

Color - Resin Black
Durability (mating cycles max) 100
First Mate / Last Break No
Flammability 94V-0

Flammability 94V-0
Guide to Mating Part No
Keying to Mating Part None

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 5.791/g
Number of Columns 1
Number of Pairs 4
Number of Rows 2

Orientation Right Angle
PC Tail Length 2.41mm
PCB Locator Yes
PCB Retention Yes
PCB Thickness - Recommended 1.60mm
Packaging Type Tray

Pitch - Mating Interface 2.00mm, 7.40mm Pitch - Termination Interface 2.00mm, 7.40mm

Polarized to PCB Yes
Stackable No
Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -20° to +85°C

Termination Interface: Style Through Hole - Compliant Pin



Series image - Reference only

EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/30/2017 (7 July 2017)

Halogen-Free Status

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

78229 Series

Mates With

78227 GbX I-Trac Vertical Receptacle, Power Module. 78230 GbX I-Trac Power

Receptacle

Use With

76020 GbX I-Trac Right Angle, 7 Row Receptacle Module

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product #

Electrical

Current - Maximum per Contact 40.0A Data Rate 12.0 Gbps Shield Type N/A

Shielded No 250V DC Voltage - Maximum

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Application Specification AS-78231-007-001 **Product Specification** PS-78231-006-001 Sales Drawing SD-78229-003

Press-in Tool for

0622018627

Right Angle Power Receptacle and Header for 7-Row

This document was generated on 08/20/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

09231126901 PCN10F-24P-2.54DS(72) 004.767 02221602702 024069 602427301412000 013275 691327-1 74670-0732 74680-0340
75880-0015 76453-0014 86093159ALF 923454 QLC260R 120X10099X 120X10019X 120X10089X 120X10129X 121A10039X
121A10309X 122A10019X 122A10029X 122A10249X 122A10669X 122A11089X 122A13089X 121B10409X 122A10089X
122A10129X 122A10349X 122A13359X 1377391-4 DIN-048CPC-SR1-MH 1393583-2 1393726-7 140X10059X 140X10129X 143-1913000 143-1908-000 1484472-1 173052 2110070-1 2110070-2 CBC20T00-008FDS5-0-1-002VR 983-0SE12-12P6 17041102202 1726995036 173051 20 8457096 010 025