CAT6 Unshielded Cable

pro-**Power**



RoHS Compliant

Specifications:

(-

Designed of cable

Inner conductor	: Single Bare Copper (0.553mm ±0.005mm)		
Insulation	: HDPE		
Insulation Dia	: 1mm ±0.05mm		
Core colour	: White-Blue; White-Orange; White-Green & White-Brown		
Drain Wire	: 0.4 ±0.01mm Tinned Copper		
Jacket Material	: PVC		
Colour	: White		
Size	: 6.3mm ±0.2mm		
Wall thickness	: 0.6mm		
Electric data at 20°C			
Conductor resistance	: ≤70Ω/kM		
Insulation resistance	: ≥5,000M Ω × kM		
Testing voltage	: wire/wire 50Hz 1min=1.5kV		
Permissible temperature	: -10°C to 60°C		

Other Electric data:

Frequency	Impedance	RL	ATT	NEXT	ELFEXT	PSNEXT	PSELFEXT	SKW	NVP
Mhz	ohm	≥dB/100M	≤dB/100M	≥dB/100M	≥dB/100M	≥dB/100M	≥dB/100M	≤ns/100M	
1	- 100 ±15	20	2.03	74.3	68	72.3	65		
4		23	3.7	65	56	63.3	53		
8		24.5	5.3	60.7	49.9	48.8	46.9		
10		25	5.9	59	48	57.3	45		
16		25	7.5	56	43.9	54.2	40.9		
20		25	8.4	55	42	52.8	39	- 45	CC0/
25		24.3	9.5	53.3	40	41.3	37	≤45	66%
31.25		23.6	10.6	52	38.1	49.9	35.1		
62.5		21.5	15.4	47	32.1	45.4	29.1		
100		20.1	19.8	44	28	42.3	25		
200	100 ±20	18	29	40	22	37.8	19		
250		17.3	32.8	38.3	20	36.3	17		

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

pro-**Power**



Part Number Table

Description	Part Number		
CAT 6 White Cable, 305m	CAT6 WHITE 305M		

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



X-ON Electronics

Authorized Distributor

Click to view similar products for Pro Power manufacturer.

Other Similar products are found below :

 0301CV100W
 04JSBLACK
 06JSBLACK
 08450046010
 08450056010
 08450066010

 08450166010
 08450236010
 08450256010
 08JSBLACK
 10026B
 10026BK
 10026G

 10026R
 10026TB
 10026TBK
 10026TG
 10026TR
 10026TW
 10030B

 10030BK
 10030G
 10030R
 10030R
 10030B
 10030B