



ELECTRONICS, INC.  
44 FARRAND STREET  
BLOOMFIELD, NJ 07003  
(973) 748-5089  
<http://www.nteinc.com>

## NTE5437 & NTE5438 Silicon Controlled Rectifier (SCR) 8 Amp Sensitive Gate, TO220

### **Description:**

The NTE5437 and NTE5438 are silicon controlled rectifiers (SCR) in a TO220 type package designed for general purpose high voltage applications where gate sensitivity is required.

### **Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)


Repetitive Peak Off-State Voltage ( $T_J = -40^\circ$ to $+125^\circ\text{C}$ , $R_{GK} = 1\text{k}\Omega$ ), $V_{DRM}$ , $V_{RRM}$	
NTE5437 .....	400V
NTE5438 .....	600V
On-State Current (All Conducting Angles, $T_C = +85^\circ\text{C}$ ), $I_T(\text{RMS})$ .....	8A
Average On-State Current (Half Cycle, $\ominus = 180^\circ$ , $T_C = +85^\circ\text{C}$ ), $I_T(\text{AV})$ .....	5.1A
Non-Repetitive On-State Current, $I_{TSM}$	
Half Cycle, 60Hz .....	88A
Half Cycle, 50Hz .....	80A
Fusing Current ( $t= 10\text{ms}$ , Half Cycle), $I^2t$ .....	32A <sup>2</sup> s
Peak Reverse Gate Voltage ( $I_{GR} = 50\mu\text{A}$ ), $V_{GRM}$ .....	8V
Peak Gate Current (10 $\mu\text{s}$ Max), $I_{GM}$ .....	2A
Peak Gate Dissipation (10 $\mu\text{s}$ Max), $P_{GM}$ .....	5W
Gate Dissipation (20ms Max), $P_{G(\text{AV})}$ .....	0.5W
Oprating Junction Temperature Range, $T_J$ .....	$-40^\circ$ to $+125^\circ\text{C}$
Storage Temperature Range, $T_{stg}$ .....	$-40^\circ$ to $+125^\circ\text{C}$
Lead Temperature (During Soldering, 1.6mm from case, 10sec Max), $T_L$ .....	$+250^\circ\text{C}$
Thermal Resistance, Junction-to-Case, $R_{thJC}$ .....	4K/W
Thermal Resistance, Junction-to-Ambient, $R_{thJA}$ .....	60K/W

### **Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Max	Unit
Off-State Leakage Current	$I_{DRM}$ , $I_{RRM}$	$V_{DRM} + V_{RRM} = \text{Rated Voltage}$ , $R_{GK} = 1\text{k}\Omega$	$T_J = +125^\circ\text{C}$	-	0.5 mA
			$T_J = +25^\circ\text{C}$	-	5.0 $\mu\text{A}$

**Electrical Characteristics (Cont'd):** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Max	Unit
On-State Voltage	$V_T$	$I_T = 16\text{A}$ , $T_J = +25^\circ\text{C}$	—	1.95	V
On-State Threshold Voltage	$V_{T(TO)}$	$T_J = +125^\circ\text{C}$	—	1.05	V
On-State Slope Resistance	$r_T$	$T_J = +125^\circ\text{C}$	—	65	$\text{m}\Omega$
Gate Trigger Current	$I_{GT}$	$V_D = 7\text{V}$	—	200	$\mu\text{A}$
Gate Trigger Voltage	$V_{GT}$	$V_D = 7\text{V}$	—	2.0	V
Holding Current	$I_H$	$R_{GK} = 1\text{k}\Omega$	—	10	mA
Latching Current	$I_L$	$R_{GK} = 1\text{k}\Omega$	—	20	mA
Critical Rate of Voltage Rise	$dv/dt$	$V_D = .67 \times V_{DRM}$ , $R_{GK} = 1\text{k}\Omega$ , $T_J = +125^\circ\text{C}$	5	—	$\text{V}/\mu\text{s}$
Critical Rate of Current Rise	$di/dt$	$I_G = 10\text{mA}$ , $di_G/dt = 0.1\text{A}/\mu\text{s}$ , $T_J = +125^\circ\text{C}$	100	—	$\text{A}/\mu\text{s}$
Gate Controlled Delay Time	$t_{gd}$	$I_G = 10\text{mA}$ , $di_G/dt = 0.1\text{A}/\mu\text{s}$	—	500	ns
Commutated Turn-Off Time	$t_q$	$T_C = +85^\circ\text{C}$ , $V_D = .67 \times V_{DRM}$ , $V_R = 35\text{V}$ , $I_T = 5.1\text{A}$	—	100	$\mu\text{s}$



# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for [SCRs](#) category:***

***Click to view products by [NTE manufacturer:](#)***

Other Similar products are found below :

[NTE5428](#) [NTE5448](#) [NTE5457](#) [NTE5511](#) [T1500N16TOF VT](#) [T720N18TOF](#) [T880N14TOF](#) [T880N16TOF](#) [TS110-7UF](#) [TT104N12KOF-A](#) [TT104N12KOF-K](#) [TT162N16KOF-A](#) [TT162N16KOF-K](#) [TT330N16AOF](#) [VS-16RIA100](#) [VS-22RIA20](#) [VS-2N5206](#) [VS-2N685](#) [VS-40TPS08A-M3](#) [VS-ST230S12P1VPBF](#) [057219R](#) [CLB30I1200HB](#) [T1190N16TOF VT](#) [T1220N22TOF VT](#) [T201N70TOH](#) [T830N18TOF](#) [TD92N16KOF-A](#) [TT250N12KOF-K](#) [VS-2N692](#) [VS-2N689](#) [VS-25RIA40](#) [VS-16RIA120](#) [VS-10RIA120](#) [VS-30TPS08PBF](#) [NTE5427](#) [NTE5442](#) [VS-2N690](#) [VS-ST300S20P0PBF](#) [TT251N16KOF-K](#) [VS-22RIA100](#) [VS-16RIA40](#) [CR02AM-8#F00](#) [VS-ST110S12P0VPBF](#) [TD250N16KOF-A](#) [VS-ST110S16P0](#) [VS-10RIA10](#) [VS-16TTS08-M3](#) [TS110-7A1-AP](#) [T930N36TOF VT](#) [T2160N24TOF VT](#)