

## SAFETY DATA SHEET SCC3 CONFORMAL COATING

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name SCC3 CONFORMAL COATING  
Product No. DCA-a, EDCA200H, ZE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Conformal coating for appliance protection  
Uses advised against At this moment in time we do not have information on use restrictions. They will be included in this safety data sheet when available

#### 1.3. Details of the supplier of the safety data sheet

Supplier ELECTROLUBE. A division of HK  
WENTWORTH LTD  
ASHBY PARK, COALFIELD WAY,  
ASHBY DE LA ZOUCH, LEICESTERSHIRE  
LE65 1JR  
UNITED KINGDOM  
+44 (0)1530 419600  
+44 (0)1530 416640  
info@hkw.co.uk

#### 1.4. Emergency telephone number

+44 (0)1530 419600 between 8.30am - 5.00pm GMT Mon – Fri

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Aerosol 1 - H222
Human health	Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315
Environment	Aquatic Chronic 2 - H411

Classification (1999/45/EEC) Xn;R20/21. Xi;R38. F+;R12. N;R51/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

##### Physical and Chemical Hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

#### 2.2. Label elements

Contains XYLENE  
Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

##### Hazard Statements

H222 Extremely flammable aerosol.

## SCC3 CONFORMAL COATING

<p><b>Precautionary Statements</b></p>	<p>H312 Harmful in contact with skin.            H315 Causes skin irritation.            H332 Harmful if inhaled.            H411 Toxic to aquatic life with long lasting effects.</p>
<p><b>Supplementary Precautionary Statements</b></p>	<p>P102 Keep out of reach of children.            P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.            P280 Wear protective gloves, eye and face protection.</p> <p>P211 Do not spray on an open flame or other ignition source.            P251 Pressurized container: Do not pierce or burn, even after use.            P261 Avoid breathing vapour/spray.            P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.</p>

### 2.3. Other hazards

Not Classified as PBT/vPvB by current EU criteria.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

<b>DIMETHYL ETHER</b>	<b>30-60%</b>
CAS-No.: 115-10-6                      EC No.: 204-065-8	
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
<b>XYLENE</b>	<b>10-30%</b>
CAS-No.: 1330-20-7                      EC No.: 215-535-7	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC) R10 Xn;R20/21 Xi;R38
<b>CYCLOHEXANE</b>	<b>10-30%</b>
CAS-No.: 110-82-7                      EC No.: 203-806-2	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC) F;R11 Xn;R65 Xi;R38 R67 N;R50/53
<b>1-METHOXY-2-PROPANOL</b>	<b>5-10%</b>
CAS-No.: 107-98-2                      EC No.: 203-539-1	

**SCC3 CONFORMAL COATING**

Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT SE 3 - H336		Classification (67/548/EEC) R10 R67	
<b>ETHYLBENZENE</b>		<b>1-5%</b>	
CAS-No.: 100-41-4		EC No.: 202-849-4	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 4 - H332		Classification (67/548/EEC) F;R11 Xn;R20	
<b>HEXANE MIXTURE OF ISOMERS (MAX 5% n-HEXANE (203-777-6))</b>		<b>1-5%</b>	
CAS-No.: -		EC No.: -	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		Classification (67/548/EEC) F;R11 Xn;R65 Xi;R38 R67 N;R51/53	
<b>HEPTANE</b>		<b>1-5%</b>	
CAS-No.: 142-82-5		EC No.: 205-563-8	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		Classification (67/548/EEC) F;R11 Xn;R65 Xi;R38 R67 N;R50/53	
<b>HEXANE-norm</b>		<b>&lt;0.5%</b>	
CAS-No.: 110-54-3		EC No.: 203-777-6	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		Classification (67/548/EEC) F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67 N;R51/53	
<b>BENZENE, C10-13-ALKYL DERIVATIVES</b>		<b>&lt;0.5%</b>	
CAS-No.: 67774-74-7		EC No.: 267-051-0	
Classification (EC 1272/2008) Not classified.		Classification (67/548/EEC) N;R50.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# SCC3 CONFORMAL COATING

## Composition Comments

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### **Inhalation**

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

#### **Ingestion**

Rinse mouth thoroughly. Provide rest, warmth and fresh air.

#### **Skin contact**

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### **Eye contact**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues. Use tepid water for rinsing

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### **Extinguishing media**

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### 5.2. Special hazards arising from the substance or mixture

#### **Hazardous combustion products**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### **Unusual Fire & Explosion Hazards**

Aerosol cans may explode in a fire.

### 5.3. Advice for firefighters

#### **Special Fire Fighting Procedures**

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

#### **Protective equipment for fire-fighters**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See section 12 as well. Collect and dispose of spillage as indicated in section 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

# SCC3 CONFORMAL COATING

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.

## 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### Storage Class

Flammable compressed gas storage.

## 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
1-METHOXY-2-PROPANOL	WEL	100 ppm	375 mg/m <sup>3</sup>	150 ppm	560 mg/m <sup>3</sup>	Sk
CYCLOHEXANE	WEL	100 ppm	350 mg/m <sup>3</sup>	300 ppm	1050 mg/m <sup>3</sup>	
DIMETHYL ETHER	WEL	400 ppm	766 mg/m <sup>3</sup>	500 ppm	958 mg/m <sup>3</sup>	
ETHYLBENZENE	WEL	100 ppm(Sk)	441 mg/m <sup>3</sup> (Sk)	125 ppm(Sk)	552 mg/m <sup>3</sup> (Sk)	
HEPTANE	WEL	500 ppm				
XYLENE	WEL	50 ppm	220 mg/m <sup>3</sup>	100 ppm	441 mg/m <sup>3</sup>	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

### Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### Protective equipment



#### Process conditions

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

#### Engineering measures

All handling to take place in well-ventilated area. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

#### Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P3). EN14387

#### Hand protection

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Gloves of nitrile rubber, PVA or Viton are recommended. Gloves should conform to EN374

#### Eye protection

Use eye protection. EN166

#### Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

#### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

# SCC3 CONFORMAL COATING

Appearance	Aerosol. Liquid
Colour	Colourless.
Odour	Solvent.
Solubility	Insoluble in water
Initial boiling point and boiling range (°C)	137 - 143 (278.6 - 289.4 F)
Melting point (°C)	-24 ( -11.2 F)
Relative density	0.780
Flash point (°C)	25 (77 F) OC (Open cup).
Auto Ignition Temperature (°C)	480
Flammability Limit - Lower(%)	1.1
Flammability Limit - Upper(%)	7

## 9.2. Other information

Volatility Description	Volatile
------------------------	----------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

Not available.

#### **Hazardous Polymerisation**

Will not polymerise.

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

#### **Materials To Avoid**

Flammable/combustible material. Strong oxidising substances.

### 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### **Toxicological information**

No information available.

#### **Other Health Effects**

This substance has no evidence of carcinogenic properties.

#### **Inhalation**

Harmful by inhalation. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

#### **Skin contact**

Harmful in contact with skin. Irritating to skin. May cause allergic contact eczema. Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin.

#### **Eye contact**

Irritating to eyes.

#### **Route of entry**

Inhalation.

# SCC3 CONFORMAL COATING

## Toxicological information on ingredients.

### HEXANE MIXTURE OF ISOMERS (MAX 5% n-HEXANE (203-777-6)) (CAS: -)

#### HEPTANE (CAS: 142-82-5)

##### Toxic Dose 1 - LD 50

222 mg/kg (ivn-mouse)

##### Toxic Conc. - LC 50

103 ppm/4h (inh-rat)

#### CYCLOHEXANE (CAS: 110-82-7)

##### Toxic Dose 1 - LD 50

12705 mg/kg (oral rat)

##### Toxic Dose 2 - LD 50

813 mg/kg (oral-mouse)

#### XYLENE (CAS: 1330-20-7)

#### Acute toxicity:

##### Acute Toxicity (Oral LD50)

3523 mg/kg Rat

##### Acute Toxicity (Dermal LD50)

12126 mg/kg Rabbit

##### Acute Toxicity (Inhalation LC50)

2700 mg/l (vapours) Rabbit 4 hours

#### Aspiration hazard:

##### Inhalation

Harmful by inhalation. Upper respiratory irritation. Central nervous system depression. Vapours may cause drowsiness and dizziness.

##### Ingestion

Swallowing concentrated chemical may cause severe internal injury. May cause nausea, headache, dizziness and intoxication. Diarrhoea.

##### Skin contact

Harmful in contact with skin. Irritating to skin.

##### Eye contact

May cause severe irritation to eyes.

##### Target Organs

Central nervous system Liver Kidneys

#### ETHYLBENZENE (CAS: 100-41-4)

#### HEXANE-norm (CAS: 110-54-3)

##### Toxic Dose 1 - LD 50

28700 mg/kg (oral rat)

##### Toxic Conc. - LC 50

48000 ppm/4h (inh-rat)

#### DIMETHYL ETHER (CAS: 115-10-6)

#### 1-METHOXY-2-PROPANOL (CAS: 107-98-2)

##### Toxic Dose 1 - LD 50

5200 mg/kg (oral rat)

##### Toxic Dose 2 - LD 50

11700 mg/kg (oral-mouse)

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

#### Ecological information on ingredients.

#### XYLENE (CAS: 1330-20-7)

### Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

# SCC3 CONFORMAL COATING

## 12.1. Toxicity

### Ecological information on ingredients.

LC 50, 96 Hrs, Fish mg/l  
4.924

HEPTANE (CAS: 142-82-5)

LC 50, 96 Hrs, Fish mg/l  
42.3

CYCLOHEXANE (CAS: 110-82-7)

Acute Toxicity - Aquatic Invertebrates  
EC50 48 hours 1.0 mg/l Daphnia magna  
Acute Toxicity - Aquatic Plants  
IC50 72 hours 2.2 mg/l

XYLENE (CAS: 1330-20-7)

LC 50, 96 Hrs, Fish mg/l  
20800  
EC 50, 48 Hrs, Daphnia, mg/l  
23300

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

## 12.2. Persistence and degradability

### Degradability

There are no data on the degradability of this product.

### Ecological information on ingredients.

### Degradability

The product is biodegradable.

XYLENE (CAS: 1330-20-7)

## 12.3. Bioaccumulative potential

### Bioaccumulative potential

No data available on bioaccumulation.

### Ecological information on ingredients.

Bioaccumulation factor  
BCF 25.9  
Partition coefficient  
3.2

XYLENE (CAS: 1330-20-7)

## 12.4. Mobility in soil

### Ecological information on ingredients.

### Mobility:

The product is insoluble in water.

XYLENE (CAS: 1330-20-7)

## 12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

### Ecological information on ingredients.

Not Classified as PBT/vPvB by current EU criteria.

XYLENE (CAS: 1330-20-7)

## 12.6. Other adverse effects



# SCC3 CONFORMAL COATING

## Ecological information on ingredients.

### XYLENE (CAS: 1330-20-7)

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1litre packed in cartons of less than 30kg gross to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed must show the following

### 14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### 14.2. UN proper shipping name

Proper Shipping Name AEROSOLS (CYCLOHEXANE)

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	2.1
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1

Transport Labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



### 14.6. Special precautions for user

EMS	F-D, S-U
Tunnel Restriction Code	(D)

# SCC3 CONFORMAL COATING

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information required.

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

#### Guidance Notes

Workplace Exposure Limits EH40.

#### EU Legislation

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

#### Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

#### Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

## SECTION 16: OTHER INFORMATION

Issued By	Helen O'Reilly
Revision Date	APRIL 2013
Revision	7
SDS No.	11409

#### Risk Phrases In Full

R12	Extremely flammable.
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R20	Harmful by inhalation.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R38	Irritating to skin.
R62	Possible risk of impaired fertility.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50	Very toxic to aquatic organisms.

## SCC3 CONFORMAL COATING

### Hazard Statements In Full

H315	Causes skin irritation.
H222	Extremely flammable aerosol.
H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H312	Harmful in contact with skin.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
H410	Very toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

## SAFETY DATA SHEET

### SCC3 CONFORMAL COATING

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1. Product identifier

Product name SCC3 CONFORMAL COATING  
 Product No. DCA-b, EDCA01L, EDCA05L, EDCA25L, EDCA200L, ZE

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Conformal coating for appliance protection  
 Uses advised against At this moment in time we do not have information on use restrictions. They will be included in this safety data sheet when available

##### 1.3. Details of the supplier of the safety data sheet

Supplier ELECTROLUBE. A division of HK  
 WENTWORTH LTD  
 ASHBY PARK, COALFIELD WAY,  
 ASHBY DE LA ZOUCH, LEICESTERSHIRE  
 LE65 1JR  
 UNITED KINGDOM  
 +44 (0)1530 419600  
 +44 (0)1530 416640  
 info@hkw.co.uk

##### 1.4. Emergency telephone number

+44 (0)1530 419600 between 8.30am - 5.00pm GMT Mon – Fri

#### SECTION 2: HAZARDS IDENTIFICATION

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 3 - H226
Human health	Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315
Environment	Not classified.

###### Classification (1999/45/EEC)

Xn;R20/21. Xi;R38. R10.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

##### 2.2. Label elements

Contains XYLENE

Label In Accordance With (EC) No. 1272/2008



Signal Word

Warning

Hazard Statements

H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.

# SCC3 CONFORMAL COATING

## Precautionary Statements

P280	Wear protective gloves, eye and face protection.
Supplementary Precautionary Statements	
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261	Avoid breathing vapour/spray.

## 2.3. Other hazards

Not Classified as PBT/vPvB by current EU criteria.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

<b>XYLENE</b>	<b>30-60%</b>
CAS-No.: 1330-20-7	EC No.: 215-535-7
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC) R10 Xn;R20/21 Xi;R38
<b>ETHYLBENZENE</b>	<b>5-10%</b>
CAS-No.: 100-41-4	EC No.: 202-849-4
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 4 - H332	Classification (67/548/EEC) F;R11 Xn;R20
<b>PROPAN-2-OL</b>	<b>1-5%</b>
CAS-No.: 67-63-0	EC No.: 200-661-7
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R36 R67
<b>BENZENE, C10-13-ALKYL DERIVATIVES</b>	<b>&lt;0.5%</b>
CAS-No.: 67774-74-7	EC No.: 267-051-0
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) N;R50.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### Composition Comments

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### Inhalation

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

# SCC3 CONFORMAL COATING

## Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Get medical attention immediately!

## Skin contact

Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

## Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists. Use tepid water for rinsing

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

### 5.2. Special hazards arising from the substance or mixture

#### Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground to sources of ignition.

#### Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up.

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out.

#### Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards. For waste disposal, see section 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### 7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

#### Storage Class

Flammable compressed gas storage.

### 7.3. Specific end use(s)

# SCC3 CONFORMAL COATING

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ETHYLBENZENE	WEL	100 ppm(Sk)	441 mg/m3(Sk)	125 ppm(Sk)	552 mg/m3(Sk)	
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	
XYLENE	WEL	50 ppm	220 mg/m3	100 ppm	441 mg/m3	Sk

WEL = Workplace Exposure Limit.  
Sk = Can be absorbed through skin.

#### Ingredient Comments

WEL = Workplace Exposure Limits

#### PROPAN-2-OL (CAS: 67-63-0)

<b>DNEL</b>			
Industry	Dermal	888	mg/kg/day
Industry	Inhalation.	500	mg/m3
Consumer	Dermal	319	mg/kg/day
Consumer	Inhalation.	89	mg/m3
Consumer	Oral	26	mg/kg/day
<b>PNEC</b>			
Freshwater	140.9	mg/l	
Marinewater	140.9	mg/l	
Sediment	552	mg/kg	
Soil	28	mg/kg	

### 8.2. Exposure controls

#### Protective equipment



#### Process conditions

Use engineering controls to reduce air contamination to permissible exposure level.

#### Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

#### Respiratory equipment

Respiratory protection must be used if air contamination exceeds acceptable level. In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. Use respiratory equipment with combination filter, type A2/P3. EN14387

#### Hand protection

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

#### Eye protection

Wear approved, tight fitting safety glasses where splashing is probable.

#### Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

#### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Amber.

# SCC3 CONFORMAL COATING

Odour	Aromatic.
Solubility	Immiscible with water
Initial boiling point and boiling range (°C)	137 - 143 (278 - 290 F)
Relative density	0.965 @ 20 °C (68 F)
Vapour pressure	1.0 kPa @ 30 °C (86 F)
Flash point (°C)	27 (80.6 F) CC (Closed cup).
Flammability Limit - Lower(%)	7
Flammability Limit - Upper(%)	10

## 9.2. Other information

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

There are no known reactivity hazards associated with this product.

#### 10.2. Chemical stability

Stable under normal temperature conditions.

#### 10.3. Possibility of hazardous reactions

Not available.

#### Hazardous Polymerisation

Will not polymerise.

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

#### 10.5. Incompatible materials

#### Materials To Avoid

Strong oxidising substances.

#### 10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

#### Toxicological information

No information available.

#### General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

#### Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

#### Ingestion

Harmful if swallowed. Swallowing concentrated chemical may cause severe internal injury. May cause liver and/or renal damage.

#### Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

#### Eye contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

#### Toxicological information on ingredients.



# SCC3 CONFORMAL COATING

## XYLENE (CAS: 1330-20-7)

### Acute toxicity:

#### Acute Toxicity (Oral LD50)

3523 mg/kg Rat

#### Acute Toxicity (Dermal LD50)

12126 mg/kg Rabbit

#### Acute Toxicity (Inhalation LC50)

2700 mg/l (vapours) Rabbit 4 hours

### Aspiration hazard:

#### Inhalation

Harmful by inhalation. Upper respiratory irritation. Central nervous system depression. Vapours may cause drowsiness and dizziness.

#### Ingestion

Swallowing concentrated chemical may cause severe internal injury. May cause nausea, headache, dizziness and intoxication. Diarrhoea.

#### Skin contact

Harmful in contact with skin. Irritating to skin.

#### Eye contact

May cause severe irritation to eyes.

#### Target Organs

Central nervous system Liver Kidneys

## PROPAN-2-OL (CAS: 67-63-0)

### Acute toxicity:

#### Acute Toxicity (Oral LD50)

5280 mg/kg Rat

#### Acute Toxicity (Dermal LD50)

12800 mg/kg Rabbit

#### Acute Toxicity (Inhalation LC50)

72.6 mg/l (vapours) Rat 4 hours

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Not regarded as dangerous for the environment.

### Ecological information on ingredients.

## XYLENE (CAS: 1330-20-7)

### Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

### 12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l

Xylene 2.6-8.4

# SCC3 CONFORMAL COATING

## Ecological information on ingredients.

### XYLENE (CAS: 1330-20-7)

#### Acute Toxicity - Aquatic Invertebrates

EC50 48 hours 1.0 mg/l Daphnia magna

#### Acute Toxicity - Aquatic Plants

IC50 72 hours 2.2 mg/l

### PROPAN-2-OL (CAS: 67-63-0)

#### Acute Toxicity - Fish

LC50 96 hours 9640 mg/l Pimephales promelas (Fat-head Minnow)

#### Acute Toxicity - Aquatic Invertebrates

EC50 48 hours 13299 mg/l Daphnia magna

#### Acute Toxicity - Aquatic Plants

EC50 72 hours > 1.000 mg/l Scenedesmus subspicatus

#### Acute Toxicity - Microorganisms

EC50 > 1.000 mg/l Activated sludge

## 12.2. Persistence and degradability

### Degradability

There are no data on the degradability of this product.

## Ecological information on ingredients.

### XYLENE (CAS: 1330-20-7)

#### Degradability

The product is biodegradable.

## 12.3. Bioaccumulative potential

### Bioaccumulative potential

No data available on bioaccumulation.

## Ecological information on ingredients.

### XYLENE (CAS: 1330-20-7)

#### Bioaccumulation factor

BCF 25.9

#### Partition coefficient

3.2

## 12.4. Mobility in soil

## Ecological information on ingredients.

### XYLENE (CAS: 1330-20-7)

#### Mobility:

The product is insoluble in water.

## 12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

## Ecological information on ingredients.

### XYLENE (CAS: 1330-20-7)

Not Classified as PBT/vPvB by current EU criteria.

## 12.6. Other adverse effects

## Ecological information on ingredients.

### XYLENE (CAS: 1330-20-7)

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

# SCC3 CONFORMAL COATING

## 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

UN No. (ADR/RID/ADN)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

### 14.2. UN proper shipping name

Proper Shipping Name	PAINT
----------------------	-------

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	



### 14.4. Packing group

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

### 14.6. Special precautions for user

EMS	F-E, S-E
Emergency Action Code	•3Y
Hazard No. (ADR)	30
Tunnel Restriction Code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information required.

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

# SCC3 CONFORMAL COATING

## Guidance Notes

Workplace Exposure Limits EH40.

## EU Legislation

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

### Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

### Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

## 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

## SECTION 16: OTHER INFORMATION

Issued By	Helen O'Reilly
Revision Date	APRIL 2013
Revision	10
SDS No.	11407

### Risk Phrases In Full

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R20	Harmful by inhalation.
R11	Highly flammable
R36	Irritating to eyes.
R38	Irritating to skin.
R67	Vapours may cause drowsiness and dizziness.
R50	Very toxic to aquatic organisms.

### Hazard Statements In Full

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H312	Harmful in contact with skin.
H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

## Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for PPE Safety Equipment / Lockout Tagout category:*

*Click to view products by Electrolube manufacturer:*

Other Similar products are found below :

[S-920S](#) [GPSL-7KAMK](#) [GPSL-6LSKA](#) [GPSL-6MK](#) [GPSL-7LSKA](#) [GPSL-7MK](#) [GPSL-8MK](#) [50585](#) [GPSL-8MK-E](#) [740053624](#) [GPSL-12MK](#) [GPSL-8KAMK-P](#) [GPSL-13AKA](#) [GPSL-13BKA](#) [GPSL-16AKA](#) [GPSL-13CKA](#) [GPSL-16BKA](#) [GPSL-13DKA](#) [GPSL-13D-LSKA](#) [GPSL-16CKA](#) [GPSL-16C-LSKA](#) [GPSL-16DKA](#) [GPSL-6ABUKA](#) [GPSL-14ABLKA](#) [GPSL-13EKA](#) [GPSL-6ABU-LSKA](#) [GPSL-6BUKA](#) [GPSL-16EKA](#) [GPSL-14BYLKA](#) [GPSL-14BYL-LSKA](#) [GPSL-6CBUKA](#) [GPSL-6BU-LSKA](#) [GPSL-6ABUMK](#) [GPSL-6CBU-LSKA](#) [GPSL-15ABUKA](#) [GPSL-6BUMK](#) [GPSL-6DBUKA](#) [GPSL-17BBLKA](#) [GPSL-16FKA](#) [GPSL-6CBUMK](#) [GPSL-6BU-LSMK](#) [GPSL-6DBU-LSKA](#) [GPSL-6CBU-LSMK](#) [GPSL-15ABUMK](#) [GPSL-15ABU-LSKA](#) [GPSL-6DBUMK](#) [GPSL-15BBUKA](#) [GPSL-15ABU-LSMK](#) [GPSL-15BBUMK](#) [PSL-20SA-S](#)