



[United States](#) > [Products & Services](#) > [Safety, Security, and Protection](#) > [Wire-to-Board Connectors](#) > 3M™ Four-Wall Header, 2500 Series, N2534-6003-RB

3M™ Four-Wall Header, 2500 Series, N2534-6003-RB

UPC# 00051111651995 3M Product Number N2534-6003-RB 3M ID 80400028868

Print Share



· Low profile, space saving design · Center slot polarization prevents mis-insertions and reduces insertion time · Dual slot polarization means broader compatibility with competitive polarization designs (not 10 pos.) · Optional retainer clip for locking sockets in place and increasing connection reliability in vibration-prone environments · Optional high temperature insulator suitable for "no lead" soldering operations · High temperature option in through-hole version suitable for "paste in hole" reflow soldering techniques · Exposed solder tails (on right angle version) provide ease of cleaning and reduced repair costs · Straight surface mount version available · See Regulatory Information Appendix (last page of Tech Data Sheet) for chemical compliance information

Need Help?

Questions? We can help
[Contact Us](#)



Overview **Support**

· Low profile, space saving design · Center slot polarization prevents mis-insertions and reduces insertion time · Dual slot polarization means broader compatibility with competitive polarization designs (not 8 or 10 pos.) · Optional retainer clip for locking sockets in place and increasing connection reliability in vibration-prone environments · Optional High temperature insulator suitable for "no lead" soldering operations · High temperature option in thru hole version suitable for "paste in hole" reflow soldering techniques · Exposed solder tails (on right angle version) provide ease of cleaning and reduced repair costs · Straight surfacemount version available · See Regulatory Information Appendix (last page of Tech Data Sheet) for chemical compliance information

Specifications

Color	Gray (PBT), Black (PCT)
Electrical Current Rating	5.00 A, 1 Contact Powered; 3.00 A, 6 Contacts Powered; 1.75 A, All Contacts Powered
EU RoHS Compliant	Yes
Process Rating	High Temp PCT insulator version: 260 Degree C, per J-STD-020C, single pass PBT insulator version: 191 Degree C, maximum insulator temperature, solder wave process only

People who viewed this item also viewed



3M™ .100 in. 4-Wall Header, High Temp Option, Straight, 24 Contacts, 3627-6603



3M™ Color Coded Flat Cable, 3302 Series, 3302/64SF, 100 ft.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [3M](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [009176003701906](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#)