TK 2002





TEMPERATURE DIFFERENCE **MEASUREMENT AS WELL!**

New! TK 2002, simplicity with 2 inputs!

The TK 2002 is a 2-input, K-thermocouple thermometer equipped with a HOLD function.

Technical specifications:

-Measurement range: -50 $^{\circ}\text{C}$ to 1,000 $^{\circ}\text{C}$

-Resolution: 0.1 or 1 °C

-Accuracy: -50 $^{\circ}$ C to 0 $^{\circ}$ C: ± 1 $^{\circ}$ C and 0 to 1,000 $^{\circ}$ C: $\pm 1.5\% \pm 0.5$ $^{\circ}$ C

- Display: 2,000 points

-Dimensions: 63 x 163 x 37.5 mm

-Weight: 200 g

State of delivery: delivered with 2 flexible K-thermocouple sensors

for measurements from -40 °C to +200 °C

environmental testing & measurement > thermometer > with K-type thermocouple





NEW!

Simple temperature testing in all circumstances!

The TK 2000 is a 1-input, K-thermocouple thermometer equipped with a HOLD function:

Technical specifications:

- -Measurement range: -50 $^{\circ}\text{C}$ to 1,000 $^{\circ}\text{C}$ -Resolution: 0.1 or 1 $^{\circ}\text{C}$
- -Accuracy: -50 $^{\circ}C$ to 0 $^{\circ}C:$ ±1 $^{\circ}C$ and 0 to 1,000 $^{\circ}C:$ ±1.5% ±0.5 $^{\circ}C$
- -Display: 2,000 counts
- -Dimensions 63 x 163 x 37.5 mm
- -Weight: 200 g

State of delivery: delivered with 1 flexible K-thermocouple sensor for measurements from -40 °C to +200 °C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Chauvin Arnoux manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160