

**Technical data**

Material : Polypropylene (PP)  
 Adhesive material (for HTC-SK) : Synthetic rubber with base of polyethylene foam  
 Colour : White  
 Operating temperature : From -20°C to +70 °C  
 Flammability (excluding adhesive) : UL94 V0  
 Approvals : Material: UL94 V0 (File E86615)



Article-No.	Type	Inner Ø	Capacity in pieces (no. of wires)		
			0,75 mm <sup>2</sup>	1,5 mm <sup>2</sup>	2,5 mm <sup>2</sup>
<b>screwable</b>					
164-11008	Heladuct Flex10	9 x 11	9	6	4
164-21008	Heladuct Flex20	20	32	22	14
164-31008	Heladuct Flex30	30	67	50	34
164-41008	Heladuct Flex40	40	-	81	60
<b>adhesive</b>					
164-11108	Heladuct Flex10 SK	9 x 11	9	6	4
164-21108	Heladuct Flex20 SK	20	32	22	14
164-31108	Heladuct Flex30 SK	30	67	50	34
164-41108	Heladuct Flex40 SK	40	-	81	60

All dimensions in mm. Supplied in 500mm length.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)