

3M Electrical

Solutions for Electrical

- + Electrical Construction & Maintenance
- Electrical and Electronic OEM
- + Utilities
- Mining
- Field Training
- Oil & Gas
- Heat Tracing
 - Heat Tracing Design Software Registration
 - Job Box

Product and Services

- Products
- Where to Buy
- Request Product Information
- Shelf Life & Storage Conditions

Resources

- + Industry Standards & Compliance
- Literature Selector

News & Events

- Press Releases
- Industry Links

Support

- Contact Us
- Training

Heat Tracing

Product Catalog for 3M Mining > 3M Electronics Manufacturing . . . 3M™ .100 in. 4-Wall Header, Straight, 3000 Series > 3M™ .100 in. 4-Wall Header, High Temp Option, Straight, 34 Contacts, 3431 Series >

3M™ 4-Wall Header .100 in., High Temp Option, Straight, 34 Contacts, 3431-6603

[Printer-friendly format](#)



.100" x .100" Latch/Ejector, Standard, 4 wall straight solder tail, Long Snap-In Latch/Ejectors (3M Part#3505-31) Solder tails for .094 to .125[2.39 to 3.18] thick board, 30µ" gold plating.

[\[click to enlarge\]](#)

3M Id : 80-6104-7370-6
GTIN(UPC/EAN) : 0 00 51138 62104 9


Additional Information

Learn More . . .

[Packaging Data](#)
[3M™ .100 in. 4-Wall Hdr., Latch/Ejector, High Temp Opt., TS0772 - Data Sheet \(PDF 1.3 MB\)](#)

Please Note:

Adobe® Acrobat® Reader is required to view PDF documents.



Characteristics

China RoHS - Below MCV	No
Color	Gray (PBT), Black (PCT)
Contact Material	Copper Alloy
Contact Termination Area Plating	200 µ" [5.08 µm] 90/10 Tin/Lead
Contact Underplating	100 µ" [2.54 µm] Nickel
Contact Wiping Area Plating	30 µ" [0.76 µm] Gold
Current Rating	2 Ampere
Electrical Current Rating	5.00 A, 1 Contact Powered; 3.00 A, 6 Contacts Powered; 1.75 A, All Contacts Powered
EU RoHS Compliant	No
Insulation Color	Gray
Insulation Flammability Rating	UL 94V-0
Insulation Material	Glass Filled Polyester (PBT)
Insulation Resistance	>1 X 10 ⁹ Ohms @ 500 Vdc
Interface Grid	.100" x .100"
Interface Style	Header (Rectangular Plug)
Latch/Ejector Type	Long, Snap in Latch/Ejectors
Markings	3M Logo, Part Identification Number and Orientation Triangle
Mounting Option	None
Non-Operating Temperature	-55 to 105 Degree Celsius
Number of Contact Rows	2
Number of Contacts	34
Number of Walls	4
Orientation	Vertical
Pitch	0.100 Inch
Polarization	Military & Center Bump
Process Rating	High Temp PCT insulator version: 260 Degree C, per J-STD-020C, single pass PBT insulator version: 191 Degree C, maximum insulator temperature, solder wave process only
Separable	Yes
Tail Length	.155 Inch
Termination Method	Solder Tail
Termination Style	Printed Circuit Board
UnderPlating Material	100 micro inches [2.54 micro meter] Nickel-Overall
Withstanding Voltage	1000 Vrms at Sea Level

Quick Clicks

- [Where to Buy](#)
- < [Product Selectors](#)
- ✉ [Contact Us](#)
- [RoHS Compliance Product Look Up](#)
- [Material Safety Data Sheets](#)

FREE
Download your copy of the TTS™ Trace Design Software

Where to Buy
and/or
Request More Information

Related Links

- [Sustainability](#)
- [3M RoHS Specification \(PDF 46K\)](#)
- [RoHS Directive](#)
- [Request more RoHS](#)
- [Compliance Information](#)
- [WEEE Initiative](#)
- [WEEE Legislative Summary](#)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [3M](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65781-018](#) [65781-047](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#)