

Bulk Cable Specification

TFCLS2004 Category 5e Cable

Cross-Sectional View				Color Code
JACKET O O DRAIN WIRE TWISTED O O POLYESTER PAIR SHIELD				Pair 1. Blue, White / Blue Pair 2. Orange, White / Orange Pair 3. Green, White / Green Pair 4. Brown, White / Brown
ITEM			DESCRIPTION	
	ductors	4 Pairs		
Conductor	Material		Stranded Tinned copper	
	Construction		26 AWG 7/34	
Insulation	Material		Polyolefin	
	Nominal Diameter		.039"	
Shielding	Material		Aluminum / polyester tape	
	Coverage		100%	
Drain Wire	Material		Tinned copper	
	Construction		26 AWG 7/34	
Jacket	Material		Low Smoke, Zero Halogen	
	Nominal Thickness		.022"	
	Nominal Diameter		.215"	
	Color		Black	
Minimum Marking: (White Ink) (Spaced at 18") L-COM LOW SMOKE ZERO HALOGEN CATEGORY 5e 26 AWG FTP STRANDED 75° C 300V				
ELECTRICAL PROPERTIES				
DC Resistance		42.6Ω / 1000 ft		
Conductor to conductor capacitance		13.5pF / ft @ 1MHz		
Impedance		100Ω ± 15Ω, 1-350 MHz		
Dielectric Withstanding, MIN		1500 Vrms		
Voltage rating MAX		300V		
LISTINGS / RATINGS				
Temperature Rating: -20°C to +75°C				
Flame Rating: IEC 332 Part 1				

Packaging: 1000 FT REEL

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 1-com manufacturer:

Other Similar products are found below :

FOA-550A UMC-201 CSMN50MF-5 CSMNB15MF-15 TRD815RA2BL-5 CA3N050 CA3A-90DA-1M CTLF3VGAMM-20 HDCAMM-3 U3A00014-03M ECF-SK-25 CSMT15MF-10 CSMT15MM-15 CSMT15MM-25 CSPL15MF-50 CSPL25MF-25 CSPL9MF-10 CSPL9MF-5 CSPL25MF-5 CSPL25MF-2.5 AL-IPEPS NB201611-10F-1 TDG1026KC5-MNL NB121005-10F TRD855SRA6DBL-10M TRD855SRA7DBL-1M TRD855SRA7DBL-10M PR175SCDLCQ24 TRG508-T4T-3M TRA5261-15F TRA5261S-1F TRA6261-1F USBBFT DGB25M CASATAL-18 CSM25MM-10 CSM37MF-10 CSUSB-100 CA3A-90RA-1M CA3A-90RMICB-1M U2A00003-3M U3A00003-05M U2A00008-12I U3A00007-075M U3A00007-1M CSMT15MF-5 CSMT15MM-50 CSPL15MF-25 LPXT-WP-PMT CSMT15MF-50