

## T50ML9C2



**Article Number:** 113-05419

**Screw Mount Tie, 50lb, 15.4", Max Bundle Diameter 4.0", #10 Screw, PA66HS, Natural, 100/pkg**



Download spec sheet

### Base Data

<b>Local Order Number</b>	T50ML9C2
<b>Type</b>	T50ML
<b>Color</b>	Natural (NA)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Mount design secures firmly with any #10 Screw.</li> <li>• Screw mount style creates low insertion and high extraction force.</li> </ul>
<b>Product Description</b>	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
<b>Short Description</b>	Screw Mount Tie, 50lb, 15.4", Max Bundle Diameter 4.0", #10 Screw, PA66HS, Natural, 100/pkg

### Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	50.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	225 N
<b>Length L (Imperial)</b>	15.4 "
<b>Length L (Metric)</b>	390.0 mm
<b>Fixation Method</b>	fixing hole
<b>Identification Plate Position</b>	none
<b>Mounting Screw Type</b>	M5
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18 "
<b>Width W (Metric)</b>	4.7 mm
<b>Height H (Imperial)</b>	0.23 "
<b>Height H (Metric)</b>	5.7 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.12 "
<b>Bundle Diameter Min. (Metric)</b>	3.0 mm
<b>Bundle Diameter Max. (Imperial)</b>	4.0 "
<b>Bundle Diameter Max. (Metric)</b>	100.0 mm
<b>Mounting Hole Diameter D (Imperial)</b>	0.22 "
<b>Mounting Hole Diameter D (Metric)</b>	5.5 mm
<b>Thickness T (Imperial)</b>	0.05 "
<b>Cable Tie Head Length (Imperial)</b>	0.79 "
<b>Cable Tie Head Width (Imperial)</b>	0.35 "
<b>Mounting Hole Diameter D Max.</b>	5.5 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 5.5 mm

**Thickness T (Metric)** 1.2 mm

---

## Logistics and Packaging

---

**Quantity Per** bag

**Package Quantity (Metric)** 100 Pieces

**Carton Quantity** 5000

**Weight (Metric)** 2.9 kg

---

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes

**Certification/Specification** UL

**UL Listed (US and Canada)** Yes

**UL Recognized (US and Canada)** Yes

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)