

T30RSF0M4



Article Number: 126-00702

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19" - 0.22", PA66HS, Black, 1,000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T30RSF0M4

Type T30RSF(U)

Color Black (BK)

- Features and Benefits**
- Push Mount design provides quick and easy mounting.
 - Push mount style creates low insertion and high extraction force.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.

Product Description Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

Short Description Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19" - 0.22", PA66HS, Black, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 135 N

Length L (Imperial) 6.3 "

Length L (Metric) 161.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14 "

Width W (Metric) 3.6 mm

Height H (Imperial) 0.2 "

Height H (Metric) 5.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.3 "

Bundle Diameter Max. (Metric) 31.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Max. (Metric) 2.4 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 0.9 mm

Mounting Hole Diameter D (Imperial) 0.19 - 0.22 "

Mounting Hole Diameter D (Metric) 4.7 - 5.5 mm

Mounting Hole Diameter D Min. 0.19 "
(Imperial)

Mounting Hole Diameter D Max. 0.22 "
(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. 5.6 mm
(Metric)

Mounting Hole Diameter D Min. (Metric) 4.8 mm

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)