

EAO AG

Tannwaldstrasse 88 4600 Olten Switzerland

Phone: +41 62 286 9111

info@eao.com

## Part No. 45-1231.21K6.000.101, Illuminated Pushbutton



## Specifications | Bill of Materials

pecifications	
Actuator	Illuminated pushbutton
Lens Colour	Clear, transparent
Function	2 Positions, momentary (O <i)< td=""></i)<>
Housing Material	Metal
Shape of Handle or Frontring	raised/ level to bezel
Lock System	None
Key	None
Key Type	None
Switching Angle	None
Contacts	1NO
Terminal	Screw terminal
Voltage Illumination	24V AC/DC

Mounting Type	Front mounting		
Mounting Style	Holder		
Environmental Rating	IP66, IP67, IP69K		
Industry Standards/Certifications	UL, CSA, VDE, CCC, CE, RoHS		
Switching Function	On-Off		
Illumination	White		
Contact Material	Silver		
Termination Style	Screw		
Mechanical Life	Maintain 500'000 switching cycles Momentary 3'000'000 switching cycles		
AC Voltage	500 V		
DC Voltage	500 V		
Switching Current	10 A		

Bill of Materials		-
Actuator	45-2231.21K0.000	
Holder	45-2300.2000.000	
Switch Element 1	45-311.1Z10	
LED Module	45-320.1N16	

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by EAO manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000

MDPSSGLFS 810KSV30B FLT 2U EE 01A MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL

8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL

ABD122N-B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047

1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6

1301940184 RELBARF6X10(PLASTIC)