

EAO AG

Tannwaldstrasse 88 4600 Olten Switzerland

Phone: +41 62 286 9111

info@eao.com

Part No. 45-1131.3110.000.101, Pushbutton



Specifications | Bill of Materials

ecifications		
Actuator	<u>Pushbutton</u>	
Lens Colour	Black	
Function	2 Positions, momentary (O <i)< td=""></i)<>	
Housing Material	Metal/Plastic	
Shape of Handle or Frontring	raised/ level to bezel	
Lock System	None	
Key	None	
Key Type	None	
Switching Angle	None	
Contacts	1NO	
Terminal	Screw terminal	
Voltage Illumination	None	

Mounting Type	Front mounting		
Mounting Style	Holder		
Environmental Rating	IP66, IP67, IP69K		
Industry Standards/Certifications	UL, CSA, VDE, CCC, CE, RoHS		
Switching Function	On-Off		
Illumination	None		
Contact Material	Silver		
Termination Style	Screw		
Mechanical Life	Maintain 500'000 switching cycles Momentary 10'000'000 switching cycles		
AC Voltage	500 V		
DC Voltage	500 V		
Switching Current	10 A		

Bill of Materials		_
Actuator	45-2131.3110.000	
Holder	45-2300.1000.000	
Switch Element 1	45-311.1Z10	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by EAO manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000

MDPSSGLFS 810KSV30B FLT 2U EE 01A MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL

8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL

ABD122N-B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047

1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6

1301940184 RELBARF6X10(PLASTIC)