



Stripmaster® & Stripmaster® Lite Wire Strippers

- One-step stripping enhances productivity
- Precision-ground, knife-type blades provide clean, accurate stripping
- Sturdy die-cast zinc frame provides long-term durability
- Stripmaster® Lite designed for smaller hands – 3/4 the size of the standard Stripmaster®
- 90-day warranty

Stripmaster® Wire Strippers and Knife-Type Blades

| Specifications — Stripping Hole Diameter in Inches (mm) | | | | | | | | | | | | | Replacement Blades (Pair) Cat. No. | Replacement Frame Cat. No. | Tool w/Blades Cat. No. |
|---|----------------|---|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|------------------------------------|----------------------------|------------------------|
| Wire Size AWG | | | | | | | | | | | | | | | |
| 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26 | 28 | 30 | | | |
| | 0.159 (4.0) | .141 (3.6) | .106 (2.7) | | | | | | | | | | L-4419 | L-5620 | 45-090 or 45-290* |
| | | .144 (3.6) | .105 (2.7) | .085 (2.2) | .073 (1.8) | .073 (1.8) | | | | | | | L-4420 | L-5620 | 45-091 |
| | | .144 (3.6) | .113 (2.9) | .090 (2.3) | .072 (1.8) | .061 (1.5) | .048 (1.2) | .048 (1.2) | | | | | L-4421 | L-5620 | 45-092 or 45-292* |
| | | | | .090 (2.3) | .072 (1.8) | .061 (1.5) | .039 (1.0) | .039 (1.0) | | | | | L-4422 | L-5620 | 45-093 |
| .230 (2.3) | .198 (5.0) | <i>This tool has a custom steel frame & custom step grippers.</i> | | | | | | | | | | | L-4453 | L-4453 | 45-096 |
| | | | | | .072 (1.8) | .061 (1.5) | .048 (1.2) | .039 (1.0) | .032 (0.8) | .026 (0.7) | | | L-4994 | L-5620 | 45-097 |
| | | | | | | | .048 (1.2) | .039 (1.0) | .032 (0.8) | .026 (0.7) | .021 (0.5) | .016 (0.4) | L-5361 | L-5620 | 45-098 |
| | .198 (5.0) | .167 (4.2) | | | .062 (1.6) | .055 (1.4) | | | | | | | L-8763 | L-5620 | 45-099 |

* Blister Card Tolerances ±.001"

Stripmaster® Lite Wire Strippers and Knife-Type Blades

| Specifications — Stripping Hole Diameter Inches (mm) | | | | | | | | | | Replacement Blades (Pair) Cat. No. | Replacement Frame Cat. No. | Tool w/Blades Cat. No. |
|--|---------------|---------------|---------------|---|---------------|---------------|---------------|---------------|---------------|------------------------------------|----------------------------|------------------------|
| Wire Size AWG | | | | | | | | | | | | |
| 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26 | 28 | 30 | | | |
| | | .072 (1.8) | .061 (1.5) | .048 (1.2) | .039 (1.0) | | | | | LB-1001 | LB-1421 | 45-671 |
| | | | | | | .032 (0.8) | .026 (0.7) | .021 (0.5) | .016 (0.4) | LB-1002 | LB-1421 | 45-672 |
| .113 (2.9) | .090 (2.3) | .072 (1.8) | .061 (1.5) | All stranded wire | | | | | | LB-1003 | LB-1421 | 45-673 |
| .096 (2.4) | .085 (2.2) | .073 (1.9) | .061 (1.5) | 12 & 14 Solid Wire, 16 & 18 Stranded Wire | | | | | | LB-1004 | LB-1421 | 45-674 |

Tolerances ±.001"

Stripmaster® Wire Strippers and Knife-Type Blades for Metric Wire

| Specifications — Stripping Hole Diameter (mm) | | | | | | | | | | | | | | Replacement Blades (Pair) Cat. No. | Replacement Frame Cat. No. | Tool w/Blades Cat. No. |
|---|-----|------|------|------|-----|------|-----|-----|-----|---|-----|-----|-----|------------------------------------|----------------------------|---------------------------|
| Wire Size mm ² | | | | | | | | | | | | | | | | |
| 0.05 | 0.1 | 0.15 | 0.22 | 0.34 | 0.5 | 0.75 | 1 | 1.5 | 2.5 | 4 | 6 | 8 | 10 | | | |
| | | | | | | | | | | | | 4.3 | 5.0 | L-4419M | LA-2358 | 45-090-341 |
| | | | | | | 1.3 | 1.6 | 1.9 | 2.4 | 3 | 3.6 | | | L-4421M | LA-2358 | 45-092-341 or 45-292-341* |
| 0.6 | 0.7 | 0.8 | 0.9 | 1.0 | 1.1 | | | | | | | | | L-5361M | LA-2358 | 45-098-341 |

*Blister Card Tolerances ±.025mm

Stripmaster® Lite Wire Strippers

Stripmaster® Lite Wire Strippers and Knife-Type Blades for Metric Wire

| Specifications — Stripping Hole Diameter (mm) | | | | | | | | | Replacement Blades (Pair) Cat. No. | Replacement Frame Cat. No. | Tool w/Blade Cat. No. |
|---|-----|------|------|------|-----|------|-----|-----|------------------------------------|----------------------------|-----------------------|
| Wire Size mm ² | | | | | | | | | | | |
| 0.05 | 0.1 | 0.15 | 0.22 | 0.34 | 0.5 | 0.75 | 1 | 1.5 | | | |
| | | | | 1.0 | 1.1 | 1.3 | 1.6 | 1.9 | LB-1001M | H-2909 | 45-671-341 |
| 0.6 | 0.7 | 0.8 | 0.9 | | | | | | LB-1002M | H-2909 | 45-672-341 |

Coax Stripmaster® Wire Strippers & Blades



| Description | Repl. Blade Cat. No. | Tool w/Blade Cat. No. |
|---------------------------------------|----------------------|-----------------------|
| Coax Stripmaster® for RG-6 | LB-740 | 45-262 |
| Coax Stripmaster® for RG-58 | LB-742 | 45-264 |
| Coax Stripmaster® for RG-59 | LB-743 | 45-265 |
| Coax Stripmaster® for RG-6 QuadShield | LA-3953 | 45-282 |

Coaxial Cables: two-step strip for termination, jacket and dielectric.

Stripmaster® Wire Strippers with Rectangular Holes



| Description | Replacement Blades (Pair) Cat. No. | Tool w/Blade Cat. No. |
|---|------------------------------------|-----------------------|
| For Flat Telephone Cable (.060 in. or 1.52mm) | LB-1155 | N/A |
| For European Flat Lamp Cord | L-8762 | 45-089 |
| For SP-SPT Lamp Cord | L-4452 | 45-095* |

*Also strips 2- and 3-conductor low-voltage wire used in E.E. and Touchplate remote control wiring system.

Optional Accessories

- Wire Stop provides uniform stripping length, range = 3/32" to 3/4"
- Short stop latches protect wire strands by limiting stripping stroke to 5/32 in. and retain slug until wire is ready for terminating.



| Description | Cat. No. |
|---|----------|
| Transparent Adjustable Wire Stop (for Stripmaster® Wire Strippers) | L-5270 |
| Transparent Adjustable Wire Stop (for Stripmaster® Lite Wire Strippers) | LB-1195 |
| Transparent Adjustable Wire Stop (for Metric Stripmaster® Wire Strippers) | 45-2019 |
| Short Stop Latch for Custom & Customer Steel Stripmaster® Wire Strippers | L-5269 |
| Short Stop Latch for Custom Stripmaster® Lite Wire Strippers | LB-1194 |

Replacement Parts

| Description | Cat. No. |
|--|----------|
| Replacement Frame for Stripmaster® Wire Strippers | L-5620 |
| Replacement Frame for Stripmaster® Lite Wire Strippers | LB-1421 |
| Replacement Moveable Gripper for Stripmaster® Wire Strippers | L-1953 |

FREE APPLICATION ENGINEERING SERVICE AVAILABLE. CONTACT IDEAL ELECTRICAL FOR COMPLETE INFORMATION AT 1-800-324-9571 OR DOWNLOAD APPLICATION AT WWW.IDEALIND.COM/PRODUCTS/WIRE-PROCESSING.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ideal manufacturer](#):

Other Similar products are found below :

[30-696](#) [74-027](#) [45-292](#) [45-098](#) [L-5361](#) [45-093](#) [45-177](#) [45-1987-1](#) [41-990](#) [25HK-AY-090A266-DH](#) [45-415](#) [45-418](#) [30-503](#) [35-020](#) [35-060](#)
[35-516](#) [45-1633-1](#) [45-170](#) [45-1773-1](#) [45-1774](#) [45-1939-1](#) [45-2133-1](#) [45-298](#) [45-372](#) [K-6336](#) [K-8906R](#) [L-4866](#) [L-5210](#) [L-5562](#) [L-9038](#)
[LB-1091](#) [35-522](#) [61-775](#) [KB-0276R](#) [30-429](#) [33-856](#) [45-672](#) [45-171](#) [34-015](#) [33-864](#) [30-506](#) [25HK-AP-060A100-CP-3A](#) [15DYS624-](#)
[240125W-K](#) [15DYS602-120500W](#) [15DYS6150-4800312P](#) [33-704](#) [45-092](#) [45-121](#) [45-1513](#) [45-2020-1](#)