



Note:
To Remove mounting ring from bellows as supplied by inserting a 3.0Ø bar in one of the holes and twisting anti-clockwise through 41°. Mounting ring can be used as a template for drilling/tapping holes in mounting face.

Benefits

- ❖ Low profile easy to operate foot bellow
- ❖ For free standing applications or secured with a built in mounting plate

- ❖ Available as twin foot bellows (see 6447) and with convex top and base
- ❖ Base material - black rigid PVC, except double volume
- ❖ Bellow material - flexible PVC

6448 - - 0 0 0 0

1. Model Number

2. Tube Entry

- A Side Entry Tube, Flat Base with Mounting Ring
- B Side Entry Tube, Flat Base, no Mounting Ring
- C Back Entry 2mm Spout, Flat Base with Mounting Ring
- D Back Entry 2mm Spout, Flat base, no Mounting Ring
- E Side Entry Tube, Flexible Base (Double Volume)

3. Colour Option

- A Black
- B Grey
- C White
- D Red
- E Brown
- F Green

4. Tube Type

- A Black PVC Tubing with 3mm I/D and 6mm O/D
- B Clear PVC Tubing with 3mm I/D and 6mm O/D
- C Black PU Tube with 1.5mm I/D and 3mm O/D
- D Black PU Curly Coil with 1.5mm I/D and 3mm O/D (please select option 8G below)
- Z No Tubing required

5. Tube Length

- A 1.5 Metres
- B 2 Metres
- C 3 Metres
- D 4 Metres
- E 5 Metres
- F 6 Metres
- G Curly tube
- Z None supplied

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [herga manufacturer](#):

Other Similar products are found below :

[6433-0019](#) [6289-PP](#) [6254-OB](#) [6442-OW](#) [6438-ACAC-AB00](#) [6227-0004](#) [6289-01](#) [6251-BAAA-CBZ0](#) [6226-0003](#) [6438-ABAB-AB00](#) [6289-CC](#) [6753-AEJA-A000](#) [6448-AAAB-0000](#) [6871-0C](#)