# PRODUCT DATASHEET

# 2D ATEX **Energizer**

### **European Region**

### **Product Detail:**

**Designation:** Energizer

2D ATEX SAP: 638575

Colour: Safety Orange and Black

Power Source: Two "D" IEC: LR20

Lamp: One High Power LED

Lamp Life (hr): Lifetime

Light Output (lumens): 60 Run Time (h:min): 135 Beam Distance (m): 150 Peak Beam Intensity (cd): N/A

**Durability:** Survives 1-metre drop


Typical Weight: 162 grams

without batteries

**Dimensions (mm):** 201.4 x 50.8 x 64.8

### Performance: Run Time

Continuous Drain to End of Useable Light (21° C)



**Battery Type** 

Tested according to ANSI/NEMA FL 1 Standards.

### **Important Notice**

This datasheet contains information specific to products manufactured at the time of its publication Contents herein do not constitute a warranty ©Energizer / All Rights Reserved

# 638575

Approved by global safety agencies, the Energizer® 2D ATEX torch is ideal for work in harsh conditions. The light is waterproof, dustproof and survives a 1-

meter drop test.

A built-in carabiner belt clip makes for easy access, while the internationally approved orange safety color provides instant recognition. The White LED lamp supplies steady, bright illumination for about 68 hours between battery changes using Energizer<sub>®</sub> MAX<sup>®</sup> batteries.



Division 1, Class 1 rated

agencies for intrinsically

### **WATERPROOF**

safe lights

**INTRINSICALLY** 

Approved by global

SAFE

- Meets IEC 60529 IPX7 standards
- · Continues to operate after submersion in 1 meter of water for 30 minutes

### **IMPACT RESISTANT**

 Survives a 1-metre drop Shatterproof lens



FL1 STANDARD

1 m

L1 STANDARD

m

### **RELIABLE**

• 135 hour run time using Energizer<sub>®</sub> MAX<sup>®</sup> batteries



### UL/CUL intrinsic safety for hazardous locations Class I Div. 1 Groups A,B,C, & D, Class II Div. 1 Groups E,F,&G, and Class III Div. 1; T4. IM2/II1G

 ATEX intrinsically safe flashlight for EEx ia I/IIC T4

IECEx intrinsically safe flashlight for Ex ia IIC T4

-20°C to 40°C ambient operating range.

€0529 ingress protection level IP67.

### **Before Using Your Flashlight:**

Please read all instructions and cautionary markings on the package and light

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for energizer manufacturer:

Other Similar products are found below:

1215F2X3 E11A B2 LR43 186 AC13 AC675 3LR12 603298 625304 638006 639830 S9025 7638900426687 7638900414660 HARD CASE RECHARGEABLE HARD CASE PRO MULTI USE HCHD311 S9029 639826 603386 HARD CASE PROFF 4AA HARDCASE PRO HEADLIGHT 639618 RCLINM2WR S8865 S8707 S8100 7638900424478 7638900313130 626177 E300116200 E300280600 639838 HARDCASE PRO WORK LIGHT 603305 METAL LED 6AA S8864 HDD32E MS2AALED ENERGIZER® 2-IN-1 LANTERN HANDHELD E300124200 E300171700 ENFFL81E E300112600 633474 HDA32E 7638900421422 HARD CASE PRO PIVOT HCSP61E 7638900424485 HDC32E