

Acrylic Tape

2 Sided, Fabric, Precut

pro-POWER



Description:

A closely woven fabric coated on both sides with a high mass of a high tack modified acrylic adhesive.

Features:

- High tack adhesive bonds to most surface including metals, paints, foams, rubbers, plastics and textiles
- Balanced adhesion allows clean removal even after prolonged contact and on many plasticised materials
- Thick fabric is very conformable and easy to handle
- Good resistance to UV light and ageing
- Ideal for most temporary bonding applications

Specifications:

| | |
|-------------|-----------|
| Tape Type | : Sealing |
| Tape Width | : 25mm |
| Tape Length | : 12mm |
| Material | : Acrylic |

Technical Details:

| | |
|------------------------|------------------------|
| Thickness | : 0.31mm |
| Peel Adhesion @ 23°C | : 12N/25mm |
| Peel Adhesion @ 70°C | : 6N/25mm |
| Peel (AFERA) @ 23°C | : 6N/25mm ² |
| Peel (AFERA) @ 70°C | : 2N/25mm ² |
| Peel (PSTC) @ 23°C | : 0 hour |
| Peel (PSTC) @ 70°C | : 0 hour |
| Temperature Range | : -40°C to +100°C |
| Min. Application Temp. | : 5°C |

Part Number Table

| Description | Part Number |
|-------------------------------|---------------------|
| Tape, 2 Sided, Fabric, Precut | 431 PADS 0.25X12X25 |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)