






Miniature Through/Ground Conductor and Ex Terminal Blocks 2.5 mm² for DIN 15 Rail 264 Series

0.08 ... 2.5 mm ² 800 V/8 kV/3 ① I _N 24 A	AWG 28 ... 12 * 300 V, 20 A ② 600 V, 20 A ③	0.08 ... 2.5 mm ² 800 V/8 kV/3 ① I _N 24 A	AWG 28 ... 12 * 300 V, 20 A ② 600 V, 20 A ③
Terminal block width 6 mm / 0.236 in.  8 ... 9 mm / 0.33 in. ②		Terminal block width 10 mm / 0.394 in.  8 ... 9 mm / 0.33 in. ②	



- * AWG 12: THHN, THWN
- ① 800 V = rated voltage
8 kV = rated surge voltage
3 = pollution degree
(also see Section 14)
- ② Strip length, see packaging or instructions.
- ③ Suitable for Ex i applications
- ④ Suitable for Ex e II applications
0.5 mm² ... 2.5 mm²/AWG 20 ... 12*
690 V, 23 A
(also see Section 14)
- ⑤ See application notes for:
Test plug module, page 416
Alternate comb-style jumper bar, page 294

Item No.	Pack. Unit	Item No.	Pack. Unit	264 Series Accessories
2-conductor miniature through terminal block, for DIN 15 rail		4-conductor miniature through terminal block, for DIN 15 rail		Miniature WSB (see Section 13)
② gray 264-701	100	② gray 264-721	100	End and intermediate plate, 4 mm thick
③ blue 264-704	100	③ blue 264-724	100	orange 264-369 25
④ orange 264-706	100	④ orange 264-726	100	gray 264-368 25
⑤ light gray 264-120	100	⑤ light gray 264-220	100	light gray 264-370 25
Item-Specific Accessories		Item-Specific Accessories		Ex e/Ex i separator, orange, 4 mm thick
Alternate comb-style jumper bar, ⑤ insulated, I_N = I_N terminal block		Alternate comb-style jumper bar, ⑤ insulated, I_N = I_N terminal block		66 mm 264-367 25
2-way 281-492	100 (4x25)	2-way 280-492	200 (8x25)	Comb-style jumper bar, insulated, I_N 16 A, gray, reduces maximum conductor size to 1.5 mm²/AWG 16
Test plug module, ⑤ can be snapped together, 6 mm wide		Test plug module, ⑤ can be snapped together, 10 mm wide		2-way 264-402 200 (8x25)
gray 249-136	100 (4x25)	gray 249-139	100 (4x25)	Operating tool, of insulating material
				2-way 280-432 1
				Test plug,
				with 500 mm cable, 2 mm Ø red 210-136 50
				Test plug,
				with 500 mm cable, 2.3 mm Ø yellow 210-137 50
				Miniature WSB Quick marking system,
				10 strips with 10 markers per card, 5 mm wide markers plain 248-501 5
				Screwless end stop, for DIN 15 rail, 6 mm wide
				gray 249-101 25
				Steel carrier rail, acc. to EN 60715, 15 x 5.5 mm, 1 mm, 2 m/6'6" long slotted 210-111 1
				Steel carrier rail, acc. to EN 60715, 15 x 5.5 mm, 1 mm, 2 m/6'6" long unslotted 210-295 1
				Aluminum carrier rail, acc. to EN 60715, 15 x 5.5 mm, 1 mm, 2 m/6'6" long unslotted 210-296 10
				Operating tool, of insulating material
				1-way 209-130 1



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [wago manufacturer](#):

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [210-111](#) [231-303/037-000](#) [231-446/001-000_NR](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [0283-0671](#) [830-800/000-305](#) [750-512](#) [750-455](#) [51251782](#) [286-312](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [793-3505](#) [826-172](#) [859-304](#) [280-335](#) [231-535/001-000](#) [2604-1106](#) [2604-1504](#) [2606-1103/020-000](#) [2624-1103](#) [2626-3103/020-000](#) [821-104](#) [713-1107](#) [852-1411](#) [2106-1307](#) [2116-5307](#) [832-1205](#) [832-3604](#) [2009-110](#) [281-512/281-501](#) [286-336](#) [750-421](#) [750-838](#) [753-559](#) [750-1505](#) [787-732](#)