

# Fuse holder terminal blocks

## Double-deck

### for 5 x 20 and 5 x 25 mm fuses

### Screw clamp

DIN 1 - DIN 3



End stop		th. 9 mm	BADL	V0	1SNA 399 903 R0200
End stop		th. 10 mm	BAM2	V2	1SNA 206 351 R1600
End stop		th. 10 mm	BAM2 V0	V0	1SNA 296 351 R0000
Rail		35 x 7,5 x 1	PR3.Z2		1SNA 174 300 R1700
Rail		35 x 15 x 2,3	PR4		1SNA 168 500 R1200
Rail		35 x 15 x 1,5	PR5		1SNA 168 700 R2200
Rail		32 x 15 x 1,5	PR1.Z2		1SNA 163 050 R0400

Other end stops, rails and accessories : see section on accessories.

### Notes

The use of some accessories may decrease the block's voltage rating. For more information, consult us.

\* Blocks with LED indicator are labeled "+" on the outside of the lever. The indicator can be reversed in the field if required.




### Accessories

	1	End section	grey
	2	Test socket	
	3	Test plug	
	4	Assembled jumper bar (without IP 20 protection)	
	5	Connector plate	
	6	Comb-type jumper bar	
	7	IDC jumper	
	8	Assembly rod	
	9	Assembly ring	
	10	Fuse 5 x 20	250 V
		Fuse 5 x 25	250 V
		Fast acting HPC 1500 A	
	11	Disconnect link bar	
	12	Shield connector	

R See section on marking method

### M 4/8.D2.SF

Spacing 8 mm (.315")



Standard block.

Colour	Type	Part numbers	
Grey	<input type="checkbox"/> M 4/8.D2.SF	1SNA 115 604	R2100
Beige V0	<input type="checkbox"/> M 4/8.D2.SF.V0	1SNA 195 604	R2200


### Characteristics

Wire size		IEC	DIN	UL/CSA
Screw clamp	Solid wire	0,5-6 mm <sup>2</sup>		24-12 AWG
	Stranded wire	0,5-4 mm <sup>2</sup>		24-12 AWG

Voltage			
Rated	630 V (7)	300 V (1)	
Pulse	8 kV		
Pollution degree	3		
Current			
Rated	6,3 A	20 A	
Wire size			
Rated / Gauge	4 mm <sup>2</sup> / A4	12 AWG	
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
9,5 mm .37"	4 mm .16"	0,5-0,8 Nm 4.4-7.1 lb.in	IP 20 NEMA 1

### M 4/8.D2.SF...

Spacing 8 mm (.315")



M 4/8.D2.SF with fusion indicator.

Colour	Type	Part numbers	
Grey/LED 24/100 V (8)	<input type="checkbox"/> M 4/8.D2.SFD3	1SNA 115 936	R0300
Grey/Neon 110-230 V (5)	<input type="checkbox"/> M 4/8.D2.SFL	1SNA 115 646	R2200
Grey/LED 24 V (6)	<input type="checkbox"/> M 4/8.D2.SFD	1SNA 115 647	R2300
Grey/LED 48 V (6)	<input type="checkbox"/> M 4/8.D2.SFD1	1SNA 115 648	R0400

### Characteristics

Wire size		IEC	DIN	UL/CSA
Screw clamp	Solid wire	0,5-6 mm <sup>2</sup>		24-12 AWG
	Stranded wire	0,5-4 mm <sup>2</sup>		24-12 AWG

Voltage			
Rated	500 V (7)	300 V (1)	
Pulse	6 kV		
Pollution degree	3		
Current			
Rated	6,3 A	20 A	
Wire size			
Rated / Gauge	4 mm <sup>2</sup> / A4	12 AWG	
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
9,5 mm .37"	4 mm .16"	0,5-0,8 Nm 4.4-7.1 lb.in	IP 20 NEMA 1

Note: (1) Only for lower deck. (2) Only for upper connection. Use of these accessories requires the user to cut out the partition. (3) For block equipped with test socket AL2. (4) For block equipped with test socket AL4. (5) Leakage current with neon lamp : < 0,5 mA (110 VAC), < 0,7 mA (230 VAC). (6) Leakage current with LED 24 or 48 VDC < 4,5 mA. (7) Insulation voltage of terminal block - operating voltage : according to fuse. (8) Leakage current with LED 24 or 110 VDC : 0,5 mA at 24 V ; 2,2 mA at 110 V.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [entrelec](#) manufacturer:*

Other Similar products are found below :

[023000012](#) [023103024](#) [023000107](#) [1SNK505310R0000](#) [011762822](#) [016511417](#) [016340320](#) [1SNK516020R0000](#) [023300421](#)

[1SNK510010R0000](#) [018731214](#) [011870703](#) [010500220](#) [011511607](#) [023300227](#) [016049626](#) [017666704](#) [1SNK508411R0000](#) [023300320](#)

[023300001](#) [016548827](#) [012511813](#) [017301610](#) [011546820](#) [010500127](#)