

KM340



Type K, Differential Temperature Thermometer

- * Twin inputs, for all HVAC usage including flow and return temperature measurements and radiator output checks
- * Available in a kit with 2 x SK29M, 1 x SK21M, 1 x AK27M probes and carrying case, ref: KM340KIT
- * Displays temperature in °C or °F
- * 1° resolution
- * Maximum temperature memory, hold function to freeze displayed reading and a protective slip-on boot with desk stand
- * Sub-miniature connector

Sensor Type	Thermocouple Type K
Measurement Range	-50°C to +1300°C, -58°F to +1999°F
Scales	°C, °F
Resolution	1°
Accuracy at +23°C/+73°F	
-50°C to 0°C, -58°F to +32°F	+2,-1°C/+4,-2°F
0°C to 1100°C, +32°C to +1999°F	±(0.2% of reading +1°C/2°F)
Operating Temperature Range	0°C to +50°C, +32°F to +122°F
Connector Type	Sub-miniature
Battery Type	9V IEC 6LF22 alkaline
Battery Life	200 hours

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Comark](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)