



DESIGNER KNOBS



THE PRODUCT

Our TOP-KNOBS are incomparable in design and are thus the ideal solution for all users looking for that special something.

By selecting a marking element geared to the application, you define the function of the tuning knob and at the same time give your equipment a modern, contemporary appearance.

The invisible screw-type fixture gives your equipment a pleasing and modern appearance.

YOUR ADVANTAGE

Aesthetically pleasing knob design.

The fixing technique rules out any possibility of contact with live parts.

Functional marking elements, e.g. for fine calibration. Easy to fit.

In connection with rotary potentiometers, the arrangement of the axis is recessed in order to accommodate external nuts and to make sure that the knobs form an even line with the front panel.

Sizes (mm)


ø 16, ø 20, ø 24, ø 31, ø 40

Fastening

with lateral screw fixing on shaft ends according to DIN 41591























pinned onto the axes with flattened shaft ends ø 6/4.6 mm



detailed drawings see our website
www.okw.com



TOP-KNOB











TOP-KNOB for "shaft end" *1	Knob Ø	Dimensions in mm	Max. tightening torque	Borehole	Part-No.	
					nero	volcano
	16		0.4 Nm	4 mm	A 10 16 049	A 10 16 048
			0.4 Nm	6 mm	A 10 16 069	A 10 16 068
	20		0.5 Nm	4 mm	A 10 20 049	A 10 20 048
			0.5 Nm	6 mm	A 10 20 069	A 10 20 068
			0.5 Nm	1/4"	A 10 20 639	A 10 20 638
	24		0.6 Nm	4 mm	A 10 24 049	A 10 24 048
			0.6 Nm	6 mm	A 10 24 069	A 10 24 068
			0.6 Nm	1/4"	A 10 24 639	A 10 24 638
	31		0.6 Nm	4 mm	A 10 31 049	A 10 31 048
			0.6 Nm	6 mm	A 10 31 069	A 10 31 068
			0.6 Nm	1/4"	A 10 31 639	A 10 31 638
	40		0.65 Nm	4 mm	A 10 40 049	A 10 40 048
			0.65 Nm	6 mm	A 10 40 069	A 10 40 068
			0.65 Nm	1/4"	A 10 40 639	A 10 40 638
TOP-KNOB for "flattened end" *2	Knob Ø	Dimensions in mm	Borehole		Part-No.	
					nero	volcano
	16		6/4.6 mm		A 10 16 649	A 10 16 648
	20		6/4.6 mm		A 10 20 649	A 10 20 648
	24		6/4.6 mm		A 10 24 649	A 10 24 648
	31		6/4.6 mm		A 10 31 649	A 10 31 648
	40		6/4.6 mm		A 10 40 649	A 10 40 648

*1 lateral screw fixing with hex-socket set screw (1.5 mm) and annular cutting edge

*2 pinned onto the axes with flattened shaft ends



MARKING ELEMENTS

		Pin	Arrow	Globe	Disk	Wing
For TOP-KNOB ø 16 – 40						
Simple push-on marking elements, subsequent replacement is also possible.	Colour					
		A 11 01 003	A 11 05 003			A 11 04 003
		A 11 01 004	A 11 05 004	A 11 02 004	A 11 03 004	
		A 11 01 005	A 11 05 005			
		A 11 01 006	A 11 05 006			
		A 11 01 007	A 11 05 007	A 11 02 007	A 11 03 007	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Knobs & Dials](#) category:

Click to view products by [OKW ENCLOSURES](#) manufacturer:

Other Similar products are found below :

[61-9028.20](#) [61-9028.9](#) [8529](#) [8573](#) [9-1437622-4](#) [11K5015-EMNB](#) [11K5019-ECNB](#) [11K5020-KLAB](#) [11K5028-JMNG](#) [11K5048-KMNB](#)
[11K5014-EMNB](#) [11K5015-EMNG](#) [11K5019-EMNB](#) [11K5029-KMNG](#) [P400S-08-D6-N](#) [K6510](#) [KNSL500B1/8](#) [AL811BA18](#) [420031B18](#)
[5006](#) [KB700BA1/4](#) [KS700B14](#) [411](#) [4-1437621-3](#) [420065A14AL](#) [5149A](#) [028-1-11](#) [52-928.20](#) [52-928.60](#) [52-928.9](#) [8517](#) [8546](#) [8570](#) [8572](#)
[H-516-3A](#) [P861H-0X-S6](#) [8544](#) [11K5014-JMNG](#) [11K5014-KMNG](#) [11K5014-ECNG](#) [5700E](#) [KA500B18](#) [KFS600B14](#) [KN900AB14](#)
[KFS500B14](#) [KNS501B18](#) [PKD60B1018](#) [PK1100B18](#) [PKES140B14](#) [PKES150B14](#)