



Main

| | |
|---------------------------|---|
| Range of product | Phaseo Universal |
| Product or component type | Safety and isolation transformer type |
| Rated power in VA | 40 VA |
| Input voltage | 230 V AC single phase , terminal(s): N-L1 400 V AC phase to phase , terminal(s): L1-L2 |
| Output voltage | 24/48 V AC |
| Secondary winding | Double |
| Protective cover | With |

Complementary

| | |
|-----------------------------------|--|
| Input voltage limits | 207...253 V 360...440 V |
| Network frequency limits | 47...63 Hz |
| Input voltage tolerance | +/- 15 V |
| Efficiency | 79 % |
| Power dissipation in W | 10.6 W |
| Voltage variation at nominal load | 6.16 % at 230 V 6.5 % at 400 V |
| Output sustained overvoltage | 2.4 % (no load, hot state) |
| Voltage drop at rated load | 6 % |
| No load losses | 6.73 W |
| Short-circuit voltage | 10.60 % |
| Output protection type | Against overload , protection technology: external Against overvoltage , protection technology: external Against short-circuits , protection technology: external |
| Connections - terminals | Screw type terminals for input connection , connection capacity: 5 x 4 mm ² AWG gauge11 Screw type terminals for input ground connection , connection capacity: 1 x 4 mm ² AWG gauge11 Screw type terminals for output connection , connection capacity: 4 x 4 mm ² AWG gauge11 |
| Marking | CE |
| Fixing mode | By 4 screws , screw(s) # = 5.5 mm on vertical panel , operating position: vertical By 4 screws , screw(s) # = 5.5 mm on vertical panel , operating position: horizontal By 4 screws , screw(s) # = 5.5 mm on horizontal panel with derating to 90 % By clips on 35 x 15 mm symmetrical DIN rail |
| Output coupling | Grounding of secondary Parallel Series by internal jumper |
| Electrical insulation class | Class B |
| Status LED | 1 LED orange for input voltage |
| Product weight | 1.4 kg |

Environment

| | |
|--|--|
| Product certifications | ENEC CURus |
| IP degree of protection | IP20 conforming to EN/IEC 60529 |
| Ambient air temperature for operation | -20...60 °C |
| Ambient air temperature for storage | -40...80 °C |
| Relative humidity | 0...95 % during operation |
| Class of protection against electric shock | Class I conforming to VDE 0106-1 |
| Dielectric strength | 3200 V between input and ground 3200 V between output and ground 5100 V between input and output |
| RoHS EUR conformity date | 0501 |
| RoHS EUR status | Compliant |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [schneider manufacturer](#):

Other Similar products are found below :

[LU9M1](#) [7D](#) [7S](#) [7XA1](#) [FNQR2](#) [8501RS44V24](#) [8501RSD14P14V51](#) [8501XO20V03Y414](#) [9001KXRK](#) [9001SKR9P35RH25](#) [9001SKT35L31](#)
[9003K2C003GA](#) [9007AA1](#) [9007BA1](#) [9007C54D](#) [9007C62A2](#) [9007CA11](#) [9007FA3](#) [9007HA4](#) [9007HA6](#) [9007KA1](#) [9007KB11](#)
[9007MS01S0206](#) [9007MS02S0300](#) [9012GAR4](#) [9012GAW2](#) [9012GBW1](#) [9012GDW5E3](#) [9012GFW1](#) [9012GNG1](#) [9012GNG3](#) [9012GNG6](#)
[9013FHG39J69](#) [9013GHG2J30](#) [9050JCK2F30V14](#) [GV2ME04](#) [GV2ME10](#) [GV2ME14](#) [GV2ME20](#) [GV2ME32](#) [GV2P06](#) [GV2P08](#) [GV2P10](#)
[GV2P16](#) [GV2P20](#) [GV2P21](#) [GV2RT07](#) [GV2RT21](#) [GVAD1001](#) [GVAN11](#)