

This document was generated on 12/08/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 1201148022 | | | |
|---|---|--|--|----------------|
| | | | | |
| Status: Active | | | | |
| Overview: | Brad® Micro-Change® (M | | _ | |
| | | olded Junction Box, Top Mount, 4 Poles/8 Ports, LEDs for | | |
| | PNP sensors, with Molded PUR Cable, 5.0m Length | | | |
| | | | | |
| Documents: | | | 1.27 | |
| Drawing (PDF) | | Packaging Specification 1922-00000-00005 (PDF) | | |
| Product Specification PS-120005-001 (PDF) | | RoHS Certificate of Compliance (PDF) | | |
| | х <i>Г</i> | | - | |
| General | | | Series image - | Reference only |
| Product Family | | Passive Distribution Boxes | | |
| Series | | 120114 | EU ELV | |
| IP Rating | | IP68 | Not Relevant | |
| NEMA Rating | | NEMA 6 | Not Relevant | |
| Overview | | Brad® Micro-Change® (M12) Connectors | EU RoHS | China RoHS |
| Product Name | | Micro-Change® (M12) | Compliant/Exempted | |
| UPC | | 883906408121 | REACH SVHC | |
| | | 003300400121 | Yes -ED/108/2014 (17 | |
| Physical | | | Dec 2014) | |
| Bus I/O | | Micro-Change® (M12) | Halogen-Free | |
| Cable Connector Orientation | | Straight | Status | |
| Cable Length | | 5.0m | Not Low-Halogen | |
| Home Run Cable Length | | 5.0m | Need more information on product | |
| Home Run Connector | | N/A | environmental compliance? | |
| Home Run Interface | | N/A | environmentar compi | |
| Keyway | | Single | Email productcompliance@molex.com | |
| LED Indicator | | Yes | Please visit the <u>Contact Us</u> section for any | |
| Material - Cable Jacket | | PUR | non-product compliance | |
| Material - Housing | | PBT | | |
| Material - Metal | | Copper Alloy | | 50 Image |
| Material - Plating Mating | | Gold over Nickel | ELV | Not Relevant |
| Net Weight | | 1000.000/g | | |
| Orientation | | Top Mount | | |
| Poles | | 4 | Search Parts in this | Sorios |
| Poles (wired) | | 4 | <u>120114</u> Series | 5 Genes |
| Ports | | 8 | | |
| Temperature Range - Operating | | ∘ -5°C to +90°C | | |
| Wiring Configuration | | Single I/O per Port | | |
| | ווכ | | | |
| Electrical | | | | |
| Current - Maximum per Contact | | 12.0A per module, 4.0A per port | | |
| Functional Wiring | | PNP | | |
| Voltage - Maximum | | 10-30V DC | | |
| Ŭ | | | | |
| Material Info | | | | |
| Old Part Number | | BTY800P-FBP-05 | | |
| Reference - Draw | ing Numbers | | | |
| Packaging Specific | - | 1922-00000-00005 | | |
| Product Specification | | PS-120005-001 | | |
| Sales Drawing | | SD-120005-011 | | |
| | | | | |
| | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Air Quality Sensors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 GMS-MSTH2.S.V.3
 MO86571
 MO86561
 595001074420009
 076074 01
 DE800.A.1
 MF010-2-LC1
 MF020-2-LC3
 KGZ10-5PIN

 GMS10SENSORS
 IR25TT
 208280-0001
 LIS3MDL 3-AXIS MAGNETOMETER CARRIER
 SS-BME280#I2C
 SS-BMP280#I2C
 SS

 CCS811#I2C
 SS-HDC2010+CCS811#I2C
 SS-HDC2010#I2C
 GMS10-18C
 KGZ12
 INIR-RF-R32
 MODBUS-RS485

 114991728
 114991732
 COLORPAL
 MR003-001.2
 MIKROE-1628
 SEN0162
 T6713-6H
 FXTH8709026T1
 POLOLU-1482
 MF010-0-LC4

 MF010-0-LC3
 ELECDIT.V.1
 GP2Y0D02YK0F
 803P602
 ZS-510-B
 1201148022
 1201190004
 1201148023
 DE800.V.1
 D5VM-3P1
 E3X

 MC11
 EE-SPZ301
 XS5FD421G80A
 SGAS701
 SGAS711
 HPMA115S0-XXX
 T3032-2-5K-24-P